



QUBE™

Direct Burial LED Driver

The Next Generation of Rugged, Exterior Lighting



Dimensions 8" X 8" X 7"

IP68 / NEMA 6P/ Compact Direct Burial

Four 96W Class 2 Outputs, ELV Dimmable to 0.1%

UL Listed, CA Title 24 JA8 Approved, Made in USA

Resources

[⬇ Voltage Drop](#)

[⬇ Zero Dim](#)

[🔗 Compatibility](#)

[🔗 JA8 T24 Listing](#)

May 2019 Qube Launch



LightFair May 21-23 2019
Launch Party May 22 2019

Qube Compatibility

[Data Sheet](#) | [Visit our System Builder](#) for all Product Compatibilities | [Find a Representative](#)



Learn More

System Package

System Specification

Light Engines

9524-FR ≤ 1,100 Lm/ft.

9524-FR

1524-LE ≤ 427 Lm/ft.

1524 LE

8924-LE ≤ 463 Lm/ft.

8924 LE

4924-LE ≤ 236 Lm/ft.

4924 LE

3924-LE ≤ 116 Lm/ft.

3924 LE

Housing

AT401 Narrow, Shallow

AT401

AT402 Narrow

AT402

AT801 Standard

AT801

AT802 Deep

AT802

AT845 45° Asymmetric

AT845

Grazer

AT402-G

MT Series Compact, Low Profile

MT101

SkyTrack Linear Pendant

ST850

WR Type Flexible Linear

WR Type

Controllers

DMX AX5-1

AX5-1

3rd Party Controls

MLV DC Blue Series

3rd Party Dimmer List

Lutron A Series

D40-A | D100-A