

Home / Products / Valves / Valves / Globe / LIN-E-AIRE™

## LIN-E-AIRE® Pneumatic Valve Actuator

Ideal for Steam and Water Flow Control, Low Flow Options



SHARE

Lin-E-Aire® Valve Actuators offer the ultimate in precision diaphragm motor control. These actuators are available in either air-to-lower or air-to-raise types. Both types feature easily accessible spring compression nuts permitting easy range change and adjustment.

These actuators employ molded Buna-N rubber diaphragms reinforced with nylon, for resilient, easy valve action. No more than 10% of the diaphragm area is lost during a full stroke of the actuator, thereby imparting a practically constant force throughout the length of the stroke.

Ordering | Specifications | Support Library | Drawings | Videos | Related Products | Photo Downloads | Reviews

### Models & Ordering

Sort by Model Number

Model	Description	Usually Ships*	Price	Order
155620	Pneumatic valve actuator, air-to-lower, 1" (25.4 mm) travel max., Ae <sup>3</sup> 20 in. <sup>2</sup> (129 cm <sup>2</sup> ), 100 psi (7.0 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,006.00	<a href="#">Order</a>
155621	Pneumatic valve actuator, air-to-lower, 1" (25.4 mm) travel max., Ae <sup>3</sup> 45 in. <sup>2</sup> (290 cm <sup>2</sup> ), 50 psi (3.5 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,279.00	<a href="#">Order</a>
155623	Pneumatic valve actuator, air-to-lower, 1-1/2" (38.1 mm) travel max., Ae <sup>3</sup> 80 in. <sup>2</sup> (516 cm <sup>2</sup> ), 50 psi (3.5 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,784.00	<a href="#">Order</a>
155630	Pneumatic valve actuator, air-to-raise, 1" (25.4 mm) travel max., Ae <sup>3</sup> 20 in. <sup>2</sup> (129 cm <sup>2</sup> ), 100 psi (7.0 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,006.00	<a href="#">Order</a>
155631	Pneumatic valve actuator, air-to-raise, 1" (25.4 mm) travel max., Ae <sup>3</sup> 45 in. <sup>2</sup> (290 cm <sup>2</sup> ), 50 psi (3.5 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,243.00	<a href="#">Order</a>
155633	Pneumatic valve actuator, air-to-raise, 1-1/2" (38.1 mm) travel max., Ae <sup>3</sup> 80 in. <sup>2</sup> (516 cm <sup>2</sup> ), 50 psi (3.5 kg/cm <sup>2</sup> ) P max.	1-2 Weeks*	\$1,784.00	<a href="#">Order</a>

#### Divisions

Love®  
Mercoïd®  
W.E. Anderson®  
Proximity®

#### Markets

Building Automation  
Powder & Bulk  
Water & Wastewater  
Valve Automation  
HVAC

#### Our Company

History of Dwyer  
What's New  
Digital Catalog  
Free Literature  
Careers  
Mobile Apps  
Contact Us  
Hours of Business

#### Support

FAQ  
Agency Approval Certificates  
Catalog Pages  
Instruction Manuals  
Safety Data Sheets  
Calibration & Certificate Services  
Website Feedback  
Website Survey

#### Policies

Policies, Terms, Etc.  
Global Trade Compliance  
Environmental Policies  
Sales Tax  
MAP Policy