



(19) **United States**

(12) **Patent Application Publication**

Erbey, II et al.

(10) **Pub. No.: US 2020/0237975 A1**

(43) **Pub. Date: Jul. 30, 2020**

(54) **METHOD OF REMOVING EXCESS FLUID FROM A PATIENT WITH VENOUS CONGESTION**

A61M 25/00 (2006.01)

A61M 25/04 (2006.01)

A61M 25/02 (2006.01)

(71) Applicant: **Strataca Systems Limited**, Floriana (MT)

(52) **U.S. Cl.**

CPC ... *A61M 1/0037* (2013.01); *A61M 2210/1085* (2013.01); *A61M 1/008* (2013.01); *A61M 25/1025* (2013.01); *A61M 39/12* (2013.01); *A61M 1/0025* (2014.02); *A61M 25/0026* (2013.01); *A61M 1/0031* (2013.01); *A61M 25/0023* (2013.01); *A61M 1/0035* (2014.02); *A61M 25/04* (2013.01); *A61M 25/0017* (2013.01); *A61M 2230/50* (2013.01); *A61M 2230/00* (2013.01); *A61M 2230/65* (2013.01); *A61M 2210/1082* (2013.01); *A61M 2230/207* (2013.01); *A61M 2025/0213* (2013.01); *A61M 2210/1089* (2013.01); *A61M 2205/52* (2013.01); *A61M 2202/0496* (2013.01); *A61M 2205/3368* (2013.01); *A61M 1/0066* (2013.01)

(72) Inventors: **John R. Erbey, II**, Milton, GA (US); **Jacob L. Upperco**, Atlanta, GA (US); **Michael Alan Fisher**, Lawrenceville, GA (US); **Patrick William Strane**, Atlanta, GA (US); **Lance Michael Black**, Pearland, TX (US); **David E. Orr**, Piedmont, SC (US)

(21) Appl. No.: **16/850,052**

(22) Filed: **Apr. 16, 2020**

Related U.S. Application Data

(60) Continuation of application No. 16/670,249, filed on Oct. 31, 2019, which is a division of application No. 15/411,884, filed on Jan. 20, 2017, now Pat. No. 10,512,713, which is a continuation-in-part of application No. 15/214,955, filed on Jul. 20, 2016, now Pat. No. 10,307,564.

(60) Provisional application No. 62/300,025, filed on Feb. 25, 2016, provisional application No. 62/278,721, filed on Jan. 14, 2016, provisional application No. 62/260,966, filed on Nov. 30, 2015, provisional application No. 62/194,585, filed on Jul. 20, 2015.

Publication Classification

(51) **Int. Cl.**

A61M 1/00 (2006.01)


A61M 25/10 (2013.01)

A61M 39/12 (2006.01)

(57)

ABSTRACT

A method for increasing urine output rate from a patient having venous congestion is provided. The method includes: deploying a urinary catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter; applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient; periodically measuring an edema value of the patient; and if the measured edema value is less than or equal to Grade 1 in which the depth of indentation is less than about 2 mm after about 10 seconds, ceasing the application of the negative pressure to the ureter and/or kidney.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3E

FIG. 3D

FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A






FIG. 5B






FIG. 8




FIG. 9A






FIG. 9B






FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B




FIG. 19




FIG. 20A




FIG. 20B




FIG. 21




FIG. 22




FIG. 23A




FIG. 23B



FIG. 23C




FIG. 23D




FIG. 24




FIG. 25




FIG. 26

METHOD OF REMOVING EXCESS FLUID FROM A PATIENT WITH VENOUS CONGESTION

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 16/670,249, filed Oct. 31, 2019, which is a divisional of U.S. patent application Ser. No. 15/411,884, filed Jan. 20, 2017, now issued as U.S. Pat. No. 10,512,713, which is continuation-in-part of U.S. patent application Ser. No. 15/214,955 filed Jul. 20, 2016, now issued as U.S. Pat. No. 10,307,564, which claims the benefit of U.S. Provisional Application No. 62/300,025 filed Feb. 25, 2016, U.S. Provisional Application No. 62/278,721, filed Jan. 14, 2016, U.S. Provisional Application No. 62/260,966 filed Nov. 30, 2015, and U.S. Provisional Application No. 62/194,585, filed Jul. 20, 2015, each of which is hereby incorporated by reference in their entireties.

BACKGROUND

Technical Field

[0002] The present disclosure relates to methods and devices for treating impaired renal function across a variety of disease states and, in particular, to catheter devices, assemblies, and methods for collection of urine and/or inducement of negative pressure in the ureters and/or kidneys.

Background

[0003] The renal or urinary system includes a pair of kidneys, each kidney being connected by a ureter to the bladder, and a urethra for draining urine produced by the kidneys from the bladder. The kidneys perform several vital functions for the human body including, for example, filtering the blood to eliminate waste in the form of urine. The kidneys also regulate electrolytes (e.g., sodium, potassium and calcium) and metabolites, blood volume, blood pressure, blood pH, fluid volume, production of red blood cells, and bone metabolism. Adequate understanding of the anatomy and physiology of the kidneys is useful for understanding the impact that altered hemodynamics other fluid overload conditions have on their function.

[0004] In normal anatomy, the two kidneys are located retroperitoneally in the abdominal cavity. The kidneys are bean-shaped encapsulated organs. Urine is formed by nephrons, the functional unit of the kidney, and then flows through a system of converging tubules called collecting ducts. The collecting ducts join together to form minor calyces, then major calyces, which ultimately join near the concave portion of the kidney (renal pelvis). A major function of the renal pelvis is to direct urine flow to the ureter. Urine flows from the renal pelvis into the ureter, a tube-like structure that carries the urine from the kidneys into the bladder. The outer layer of the kidney is called the cortex, and is a rigid fibrous encapsulation. The interior of the kidney is called the medulla. The medulla structures are arranged in pyramids.

[0005] Each kidney is made up of approximately one million nephrons. Each nephron includes the glomerulus, Bowman's capsule, and tubules. The tubules include the proximal convoluted tubule, the loop of Henle, the distal

convoluted tubule, and the collecting duct. The nephrons contained in the cortex layer of the kidney are distinct from the anatomy of those contained in the medulla. The principal difference is the length of the loop of Henle. Medullary nephrons contain a longer loop of Henle, which, under normal circumstances, allows greater regulation of water and sodium reabsorption than in the cortex nephrons.

[0006] The glomerulus is the beginning of the nephron, and is responsible for the initial filtration of blood. Afferent arterioles pass blood into the glomerular capillaries, where hydrostatic pressure pushes water and solutes into Bowman's capsule. Net filtration pressure is expressed as the hydrostatic pressure in the afferent arteriole minus the hydrostatic pressure in Bowman's space minus the osmotic pressure in the efferent arteriole.

$$\text{Net Filtration Pressure} = \text{Hydrostatic Pressure (Afferent Arteriole)} - \text{Hydrostatic Pressure (Bowman's Space)} - \text{Osmotic Pressure (Efferent Arteriole)} \quad (\text{Equation 1})$$

[0007] The magnitude of this net filtration pressure defined by Equation 1 determines how much ultra-filtrate is formed in Bowman's space and delivered to the tubules. The remaining blood exits the glomerulus via the efferent arteriole. Normal glomerular filtration, or delivery of ultra-filtrate into the tubules, is about 90 ml/min/1.73 m².

[0008] The glomerulus has a three-layer filtration structure, which includes the vascular endothelium, a glomerular basement membrane, and podocytes. Normally, large proteins such as albumin and red blood cells, are not filtered into Bowman's space. However, elevated glomerular pressures and mesangial expansion create surface area changes on the basement membrane and larger fenestrations between the podocytes allowing larger proteins to pass into Bowman's space.

[0009] Ultra-filtrate collected in Bowman's space is delivered first to the proximal convoluted tubule. Re-absorption and secretion of water and solutes in the tubules is performed by a mix of active transport channels and passive pressure gradients. The proximal convoluted tubules normally reabsorb a majority of the sodium chloride and water, and nearly all glucose and amino acids that were filtered by the glomerulus. The loop of Henle has two components that are designed to concentrate wastes in the urine. The descending limb is highly water permeable and reabsorbs most of the remaining water. The ascending limb reabsorbs 25% of the remaining sodium chloride, creating a concentrated urine, for example, in terms of urea and creatinine. The distal convoluted tubule normally reabsorbs a small proportion of sodium chloride, and the osmotic gradient creates conditions for the water to follow.

[0010] Under normal conditions, there is a net filtration of approximately 14 mmHg. The impact of venous congestion can be a significant decrease in net filtration, down to approximately 4 mmHg. See Jessup M., *The cardiorenal syndrome: Do we need a change of strategy or a change of tactics?*, *JACC* 53(7):597-600, 2009 (hereinafter "Jessup"). The second filtration stage occurs at the proximal tubules. Most of the secretion and absorption from urine occurs in tubules in the medullary nephrons. Active transport of sodium from the tubule into the interstitial space initiates this process. However, the hydrostatic forces dominate the net exchange of solutes and water. Under normal circumstances, it is believed that 75% of the sodium is reabsorbed back into lymphatic or venous circulation. However, because the kidney is encapsulated, it is sensitive to changes

in hydrostatic pressures from both venous and lymphatic congestion. During venous congestion the retention of sodium and water can exceed 85%, further perpetuating the renal congestion. See Verbrugge et al., *The kidney in congestive heart failure: Are natriuresis, sodium, and diuretics really the good, the bad and the ugly? European Journal of Heart Failure* 2014;16,133-42 (hereinafter "Verbrugge").

[0011] Venous congestion can lead to a prerenal form of acute kidney injury (AKI). Prerenal AKI is due to a loss of perfusion (or loss of blood flow) through the kidney. Many clinicians focus on the lack of flow into the kidney due to shock. However, there is also evidence that a lack of blood flow out of the organ due to venous congestion can be a clinically important sustaining injury. See Damman K, *Importance of venous congestion for worsening renal function in advanced decompensated heart failure, JACC* 17:589-96, 2009 (hereinafter "Damman").

[0012] Prerenal AKI occurs across a wide variety of diagnoses requiring critical care admissions. The most prominent admissions are for sepsis and Acute Decompensated Heart Failure (ADHF). Additional admissions include cardiovascular surgery, general surgery, cirrhosis, trauma, burns, and pancreatitis. While there is wide clinical variability in the presentation of these disease states, a common denominator is an elevated central venous pressure. In the case of ADHF, the elevated central venous pressure caused by heart failure leads to pulmonary edema, and, subsequently, dyspnea in turn precipitating the admission. In the case of sepsis, the elevated central venous pressure is largely a result of aggressive fluid resuscitation. Whether the primary insult was low perfusion due to hypovolemia or sodium and fluid retention, the sustaining injury is the venous congestion resulting in inadequate perfusion.

[0013] Hypertension is another widely recognized state that creates perturbations within the active and passive transport systems of the kidney(s). Hypertension directly impacts afferent arteriole pressure and results in a proportional increase in net filtration pressure within the glomerulus. The increased filtration fraction also elevates the peritubular capillary pressure, which stimulates sodium and water re-absorption. See Verbrugge.

[0014] Because the kidney is an encapsulated organ, it is sensitive to pressure changes in the medullary pyramids. The elevated renal venous pressure creates congestion that leads to a rise in the interstitial pressures. The elevated interstitial pressures exert forces upon both the glomerulus and tubules. See Verbrugge. In the glomerulus, the elevated interstitial pressures directly oppose filtration. The increased pressures increase the interstitial fluid, thereby increasing the hydrostatic pressures in the interstitial fluid and peritubular capillaries in the medulla of the kidney. In both instances, hypoxia can ensue leading to cellular injury and further loss of perfusion. The net result is a further exacerbation of the sodium and water re-absorption creating a negative feedback. See Verbrugge, 133-42. Fluid overload, particularly in the abdominal cavity is associated with many diseases and conditions, including elevated intra-abdominal pressure, abdominal compartment syndrome, and acute renal failure. Fluid overload can be addressed through renal replacement therapy. See Peters, C. D., *Short and Long-Term Effects of the Angiotensin II Receptor Blocker Irbesartan on Intradiastolic Central Hemodynamics: A Randomized Double-Blind Placebo-Controlled One-Year Intervention Trial (the SAFIR Study)*, PLoS ONE (2015) 10(6): e0126882. doi:10.1371/

journal.pone.0126882 (hereinafter "Peters"). However, such a clinical strategy provides no improvement in renal function for patients with the cardiorenal syndrome. See Bart B, *Ultrafiltration in decompensated heart failure with cardiorenal syndrome, NEJM* 2012; 367:2296-2304 (hereinafter "Bart").

[0015] In view of such problematic effects of fluid retention, devices and methods for improving removal of urine from the urinary tract and, specifically for increasing quantity and quality of urine output from the kidneys, are needed.

SUMMARY

[0016] In some examples, a method for removing excess fluid from a patient with hemodilution is provided. The method includes: deploying a urinary tract catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter; applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient; periodically measuring a hematocrit value of the patient; and if the measured hematocrit value is greater than a predetermined threshold value, ceasing the application of the negative pressure to the ureter and/or kidney.

[0017] In other examples, a method for removing excess fluid from a patient with hemodilution includes: deploying a urinary tract catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter; applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient; periodically measuring the patient's weight; and if the measured weight is less than a predetermined threshold value, ceasing the application of the negative pressure to the urinary tract.

[0018] In some examples, a system for removing excess fluid from a patient with hemodilution is provided. The system includes a urinary tract catheter and a pump. The urinary tract catheter includes a drainage lumen portion having a proximal end, a distal end configured to be positioned in a patient's urinary tract, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter of the drainage lumen portion. At least one of the drainage lumen portion or the retention portion has at least one drainage port to permit fluid flow into the drainage lumen. The pump is in fluid communication with a drainage lumen defined by the drainage lumen portion of the ureteral catheter. The pump includes a controller configured to: actuate the pump to cause the pump to induce a negative pressure in a ureter and/or kidney of the patient to draw urine through the drainage lumen of the urinary tract catheter, periodically receive information representative of a hematocrit value of the patient; and if the received hematocrit value exceeds a predetermined minimum threshold value, ceasing the application of the negative pressure to the ureter and/or kidney.

[0019] In some examples, ureteral catheters are provided comprising: a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, wherein the retention portion

comprises at least a first coil having a first diameter and a second coil having a second diameter, the first diameter being less than the second diameter.

[0020] In some examples, a urine collection assembly is provided comprising: at least one ureteral catheter comprising: a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, wherein the retention portion comprises at least a first coil having a first diameter and a second coil having a second diameter, the first diameter being less than the second diameter; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to essentially or fully seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0021] In some examples, a ureteral catheter is provided comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outwardly from a portion of the distal end of the drainage lumen portion, the retention portion comprising a proximal end having a first diameter, a distal end having a second diameter, and a wall and/or surface extending therebetween, the retention portion being configured to be extended into a deployed position in which the second diameter is greater than the first diameter.

[0022] In some examples, a urine collection assembly is provided comprising: at least one ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outwardly from a portion of the distal end of the drainage lumen portion, the retention portion comprising a proximal end having a first diameter, a distal end having a second diameter, and a wall and/or surface extending therebetween, the retention portion being configured to be extended into a deployed position in which the second diameter is greater than the first diameter; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0023] In some examples, a ureteral catheter is provided comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween, the drainage lumen portion defining a drainage lumen; and a retention portion which, in a deployed position, extends radially outwardly from a portion of the distal end of the

drainage lumen portion, the retention portion comprising a plurality of tubes extending between a proximal end of the retention portion and a distal end of the retention portion, wherein each tube defines a lumen in fluid communication with the drainage lumen defined by the drainage lumen portion and wherein each tube comprises a plurality of drainage ports for allowing fluid to enter the lumen.

[0024] In some examples, a urine collection assembly is provided comprising: at least one ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween, the drainage lumen portion defining a drainage lumen; and a retention portion which, in a deployed position, extends radially outward from a portion of the distal end of the drainage lumen portion, the retention portion comprising a plurality of tubes extending between a proximal end of the retention portion and a distal end of the retention portion, wherein each tube defines a lumen in fluid communication with the drainage lumen defined by the drainage lumen portion and wherein each tube comprises a plurality of drainage ports for allowing fluid to enter the lumen; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0025] In some examples, a connector is provided for connecting ureteral catheters configured to be positioned at a patient's ureter and/or kidney to a vacuum source for inducing negative pressure in the ureter and/or kidney and for connecting a bladder catheter to a fluid collection container for fluid collection of urine from the bladder by gravity drainage, the connector comprising: a connector body; first and second ureteral catheter inflow ports extending from the connector body, the inflow ports each being configured to be connected to a ureteral catheter positioned in a patient's ureter and/or kidney; a ureteral catheter outflow port in fluid communication with each inflow port and being configured to be connected to a pump for inducing negative pressure in the respective ureteral catheters; a gravity drainage inflow port configured to be connected to a bladder catheter; and a gravity drainage outflow port in fluid communication with the bladder catheter inflow port and being configured to be connected to a fluid collection container.

[0026] In some examples, a urine collection assembly is provided comprising: a first ureteral catheter configured to be positioned in a patient's ureter and/or kidney and a second ureteral catheter configured to be positioned in the patient's other ureter and/or kidney, the ureteral catheters each comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter

of the drainage lumen portion, wherein at least one of the drainage lumen portion or the retention portion comprises at least one drainage port to permit fluid flow into the drainage lumen; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0027] In some examples, a bladder catheter is provided for deployment within the patient's bladder for collecting excess urine not collected by deployed ureteral catheters positioned in the patient's ureter and/or kidney, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end portion, a distal end portion configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen for expelling urine from the bladder.

[0028] In some examples, a system is provided for inducing negative pressure in a portion of a urinary tract of a patient, the system comprising: a ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter of the drainage lumen portion, wherein at least one of the drainage lumen portion or the retention portion comprises at least one drainage port to permit fluid flow into the drainage lumen; and a pump in fluid communication with a drainage lumen defined by the drainage lumen portion of the ureteral catheter, the pump being configured for inducing a negative pressure in a portion of the urinary tract of the patient to draw fluid through the drainage lumen of the ureteral catheter.

[0029] Methods of using the above catheters and assemblies also are provided.

[0030] In some examples, a method is provided for extracting urine from a ureter and/or kidney of a patient for effecting interstitial pressure in the kidney, the method comprising: positioning a distal end of a catheter at a fluid collection position within a patient's ureter and/or kidney, the catheter comprising a tube defining a drainage lumen and comprising a helical retention portion and a plurality of drainage ports; inducing a negative pressure within a drainage lumen of the catheter; and extracting urine by drawing urine through the drainage ports into the drainage lumen, thereby altering interstitial pressure within the patient's kidney.

[0031] In some examples, a method is provided for inhibiting kidney damage by application of negative pressure to decrease interstitial pressure within tubules of the medullar

region to facilitate urine output and to prevent venous congestion-induced nephron hypoxia in the medulla of the kidney, the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney by the deployed catheter; and applying negative pressure to the ureter and/or kidney through the catheter for a predetermined period of time to facilitate urine output from the kidney.

[0032] In some examples, a method is provided for treatment of acute kidney injury due to venous congestion, the method comprising: deploying a ureteral catheter at a fluid collection position in the ureter and/or kidney of a patient such that the ureter and/or kidney is not occluded by the deployed catheter; and applying negative pressure to the ureter and/or kidney through the catheter for a predetermined period of time, thereby reducing venous congestion in the kidney to treat acute kidney injury.

[0033] In some examples, a method is provided for treatment of New York Heart Association (NYHA) Class III and/or Class IV heart failure through reduction of venous congestion in the kidney(s), the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney; and applying negative pressure to the ureter and/or kidney through the catheter for a predetermined period of time to treat volume overload in NYHA Class III and/or Class IV heart failure.

[0034] In some examples, a method is provided for treatment of Stage 4 and/or Stage 5 chronic kidney disease through reduction of venous congestion in the kidney(s), the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney; and applying negative pressure to the ureter and/or kidney through the catheter for a predetermined period of time to treat Stage 4 and/or Stage 5 chronic kidney disease.

[0035] Non-limiting examples, aspects or embodiments of the present invention will now be described in the following numbered clauses:

[0036] Clause 1: A ureteral catheter comprising: a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, wherein the retention portion comprises at least a first coil having a first diameter and a second coil having a second diameter, the first diameter being less than the second diameter.

[0037] Clause 2: The ureteral catheter of clause 1, wherein the first coil is proximal to the second coil.

[0038] Clause 3: The ureteral catheter of any of clause 1 or clause 2, wherein, prior to insertion into a patient's urinary tract, a portion of the drainage lumen that is proximal to the retention portion defines a straight or curvilinear central axis, and wherein the first coil and the second coil of the retention portion extend about an axis that is at least partially coextensive with the straight or curvilinear central axis of the portion of the drainage lumen.

[0039] Clause 4: The ureteral catheter of clause 1 or clause 2, wherein, prior to insertion to the patient's urinary tract, a portion of the drainage lumen that is proximal to the

retention portion defines a straight or curvilinear central axis, and wherein the first coil and the second coil of the retention portion extend about an axis that is essentially coextensive with the straight or curvilinear central axis of the portion of the drainage lumen.

[0040] Clause 5: The ureteral catheter of clause 3 or clause 4, wherein the axis of the retention portion is curved relative to the central axis of the drainage lumen.

[0041] Clause 6: The ureteral catheter of any of clauses 1 to 5, wherein a portion of the drainage lumen that is proximal to the retention portion defines a straight or curvilinear central axis, and wherein the first coil and the second coil of the retention portion extend about an axis of the retention portion, the axis of the retention portion being positioned at an angle from the central axis ranging from about 15 degrees to about 75 degrees.

[0042] Clause 7: The ureteral catheter of any of clauses 1 to 6, wherein the catheter is transitionable between a contracted configuration for insertion into the patient's ureter and a deployed configuration for deployment within the ureter.

[0043] Clause 8: The ureteral catheter of any of clauses 1 to 7, wherein the retention portion further comprises a third coil, the third coil having a diameter greater than or equal to either the first diameter or the second diameter.

[0044] Clause 9: The ureteral catheter of any of clauses 1 to 8, wherein the retention portion comprises a tube comprising perforations for permitting fluid to be received within the lumen of the tube.

[0045] Clause 10: The ureteral catheter of clause 9, wherein, in the retention portion, the tube comprises a radially inwardly facing side and a radially outwardly facing side, and wherein a total surface area for perforations on the radially inwardly facing side is greater than a total surface area of perforations on the radially outwardly facing side.

[0046] Clause 11: The ureteral catheter of clause 9, wherein, in the retention portion, the tube comprises a radially inwardly facing side and a radially outwardly facing side, and wherein the perforations are disposed on the radially inwardly facing side, and wherein the radially outwardly facing side of the tube is essentially free of perforations.

[0047] Clause 12: The ureteral catheter of clause 11, wherein the radially outwardly facing side of the tube is free of perforations.

[0048] Clause 13: The ureteral catheter of any of clauses 1 to 12, wherein the tube is formed, at least in part, from one or more of copper, silver, gold, nickel-titanium alloy, stainless steel, titanium, polyurethane, polyvinyl chloride, polytetrafluoroethylene (PTFE), latex, and silicone.

[0049] Clause 14: A urine collection assembly comprising: at least one ureteral catheter comprising: a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, wherein the retention portion comprises at least a first coil having a first diameter and a second coil having a second diameter, the first diameter being less than the second diameter; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebe-

tween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to essentially or fully seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0050] Clause 15: The assembly of clause 14, wherein the drainage lumen portion of the at least one ureteral catheter is removably received through the drainage port of the bladder catheter, such that the proximal end of the at least one ureteral catheter is disposed within the drainage lumen of the bladder catheter.

[0051] Clause 16: The assembly of any of clauses 14 or 15, wherein the deployable anchor portion of the bladder catheter comprises an inflatable element or balloon in fluid communication with an inflation lumen defined by the drainage lumen portion of the bladder catheter.

[0052] Clause 17: The assembly of any of clauses 14 to 16, wherein the at least one drainage port is disposed on a sidewall of the bladder catheter at a position proximal to the deployable anchor portion.

[0053] Clause 18: The assembly of any of clauses 14 to 17, wherein the deployable anchor portion comprises an expandable cage comprising a plurality of flexible members extending radially and longitudinally from the drainage lumen portion of the bladder catheter.

[0054] Clause 19: The assembly of any of clauses 14 to 18, wherein the deployable anchor portion comprises a plurality of longitudinally extending members that, in a deployed position, extend radially and longitudinally outwardly from a portion of the distal end of the bladder catheter, thereby forming a cage.

[0055] Clause 20: The assembly of clause 18, wherein the deployable anchor further comprises a flexible cover extending about an upper portion of the cage.

[0056] Clause 21: The assembly of clause 20, wherein the cover extends over at least about the upper half, or at about least the upper $\frac{2}{3}$, of the cage.

[0057] Clause 22: The assembly of any of clauses 14 to 21, wherein the drainage lumen of the at least one ureteral catheter is separate from the drainage lumen of the bladder along an entire length of the catheters.

[0058] Clause 23: A ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outwardly from a portion of the distal end of the drainage lumen portion, the retention portion comprising a proximal end having a first diameter, a distal end having a second diameter, and a wall and/or surface extending therebetween, the retention portion being configured to be extended into a deployed position in which the second diameter is greater than the first diameter.

[0059] Clause 24: The ureteral catheter of clause 23, wherein the retention portion comprises an expandable element or balloon in fluid communication with an inflation lumen extending along the drainage lumen portion.

[0060] Clause 25: The ureteral catheter of clause 23 or clause 24, wherein the retention portion comprises a coiled tube extending from the distal end of the drainage lumen portion, the tube defining a lumen in fluid communication with the drainage lumen defined by the drainage lumen portion.

[0061] Clause 26: The ureteral catheter of any of clauses 23 to 25, wherein the coiled tube comprises perforations extending through a sidewall of the tube for permitting fluid to be received within the lumen.

[0062] Clause 27: The ureteral catheter of clause 26, wherein the perforations are disposed on a radially inwardly facing portion of the tube, and wherein an opposing radially outwardly facing portion of the tube is essentially free of perforations.

[0063] Clause 28: The ureteral catheter of clause 27, wherein the opposing radially outwardly facing portion of the tube is free of perforations.

[0064] Clause 29: The ureteral catheter of any of clauses 23 to 28, wherein the drainage lumen portion and the retention portion are formed, at least in part, from one or more of copper, silver, gold, nickel-titanium alloy, stainless steel, titanium, polyurethane, polyvinyl chloride, polytetrafluoroethylene (PTFE), latex, and silicone.

[0065] Clause 30: The ureteral catheter of clause 23, wherein the retention portion comprises a wedge or funnel-shaped extension formed from a compressible and/or porous material.

[0066] Clause 31: The ureteral catheter of any of clauses 23 to 30, wherein the retention portion is integrally formed with the drainage lumen portion.

[0067] Clause 32: The ureteral catheter of any of clauses 23 to 31, wherein the retention portion further comprises a tapered inner surface configured to direct fluid towards the drainage lumen defined by the drainage lumen portion.

[0068] Clause 33: The ureteral catheter of any of clauses 23 to 32, wherein the drainage lumen of the catheter is configured to be pressurized to a negative pressure for fluid collection from the ureter and/or kidney.

[0069] Clause 34: A urine collection assembly comprising: at least one ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outwardly from a portion of the distal end of the drainage lumen portion, the retention portion comprising a proximal end having a first diameter, a distal end having a second diameter, and a wall and/or surface extending therebetween, the retention portion being configured to be extended into a deployed position in which the second diameter is greater than the first diameter; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0070] Clause 35: The assembly of clause 34, wherein the drainage lumen portion of the at least one ureteral catheter is removably received through the drainage port of the bladder catheter, such that the proximal end of the at least one ureteral catheter is disposed within the drainage lumen of the bladder catheter.

[0071] Clause 36: The assembly of clause 34 or clause 35, wherein the deployable anchor portion of the bladder catheter comprises an inflatable element or balloon in fluid

communication with an inflation lumen defined by the drainage lumen portion of the bladder catheter.

[0072] Clause 37: The assembly of any of clauses 34 to 36, wherein the at least one drainage port is disposed on a sidewall of the bladder catheter at a position proximal to the deployable anchor portion.

[0073] Clause 38: The assembly of clause 34, wherein the deployable anchor portion comprises an expandable cage comprising a plurality of flexible members extending radially and longitudinally from the drainage lumen portion of the bladder catheter.

[0074] Clause 39: The assembly of clause 34, wherein the deployable anchor portion comprises a plurality of longitudinally extending members that, in a deployed position, extend radially and longitudinally outward from a portion of the distal end of the bladder catheter, thereby forming a cage.

[0075] Clause 40: The assembly of clause 38 or clause 39, wherein the deployable anchor further comprises a flexible cover extending about an upper portion of the cage.

[0076] Clause 41: The assembly of clause 40, wherein the cover extends over at least about the upper half, or at least about the upper $\frac{2}{3}$, of the cage.

[0077] Clause 42: A ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween, the drainage lumen portion defining a drainage lumen; and a retention portion which, in a deployed position, extends radially outwardly from a portion of the distal end of the drainage lumen portion, the retention portion comprising a plurality of tubes extending between a proximal end of the retention portion and a distal end of the retention portion, wherein each tube defines a lumen in fluid communication with the drainage lumen defined by the drainage lumen portion and wherein each tube comprises a plurality of drainage ports for allowing fluid to enter the lumen.

[0078] Clause 43: The ureteral catheter of clause 42, wherein each tube comprises a radially inwardly facing side and a radially outwardly facing side, and wherein the drainage ports are disposed on the radially inwardly facing side of each tube.

[0079] Clause 44: The ureteral catheter of clause 43, wherein the radially outwardly facing side of each tube is essentially free of drainage ports.

[0080] Clause 45: The ureteral catheter of clause 43, wherein the radially outwardly facing side of each tube is free of drainage ports.

[0081] Clause 46: The ureteral catheter of any of clauses 42 to 45, wherein the retention portion is transitionable from a contracted position, in which each of the plurality of tubes is substantially parallel to a longitudinal axis of the drainage lumen portion and the deployed position in which portions of the tubes extend radially outwardly from the drainage lumen portion.

[0082] Clause 47: The ureteral catheter of any of clauses 42 to 46, wherein in the deployed position the tubes define a spherical or ellipsoidal cavity, and wherein the drainage lumen portion extends at least partially into the cavity.

[0083] Clause 48: The ureteral catheter of any of clauses 42 to 47, wherein the drainage lumen portion and the retention portion are formed, at least in part, from one or more of copper, silver, gold, nickel-titanium alloy, stainless steel, titanium, polyurethane, polyvinyl chloride, polytetrafluoroethylene (PTFE), latex, and silicone.

[0084] Clause 49: The ureteral catheter of any of clauses 42 to 48, wherein the retention portion is integrally formed with the drainage lumen portion.

[0085] Clause 50: The ureteral catheter of any of clauses 42 to 49, wherein the drainage lumen of the catheter is configured to be pressurized to a negative pressure for fluid collection from the ureter and/or kidney.

[0086] Clause 51: A urine collection assembly comprising: at least one ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween, the drainage lumen portion defining a drainage lumen; and a retention portion which, in a deployed position, extends radially outward from a portion of the distal end of the drainage lumen portion, the retention portion comprising a plurality of tubes extending between a proximal end of the retention portion and a distal end of the retention portion, wherein each tube defines a lumen in fluid communication with the drainage lumen defined by the drainage lumen portion and wherein each tube comprises a plurality of drainage ports for allowing fluid to enter the lumen; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening of the bladder, wherein the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0087] Clause 52: The assembly of clause 51, wherein the drainage lumen portion of the at least one ureteral catheter is removably received through the drainage port of the bladder catheter, such that the proximal end of the at least one ureteral catheter is disposed within the drainage lumen of the bladder catheter.

[0088] Clause 53: The assembly of clause 51 or clause 52, wherein the deployable anchor portion of the bladder catheter comprises an inflatable element or balloon in fluid communication with an inflation lumen defined by the drainage lumen portion of the bladder catheter.

[0089] Clause 54: The assembly of any of clauses 51 to 53, wherein the at least one drainage port is disposed on a sidewall of the bladder catheter at a position proximal to the deployable anchor portion.

[0090] Clause 55: The assembly of clause 51 or clause 52, wherein the deployable anchor portion comprises an expandable cage comprising a plurality of flexible members extending radially and longitudinally from the drainage lumen portion of the bladder catheter.

[0091] Clause 56: The assembly of clause 51 or clause 52, wherein the deployable anchor portion comprises a plurality of longitudinally extending members that, in a deployed position, extend radially and longitudinally outward from a portion of the distal end of the bladder catheter, thereby forming a cage.

[0092] Clause 57: The assembly of clause 55 or clause 56, wherein the deployable anchor further comprises a flexible cover extending about an upper portion of the cage.

[0093] Clause 58: The assembly of clause 57, wherein the cover extends over at least about the upper half, or about the upper $\frac{2}{3}$, of the cage.

[0094] Clause 59: A connector for connecting ureteral catheters configured to be positioned at a patient's ureter and/or kidney to a vacuum source for inducing negative pressure in the ureter and/or kidney and for connecting a bladder catheter to a fluid collection container for fluid collection of urine from the bladder by gravity drainage, the connector comprising: a connector body; first and second ureteral catheter inflow ports extending from the connector body, the inflow ports each being configured to be connected to a ureteral catheter positioned in a patient's ureter and/or kidney; a ureteral catheter outflow port in fluid communication with each inflow port and being configured to be connected to a pump for inducing negative pressure in the respective ureteral catheters; a gravity drainage inflow port configured to be connected to the bladder catheter; and a gravity drainage outflow port in fluid communication with the bladder catheter inflow port and being configured to be connected to a fluid collection container.

[0095] Clause 60: The connector of clause 59, wherein the connector body defines a fluid conduit extending from the at least two ureteral catheter inflow ports to the single ureteral catheter outflow port.

[0096] Clause 61: The connector of clause 59 or clause 60, wherein the inflow ports are configured to removably receive ends of the respective catheters.

[0097] Clause 62: The connector of any of clauses 59 to 61, wherein the vacuum outflow port and the gravity drainage outflow port are positioned for connection to a single socket for establishing fluid connection with the pump and fluid connection container.

[0098] Clause 63: A urine collection assembly comprising: a first ureteral catheter configured to be positioned in a patient's ureter and/or kidney and a second ureteral catheter configured to be positioned in the patient's other ureter and/or kidney, the ureteral catheters each comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter of the drainage lumen portion, wherein at least one of the drainage lumen portion or the retention portion comprises at least one drainage port to permit fluid flow into the drainage lumen; and a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen.

[0099] Clause 64: The assembly of clause 63, further comprising a connector for connecting proximal ends of the ureteral catheters to a vacuum source and for connecting the proximal end of the bladder catheter to a fluid collection container for fluid collection by gravity drainage.

[0100] Clause 65: The assembly of clause 64, wherein the connector comprises: at least two ureteral catheter inflow ports for connection to the respective proximal ends of the

first ureteral catheter and the second ureteral catheter; a ureteral catheter outflow port in fluid communication with each inflow port and being configured to be connected to a pump for inducing negative pressure in the respective ureteral catheters; a gravity drainage inflow port configured to be connected to the proximal end of the bladder catheter; and an outflow port in fluid communication with the bladder catheter inflow port and being configured to be connected to a fluid collection container.

[0101] Clause 66: The assembly of clause 65, wherein the connector further comprises conduit extending from the at least two ureteral catheter inflow ports to the single ureteral catheter outflow port.

[0102] Clause 67: The assembly of clause 65 or clause 66, wherein the proximal ends of the respective catheters are removably connected to their respective inflow ports.

[0103] Clause 68: The assembly of any clauses 63 to 67, wherein the deployable anchor portion of the bladder catheter comprises an inflatable element or balloon in fluid communication with an inflation lumen defined by the drainage lumen portion of the bladder catheter.

[0104] Clause 69: The assembly of clause 63, wherein the deployable anchor portion comprises an expandable cage comprising a plurality of flexible members extending radially and longitudinally from the drainage lumen portion of the bladder catheter and a cover enclosing at least a portion of the cage.

[0105] Clause 70: The assembly of clause 68 or clause 69, wherein the deployable anchor further comprises a flexible cover extending about an upper portion of the cage.

[0106] Clause 71: The assembly of clause 70, wherein the cover extends over at least about the upper half, or at least about the upper $\frac{2}{3}$, of the cage.

[0107] Clause 72: A bladder catheter for deployment within the patient's bladder for collecting excess urine not collected by deployed ureteral catheters positioned in the patient's ureter and/or kidney, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end portion, a distal end portion configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen for expelling urine from the bladder.

[0108] Clause 73: The bladder catheter of clause 72, wherein the deployable anchor portion comprises an inflatable element or balloon in fluid communication with an inflation lumen defined by the drainage lumen portion of the bladder catheter.

[0109] Clause 74: The bladder catheter of clause 73, wherein the inflatable element or balloon comprises an upper portion configured to be positioned in the patient's bladder and a lower portion configured to be positioned in the patient's urethra.

[0110] Clause 75: The bladder catheter of any of clauses 62 to 74, wherein the at least one drainage port is disposed on a sidewall of the bladder catheter at a position proximal to the anchor portion.

[0111] Clause 76: The bladder catheter of clause 72, wherein the deployable anchor portion comprises an expandable cage comprising a plurality of flexible members extending radially and longitudinally from the drainage

lumen portion of the bladder catheter and a cover enclosing at least a portion of the cage.

[0112] Clause 77: The bladder catheter of clause 76, wherein the deployable anchor portion further comprises a flexible cover extending about an upper portion of the cage.

[0113] Clause 78: The bladder catheter of clause 77, wherein the cover extends over at least about the upper half, or at least about the upper $\frac{2}{3}$, of the cage.

[0114] Clause 79: A system for inducing negative pressure in a portion of a urinary tract of a patient, the system comprising: a ureteral catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's ureter and/or kidney, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter of the drainage lumen portion, wherein at least one of the drainage lumen portion or the retention portion comprises at least one drainage port to permit fluid flow into the drainage lumen; and a pump in fluid communication with a drainage lumen defined by the drainage lumen portion of the ureteral catheter, the pump being configured for inducing a negative pressure in a portion of the urinary tract of the patient to draw fluid through the drainage lumen of the ureteral catheter.

[0115] Clause 80: The system of clause 79, further comprising: a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen for expelling urine from the bladder.

[0116] Clause 81: The system of clause 80, further comprising an external fluid collection container in fluid communication with the drainage lumen of the bladder catheter for gravity drainage of fluid through the bladder catheter.

[0117] Clause 82: The system of any of clauses 79 to 81, further comprising one or more sensors in fluid communication with the drainage lumen, the one or more sensors being configured to determine information comprising at least one of capacitance, analyte concentration, and temperature of urine within the respective drainage lumen; and a processor comprising computer readable memory including programming instructions that, when executed, cause the processor to: receive the information from the one or more sensors and adjust an operating parameter of the pump based, at least in part, on the information received from the one or more sensors to increase or decrease vacuum pressure in the drainage lumen of the at least one ureteral catheter to adjust flow of urine through the drainage lumen.

[0118] Clause 83: The system of clause 82, further comprising a data transmitter in communication with the processor, the data transmitter being configured to provide the information from the one or more sensors to an external source.

[0119] Clause 84: The system of any of clauses 80 to 83, wherein the pump provides a sensitivity of 10 mmHg or less.

[0120] Clause 85: The system of any of clauses 80 to 84, wherein the pump is capable of continuous operation for a time period ranging from about 8 to about 24 hours per day.

[0121] Clause 86: The system of any of clauses 80 to 85, wherein the pump is configured to provide intermittent negative pressure.

[0122] Clause 87: The system of any of clauses 80 to 86, wherein the pump is configured to apply negative pressure independently to each catheter such that the pressure in each catheter can be the same or different from the other catheter(s).

[0123] Clause 88: The system of any of clauses 80 to 86, wherein the pump is configured to alternate between providing negative pressure and providing positive pressure.

[0124] Clause 89: The system of any of clauses 80 to 86, wherein the pump is configured to alternate between providing negative pressure and equalizing pressure to atmosphere.

[0125] Clause 90: The system of clause 88, wherein the negative pressure is provided within a range of 5 mmHg to 50 mmHg, and/or wherein the positive pressure is provided within a range of 5 mmHg to 20 mmHg.

[0126] Clause 91: The system of any of clauses 80 to 90, wherein the pump is configured to alternate between two or more different pressure levels.

[0127] Clause 92: The system of clause 91, wherein the pump is configured to adjust the pressure levels at a regular or irregular frequency based, at least in part, on a predetermined algorithm.

[0128] Clause 93: The system of clause 92, wherein the predetermined algorithm is based in part on demographic data and/or patient-specific variables.

[0129] Clause 94: The system of clause 93, wherein the demographic data and/or patient-specific variables comprise one or more of anatomical, genetic, physiological, and pathophysiological factors.

[0130] Clause 95: The system of clause 92, wherein the predetermined algorithm is based, in part, on continuously or non-continuously changing patient values, the patient values comprising one or more of urine output rate, peristaltic activity of renal and/or urological system, heart rate, cardiac output, blood pressure, respiration rate, renal blood flow, renal plasma flow, and biomarkers.

[0131] Clause 96: A method for extracting urine from a ureter and/or kidney of a patient for effecting interstitial pressure in the kidney, the method comprising: positioning a distal end of a catheter at a fluid collection position within a patient's ureter and/or kidney, the catheter comprising a tube defining a drainage lumen and comprising a helical retention portion and a plurality of drainage ports; inducing a negative pressure within a drainage lumen of the catheter; and extracting urine by drawing urine through the drainage ports into the drainage lumen, thereby altering interstitial pressure within the patient's kidney.

[0132] Clause 97: The method of clause 96, wherein positioning the catheter comprises deploying the catheter by expanding the helical retention portion at the fluid collection position.

[0133] Clause 98: The method of clause 96 or clause 97, further comprising positioning a distal end of the bladder catheter in the patient's bladder and deploying an anchor within the bladder, such that the anchor essentially or fully seals the urethral sphincter of the bladder.

[0134] Clause 99: The method of clause 98, wherein positioning the bladder catheter in the bladder comprises advancing the bladder catheter over a guidewire used for positioning of the ureteral catheter.

[0135] Clause 100: A method of inhibiting kidney damage by application of negative pressure to decrease interstitial pressure within tubules of the medullar region to facilitate urine output and to prevent venous congestion-induced nephron hypoxia in the medulla of the kidney, the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney by the deployed catheter; and applying negative pressure to the ureter and/or kidney through the catheter for a period of time sufficient to facilitate urine output from the kidney.

[0136] Clause 101: The method of clause 100, further comprising positioning a bladder catheter in the patient's bladder, such that an anchor of the bladder catheter essentially or fully seals the urethral sphincter of the bladder.

[0137] Clause 102: The method of clause 101, further comprising causing drainage of urine from the bladder through the bladder catheter for a period of time.

[0138] Clause 103: The method of clause 100, wherein deploying the catheter comprises accessing the ureter and/or kidney through an incision or orifice other than the urethral orifice.

[0139] Clause 104: A method for treatment of acute kidney injury due to venous congestion, the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney; and applying negative pressure to the ureter and/or kidney through the catheter for a period of time sufficient to treat acute kidney injury due to venous congestion.

[0140] Clause 105: A method for treatment of NYHA Class III and/or Class IV heart failure through reduction of venous congestion in the kidney(s), the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney; and applying negative pressure to the ureter and/or kidney through the catheter for a period of time sufficient to treat NYHA Class III and/or Class IV heart failure.

[0141] Clause 106: A method for treatment of NYHA Class II, Class III, and/or Class IV heart failure through reduction of venous congestion in the kidney(s), the method comprising: deploying a catheter in a bladder of a patient such that flow of urine into the bladder from a ureter and/or kidney is not prevented by occlusion; and applying negative pressure to the bladder through the catheter for a period of time sufficient to treat NYHA Class II, Class III, and/or Class IV heart failure.

[0142] Clause 107: A method for treatment of Stage 4 and/or Stage 5 chronic kidney disease through reduction of venous congestion in the kidney(s), the method comprising: deploying a ureteral catheter in a ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney; and applying negative pressure to the ureter and/or kidney through the catheter for a period of time sufficient to treat Stage 4 and/or Stage 5 chronic kidney disease.

[0143] Clause 108: A method for treatment of Stage 3, Stage 4, and/or Stage 5 chronic kidney disease through

reduction of venous congestion in the kidney(s), the method comprising: deploying a catheter in a bladder of a patient such that flow of urine from a ureter and/or kidney is not prevented by occlusion; and applying negative pressure to the bladder through the catheter for a period of time sufficient to treat Stage 3, Stage 4, and/or Stage 5 chronic kidney disease.

[0144] Clause 109: A ureteral catheter, comprising: a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, the coiled retention portion comprising: at least a first coil having a first diameter; at least a second coil having a second diameter, the first diameter being less than the second diameter; and one or more perforations on a sidewall of the drainage lumen for permitting fluid flow into the drainage lumen, wherein, prior to insertion into a patient's urinary tract, a portion of the drainage lumen that is proximal to the retention portion defines a straight or curvilinear central axis, and wherein, when deployed, the first coil and the second coil of the retention portion extend about an axis of the retention portion that is at least partially coextensive with the straight or curvilinear central axis of the portion of the drainage lumen.

[0145] Clause 110: The ureteral catheter of clause 109, wherein the axis of the retention portion is curved relative to the central axis of the drainage lumen.

[0146] Clause 111: The ureteral catheter of clause 109 or clause 110, wherein at least a portion of the axis of the retention portion extends at an angle from the central axis ranging from about 15 degrees to about 75 degrees.

[0147] Clauses 112: The ureteral catheter of any of clauses 109 to 111, wherein the catheter is transitionable between a contracted configuration for insertion into the patient's ureter and a deployed configuration for deployment within the ureter.

[0148] Clause 113: The ureteral catheter of any of clauses 109 to 112, wherein the retention portion further comprises a third coil extending about the axis of the retention portion, the third coil having a diameter greater than or equal to either the first diameter or the second diameter.

[0149] Clause 114: The ureteral catheter of any of clauses 109 to 113, wherein, the retention portion of the drainage lumen comprises a sidewall comprising a radially inwardly facing side and a radially outwardly facing side, and wherein a total surface area of perforations on the radially inwardly facing side is greater than a total surface area of perforations on the radially outwardly facing side.

[0150] Clause 115: The ureteral catheter of any of clauses 109 to 114, wherein, the retention portion of the drainage lumen comprises a sidewall comprising a radially inwardly facing side and a radially outwardly facing side, and wherein the one or more perforations are disposed on the radially inwardly facing side, and wherein the radially outwardly facing side is essentially free of perforations.

[0151] Clause 116: The ureteral catheter of any of clauses 109 to 116, wherein the drainage lumen is formed, at least in part, from one or more of copper, silver, gold, nickel-titanium alloy, stainless steel, titanium, polyurethane, polyvinyl chloride, polytetrafluoroethylene (PTFE), latex, and silicone.

[0152] Clause 117: The ureteral catheter of any of clauses 109 to 116, wherein the retention portion of the drainage

lumen further comprises an open distal end for permitting fluid flow into the drainage lumen.

[0153] Clause 118: The ureteral catheter of any of clauses 109 to 117, wherein each of the one or more perforations has a diameter of about 0.7 to 0.9 mm.

[0154] Clause 119: The ureteral catheter of any of clauses 109 to 118, wherein the first diameter is about 8 mm to 10 mm and the second diameter is about 16 mm to 20 mm.

[0155] Clause 120: A system for inducing negative pressure in a portion of a urinary tract of a patient, the system comprising: at least one urine collection catheter comprising a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, the coiled retention portion comprising: at least a first coil having a first diameter; at least a second coil having a second diameter, the first diameter being less than the second diameter; and one or more perforations on a sidewall of the drainage lumen for permitting fluid flow into the drainage lumen, wherein, prior to insertion into a patient's urinary tract, a portion of the drainage lumen that is proximal to the retention portion defines a straight or curvilinear central axis, and wherein, when deployed, the first coil and the second coil of the retention portion extend about an axis of the retention portion that is at least partially coextensive with the straight or curvilinear central axis of the portion of the drainage lumen; and a pump in fluid communication with the drainage lumen of the at least one ureteral catheter, the pump being configured for inducing a negative pressure in a portion of the urinary tract of the patient to draw fluid through the drainage lumen of the ureteral catheter.

[0156] Clause 121: The system of clause 120, further comprising: one or more sensors in fluid communication with the drainage lumen, the one or more sensors being configured to determine information comprising at least one of capacitance, analyte concentration, and temperature of urine within the respective drainage lumen; and a controller comprising computer readable memory including programming instructions that, when executed, cause the controller to: receive the information from the one or more sensors and adjust an operating parameter of the pump based, at least in part, on the information received from the one or more sensors to increase or decrease vacuum pressure in the drainage lumen of the at least one ureteral catheter to adjust flow of urine through the drainage lumen.

[0157] Clause 122: The system of clause 120 or clause 121, further comprising a data transmitter in communication with the controller, the data transmitter being configured to provide the information from the one or more sensors to an external source.

[0158] Clause 123: The system of any of clauses 120 to 122, wherein the pump provides a sensitivity of 10 mmHg or less.

[0159] Clause 124: The system of any of clauses 120 to 122, wherein the pump is configured to alternate between providing negative pressure and providing positive pressure.

[0160] Clause 125: The system of clause 124, wherein the negative pressure is provided within a range of 5 mmHg to 50 mmHg, and wherein the positive pressure is provided within a range of 5 mmHg to 20 mmHg.

[0161] Clause 126: A method of inhibiting kidney damage by application of negative pressure to decrease interstitial

pressure within tubules of the medullar region to facilitate urine output and to prevent venous congestion-induced nephron hypoxia in the medulla of the kidney, the method comprising: deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney by the deployed catheter; and applying negative pressure to the ureter and/or kidney through the catheter for a period of time sufficient to facilitate urine output from the kidney, wherein the ureteral catheter comprises a drainage lumen comprising a proximal portion configured to be positioned in at least a portion of a patient's urethra and a distal portion configured to be positioned in a patient's ureter and/or kidney, the distal portion comprising a coiled retention portion, the coiled retention portion comprising: at least a first coil having a first diameter; at least a second coil having a second diameter, the first diameter being less than the second diameter; and one or more perforations on a sidewall of the drainage lumen for permitting fluid flow into the drainage lumen, wherein, prior to deployment, a portion of the drainage lumen that is proximal to the retention portion defines a straight or curvilinear central axis, and wherein, upon deployment, the first coil and the second coil of the retention portion extend about an axis of the retention portion that is at least partially coextensive with the straight or curvilinear central axis of the portion of the drainage lumen.

[0162] Clause 127: The method of clause 126, further comprising, upon application of negative pressure to the ureter and/or kidney, extracting urine by drawing urine through the one or more perforations into the drainage lumen, thereby altering interstitial pressure within the patient's kidney.

[0163] Clause 128: The method of clause 126 or clause 127, wherein application of negative pressure to the ureter and/or kidney through the catheter is provided for a period of time sufficient to treat acute kidney injury due to venous congestion.

[0164] Clause 129: A method for removing excess fluid from a patient with hemodilution, the method comprising: deploying a urinary tract catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter; applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient; periodically measuring a hematocrit value of the patient; and if the measured hematocrit value exceeds a predetermined minimum threshold value, ceasing the application of the negative pressure to the ureter and/or kidney.

[0165] Clause 130: The method of clause 129, wherein the urinary tract catheter comprises a ureteral catheter comprising a tube defining a drainage lumen and comprising a helical retention portion comprising a helical arrangement with multiple coils when deployed and a plurality of drainage ports.

[0166] Clause 131: The method of clause 130, wherein deploying the ureteral catheter comprises expanding the helical retention portion at a fluid collection position in the renal pelvis of the patient's kidney.

[0167] Clause 132: The method of clause 130 or clause 131, further comprising deploying a bladder catheter in the patient's bladder for receiving urine which passes through the ureter and enters the bladder.

[0168] Clause 133: The method of clause 132, wherein a proximal portion of the ureteral catheter is positioned within a drainage lumen of the bladder catheter.

[0169] Clause 134: The method of clause 132 or clause 133, wherein the bladder catheter comprises a seal for sealing an opening to the urethra for preventing passage of urine from the bladder to the urethra outside of the drainage lumen of the bladder catheter.

[0170] Clause 135: The method of any of clause 129 to 134, wherein the urinary tract catheter is introduced to one or the patient's bladder, ureter, and kidney through the urethra of the patient.

[0171] Clause 136: The method of any of clauses 129 to 135, further comprising collecting fluid extracted from the patient through the urinary tract catheter to determine a total volume of extracted fluid.

[0172] Clause 137: The method of clause 136, further comprising ceasing application of negative pressure when the determined total volume of extracted fluid exceeds a predetermined fluid volume.

[0173] Clause 138: The method of clause 137, wherein the predetermined value is based on an amount of fluid provided to a patient during a fluid resuscitation procedure.

[0174] Clause 139: The method of any of clauses 129 to 138, wherein the excess fluid is provided to the patient during a fluid resuscitation procedure performed for the patient.

[0175] Clause 140: The method of clause 139 wherein removing excess fluid from the patient is provided as one of a treatment for systemic fluid volume management associated with acute heart failure and as a treatment is provided to the patient during a coronary graft bypass procedure.

[0176] Clause 141: The method of any of clauses 129 to 140, wherein the predetermined hematocrit value is between 25% and 45%.

[0177] Clause 142: A method for removing excess fluid from a patient with hemodilution, the method comprising: deploying a urinary tract catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter; applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient; periodically measuring the patient's weight; and if the measured weight is less than a predetermined threshold value, ceasing the application of the negative pressure to the urinary tract.

[0178] Clause 143: The method of clause 142, wherein the urinary tract catheter comprises a ureteral catheter comprising a tube defining a drainage lumen and comprising a helical retention portion and a plurality of drainage ports.

[0179] Clause 144: The method of clause 143, wherein deploying the ureteral catheter comprises expanding the helical retention portion at a fluid collection position within the patient's ureter and/or kidney.

[0180] Clause 144: The method of clause 143, wherein the ureteral catheter is introduced to the patient's ureter and/or kidney through the urethra and bladder of the patient.

[0181] Clause 145: The method of clause 143, wherein the predetermined threshold value is a dry weight of the patient.

[0182] Clause 146: The method of clause 145, wherein removing excess fluid from the patient is provided as a treatment for acute kidney injury.

[0183] Clause 147: The method of clause 145, wherein the patient's dry weight is directly measured prior to a fluid resuscitation procedure.

[0184] Clause 148: A system for removing excess fluid from a patient with hemodilution, comprising: a urinary tract catheter comprising: a drainage lumen portion comprising a proximal end, a distal end configured to be positioned in a patient's urinary tract, and a sidewall extending therebetween; and a retention portion extending radially outward from a portion of the distal end of the drainage lumen portion, and being configured to be extended into a deployed position in which a diameter of the retention portion is greater than a diameter of the drainage lumen portion, wherein at least one of the drainage lumen portion or the retention portion comprises at least one drainage port to permit fluid flow into the drainage lumen; and a pump in fluid communication with a drainage lumen defined by the drainage lumen portion of the ureteral catheter, the pump comprising a controller configured to: actuate the pump to cause the pump to induce a negative pressure in a ureter and/or kidney of the patient to draw urine through the drainage lumen of the urinary tract catheter, periodically receive information representative of a hematocrit value of the patient; and if the received hematocrit value exceeds a predetermined minimum threshold value, ceasing the application of the negative pressure to the ureter and/or kidney.

[0185] Clause 149: The system of clause 148, wherein the predetermined threshold value comprises a hematocrit value for a healthy patient.

[0186] Clause 150: The system of clause 148, wherein the predetermined threshold value is between 25% and 40%.

[0187] Clause 151: The system of clause 148, further comprising a bladder catheter for deployment within the patient's bladder, the bladder catheter comprising: a drainage lumen portion defining a drainage lumen and comprising a proximal end, a distal end configured to be positioned in the patient's bladder, and a sidewall extending therebetween; and a deployable anchor portion comprising a seal configured to contact a proximal portion of the bladder wall to seal the urethral opening, wherein at least one of the drainage lumen portion or the anchor portion comprises at least one drainage port for permitting fluid flow into the drainage lumen for expelling urine from the bladder.

[0188] Clause 152: The system of clause 148, further comprising one or more physiological sensors associated with the patient, the physiological sensors being configured to provide the information representative of the hematocrit value to the controller.

[0189] Clause 153: The system of clause 152, wherein the one or more physiological sensors comprise an analyte and/or capacitance sensor associated with an extracorporeal blood system associated with the patient.

[0190] Clause 154: The system of clause 148, wherein, prior to ceasing application of the negative pressure, the controller is further configured to adjust an operating parameter of the pump based, at least in part, on the measured hematocrit value.

[0191] Clause 155: The system of clause 154, wherein adjusting an operating parameter of the pump based on the measured hematocrit value comprises reducing applied negative pressure when a downward trend in measured hematocrit value is identified.

[0192] Clause 156: The system of clause 148, wherein the pump provides a sensitivity of 10 mmHg or less.

[0193] Clause 157: The system of clause 148, wherein the controller is configured to cause the pump to alternate between providing negative pressure and providing positive pressure.

[0194] Clause 158: The system of clause 157, wherein the negative pressure is provided within a range of 5 mmHg to 50 mmHg, and wherein the positive pressure is provided within a range of 5 mmHg to 20 mmHg.

[0195] Clause 159: The system of clause 148, wherein the excess fluid is provided to the patient during a fluid resuscitation procedure.

BRIEF DESCRIPTION OF THE DRAWINGS

[0196] These and other features and characteristics of the present disclosure, as well as the methods of operation and functions of the related elements of structures and the combination of parts and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limit of the invention.

[0197] Further features and other examples and advantages will become apparent from the following detailed description made with reference to the drawings in which:

[0198] FIG. 1 is a schematic drawing of an indwelling portion of a urine collection assembly deployed in a urinary tract of a patient, according to an example of the present invention;

[0199] FIG. 2A is a perspective view of an exemplary ureteral catheter according to an example of the disclosure;

[0200] FIG. 2B is a front view of the ureteral catheter of FIG. 2A;

[0201] FIG. 3A is a schematic drawing of an example of a retention portion for a ureteral catheter according to an example of the present invention;

[0202] FIG. 3B is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0203] FIG. 3C is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0204] FIG. 3D is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0205] FIG. 3E is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0206] FIG. 4A is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0207] FIG. 4B is a schematic drawing of a cross-sectional view of a portion of the retention portion of FIG. 4A, taken along lines B-B of FIG. 4A;

[0208] FIG. 5A is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0209] FIG. 5B is a schematic drawing of a portion of a cross-sectional view of the retention portion of FIG. 5A, taken along lines B-B of FIG. 5A;

[0210] FIG. 6 is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0211] FIG. 7 is a schematic drawing of a cross section of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0212] FIG. 8 is a schematic drawing of another example of a retention portion for a ureteral catheter according to an example of the present invention;

[0213] FIG. 9A is a schematic drawing of another example of a urine collection assembly according to an example of the present invention;

[0214] FIG. 9B is a partial schematic drawing taken along section 9B-9B of the bladder anchor portion of the assembly of FIG. 9A;

[0215] FIG. 10A is a schematic drawing of another example of a urine collection assembly according to an example of the present invention;

[0216] FIG. 10B is a schematic drawing taken along section 10B-10B of the bladder anchor portion of the assembly of FIG. 10A;

[0217] FIG. 11A is a schematic drawing of a urine collection assembly according to an example of the present invention;

[0218] FIG. 11B is a schematic drawing taken along section 11B-11B of a bladder anchor portion of the assembly of FIG. 11A;

[0219] FIG. 12A is a schematic drawing of another bladder anchor portion of a urine collection assembly according to an example of the disclosure;

[0220] FIG. 12B is a schematic drawing of a cross section of a bladder catheter of a urine collection assembly, taken along line C-C of FIG. 12A;

[0221] FIG. 12C is a schematic drawing of a cross section of another example of a bladder catheter of a urine collection assembly;

[0222] FIG. 13 is a schematic drawing of another example of a bladder anchor portion of a urine collection assembly according to an example of the present disclosure;

[0223] FIG. 14 is a schematic drawing of another example of a bladder anchor portion of a urine collection assembly according to an example of the present disclosure;

[0224] FIG. 15 is a schematic drawing of another example of a bladder anchor portion of a urine collection assembly configured to be deployed in the patient's bladder and urethra according to an example of the present invention;

[0225] FIG. 16 is a schematic drawing of another example of a bladder anchor portion of a urine collection assembly according to an example of the present invention;

[0226] FIG. 17A is an exploded perspective view of a connector for a urine collection assembly according to an example of the disclosure;

[0227] FIG. 17B is a cross-sectional view of a portion of the connector of FIG. 17A;

[0228] FIG. 17C is a schematic drawing of a connector for a urine collection assembly according to an example of the disclosure;

[0229] FIG. 18A is a flow chart illustrating a process for insertion and deployment of a ureteral catheter or urine collection assembly according to an example of the present invention;

[0230] FIG. 18B is a flow chart illustrating a process for applying negative pressure using a ureteral catheter or urine collection assembly according to an example of the present invention;

[0231] FIG. 19 is a schematic drawing of a system for inducing negative pressure to the urinary tract of a patient according to an example of the present invention;

[0232] FIG. 20A is a plan view of a pump for use with the system of FIG. 19 according to an example of the present invention;

[0233] FIG. 20B is a side elevation view of the pump of FIG. 20A;

[0234] FIG. 21 is a schematic drawing of an experimental set-up for evaluating negative pressure therapy in a swine model;

[0235] FIG. 22 is a graph of creatinine clearance rates for tests conducted using the experimental set-up shown in FIG. 21;

[0236] FIG. 23A is a low magnification photomicrograph of kidney tissue from a congested kidney treated with negative pressure therapy;

[0237] FIG. 23B is a high magnification photomicrograph of the kidney tissue shown in FIG. 23A;

[0238] FIG. 23C is a low magnification photomicrograph of kidney tissue from a congested and untreated (e.g., control) kidney;

[0239] FIG. 23D is a high magnification photomicrograph of the kidney tissue shown in FIG. 23C

[0240] FIG. 24 is a flow chart illustrating a process for reducing creatinine and/or protein levels of a patient according to an aspect of the disclosure;

[0241] FIG. 25 is a flow chart illustrating a process for treating a patient undergoing fluid resuscitation according to an aspect of the disclosure; and

[0242] FIG. 26 is a graph of serum albumin relative to baseline for tests conducted on swine using the experimental method described herein.

DETAILED DESCRIPTION OF THE INVENTION

[0243] As used herein, the singular form of “a”, “an”, and “the” include plural referents unless the context clearly states otherwise.

[0244] As used herein, the terms “right”, “left”, “top”, and derivatives thereof shall relate to the invention as it is oriented in the drawing figures. The term “proximal” refers to the portion of the catheter device that is manipulated or contacted by a user and/or to a portion of an indwelling catheter nearest to the urinary tract access site. The term “distal” refers to the opposite end of the catheter device that is configured to be inserted into a patient and/or to the portion of the device that is inserted farthest into the patient's urinary tract. However, it is to be understood that the invention can assume various alternative orientations and, accordingly, such terms are not to be considered as limiting. Also, it is to be understood that the invention can assume various alternative variations and stage sequences, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification, are examples. Hence, specific dimensions and other physical characteristics related to the embodiments disclosed herein are not to be considered as limiting.

[0245] For the purposes of this specification, unless otherwise indicated, all numbers expressing quantities of ingredients, reaction conditions, dimensions, physical characteristics, and so forth used in the specification and claims are to be understood as being modified in all instances by the term “about.” Unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by the present invention.

[0246] Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains certain errors necessarily resulting from the standard deviation found in their respective testing measurements.

[0247] Also, it should be understood that any numerical range recited herein is intended to include all sub-ranges subsumed therein. For example, a range of “1 to 10” is intended to include any and all sub-ranges between and including the recited minimum value of 1 and the recited maximum value of 10, that is, all subranges beginning with a minimum value equal to or greater than 1 and ending with a maximum value equal to or less than 10, and all subranges in between, e.g., 1 to 6.3, or 5.5 to 10, or 2.7 to 6.1.

[0248] As used herein, the terms “communication” and “communicate” refer to the receipt or transfer of one or more signals, messages, commands, or other type of data. For one unit or component to be in communication with another unit or component means that the one unit or component is able to directly or indirectly receive data from and/or transmit data to the other unit or component. This can refer to a direct or indirect connection that can be wired and/or wireless in nature. Additionally, two units or components can be in communication with each other even though the data transmitted can be modified, processed, routed, and the like, between the first and second unit or component. For example, a first unit can be in communication with a second unit even though the first unit passively receives data, and does not actively transmit data to the second unit. As another example, a first unit can be in communication with a second unit if an intermediary unit processes data from one unit and transmits processed data to the second unit. It will be appreciated that numerous other arrangements are possible.

[0249] Fluid retention and venous congestion are central problems in the progression to advanced renal disease. Excess sodium ingestion coupled with relative decreases in excretion leads to isotonic volume expansion and secondary compartment involvement. In some examples, the present invention is generally directed to devices and methods for facilitating drainage of urine or waste from the bladder, ureter, and/or kidney(s) of a patient. In some examples, the present invention is generally directed to devices and methods for inducing a negative pressure in the bladder, ureter, and/or kidney(s) of a patient. While not intending to be bound by any theory, it is believed that applying a negative pressure to the bladder, ureter, and/or kidney(s) can offset the medullary nephron tubule re-absorption of sodium and water in some situations. Offsetting re-absorption of sodium and water can increase urine production, decrease total body sodium, and improve erythrocyte production. Since the intra-medullary pressures are driven by sodium and, therefore, volume overload, the targeted removal of excess

sodium enables maintenance of volume loss. Removal of volume restores medullary hemostasis. Normal urine production is 1.48-1.96 L/day (or 1-1.4 ml/min).

[0250] Fluid retention and venous congestion are also central problems in the progression of prerenal Acute Kidney Injury (AKI). Specifically, AKI can be related to loss of perfusion or blood flow through the kidney(s). Accordingly, in some examples, the present invention facilitates improved renal hemodynamics and increases urine output for the purpose of relieving or reducing venous congestion. Further, it is anticipated that treatment and/or inhibition of AKI positively impacts and/or reduces the occurrence of other conditions, for example, reduction or inhibition of worsening renal function in patients with NYHA Class III and/or Class IV heart failure. Classification of different levels of heart failure are described in *The Criteria Committee of the New York Heart Association*, (1994), *Nomenclature and Criteria for Diagnosis of Diseases of the Heart and Great Vessels*, (9th ed.), Boston: Little, Brown & Co. pp. 253-256, the disclosure of which is incorporated by reference herein in its entirety. Reduction or inhibition of episodes of AKI and/or chronically decreased perfusion may also be a treatment for Stage 4 and/or Stage 5 chronic kidney disease. Chronic kidney disease progression is described in National Kidney Foundation, *K/DOQI Clinical Practice Guidelines for Chronic Kidney Disease: Evaluation, Classification and Stratification*. Am. J. Kidney Dis. 39:S1-S266, 2002 (Suppl. 1), the disclosure of which is incorporated by reference herein in its entirety.

[0251] With reference to FIG. 1, the urinary tract comprises a patient's right kidney **2** and left kidney **4**. As discussed above, the kidneys **2, 4** are responsible for blood filtration and clearance of waste compounds from the body through urine. Urine produced by the right kidney **2** and the left kidney **4** is drained into a patient's bladder **10** through tubules, namely a right ureter **6** and a left ureter **8**. For example, urine may be conducted through the ureters **6, 8** by peristalsis of the ureter walls, as well as by gravity. The ureters **6, 8** enter the bladder **10** through a ureter orifice or opening **16**. The bladder **10** is a flexible and substantially hollow structure adapted to collect urine until the urine is excreted from the body. The bladder **10** is transitionable from an empty position (signified by reference line E) to a full position (signified by reference line F). Normally, when the bladder **10** reaches a substantially full state, urine is permitted to drain from the bladder **10** to a urethra **12** through a urethral sphincter or opening **18** located at a lower portion of the bladder **10**. Contraction of the bladder **10** can be responsive to stresses and pressure exerted on a trigone region **14** of the bladder **10**, which is the triangular region extending between the ureteral openings **16** and the urethral opening **18**. The trigone region **14** is sensitive to stress and pressure, such that as the bladder **10** begins to fill, pressure on the trigone region **14** increases. When a threshold pressure on the trigone region **14** is exceeded, the bladder **10** begins to contract to expel collected urine through the urethra **12**.

Exemplary Ureteral Catheters:

[0252] As shown in FIG. 1, a urine collection assembly **100** including ureteral catheters **112, 114** configured to be positioned within the urinary tract of a patient is illustrated. For example, distal ends **120, 121** of the ureteral catheters

112, 114 can be configured to be deployed in the patient's ureters **2, 4** and, in particular, in a renal pelvis **20, 21** area of the kidneys **6, 8**.

[0253] In some examples, the urine collection assembly **100** can comprise two separate ureteral catheters, such as a first catheter **112** disposed in or adjacent to the renal pelvis **20** of the right kidney **2** and a second catheter **114** disposed in or adjacent to the renal pelvis **21** of the left kidney **4**. The catheters **112, 114** can be separate for their entire lengths, or can be held in proximity to one another by a clip, ring, clamp, or other type of connection mechanism (e.g., connector **150**) to facilitate placement or removal of the catheters **112, 114**. In some examples, catheters **112, 114** can merge or be connected together to form a single drainage lumen. In other examples, the catheters **112, 114** can be inserted through or enclosed within another catheter, tube, or sheath along portions or segments thereof to facilitate insertion and retraction of the catheters **112, 114** from the body. For example, a bladder catheter **116** can be inserted over and/or along the same guidewire as the ureteral catheters **112, 114**, thereby causing the ureteral catheters **112, 114** to extend from the distal end of the bladder catheter **116**.

[0254] With reference to FIGS. **1, 2A, and 2B**, an exemplary ureteral catheter **112** can comprise at least one elongated body or tube **122**, the interior of which defines or comprises one or more drainage channel(s) or lumen(s), such as drainage lumen **124**. The tube **122** size can range from about 1 Fr to about 9 Fr (French catheter scale). In some examples, the tube **122** can have an external diameter ranging from about 0.33 to about 3 mm, and an internal diameter ranging from about 0.165 to about 2.39 mm. In one preferable example, the tube **122** is 6 Fr and has an outer diameter of 2.0 ± 0.1 mm. The length of the tube **122** can range from about 30 cm to about 120 cm depending on the age (e.g., pediatric or adult) and gender of the patient.

[0255] The tube **122** can be formed from a flexible and/or deformable material to facilitate advancing and/or positioning the tube **122** in the bladder **10** and ureters **6, 8** (shown in FIG. **1**). The catheter material should be flexible and soft enough to avoid or reduce irritation of the renal pelvis and ureter, but should be rigid enough that the tube **122** does not collapse when the renal pelvis or other portions of the urinary tract exert pressure on the exterior of the tube **122**, or when the renal pelvis and/or ureter are drawn against the tube **122** during inducement of negative pressure. For example, the tube **122** can be formed from materials including biocompatible polymers, polyvinyl chloride, polytetrafluoroethylene (PTFE) such as Teflon®, silicon coated latex, or silicon. In one preferable example, the tube **122** is formed from a thermoplastic polyurethane. At least a portion or all of the catheter **112**, such as the tube **122**, can be coated with a hydrophilic coating to facilitate insertion and/or removal, and/or to enhance comfort. In some examples, the coating is a hydrophobic and/or lubricious coating. For example, suitable coatings can comprise ComfortCoat® hydrophilic coating which is available from Koninklijke DSM N.V. or hydrophilic coatings comprising polyelectrolyte(s) such as are disclosed in U.S. Pat. No. 8,512,795, which is incorporated herein by reference.

[0256] In some examples, the tube **122** can comprise: a distal portion **118** (e.g., a portion of the tube **122** configured to be positioned in the ureter **6, 8** and renal pelvis **20, 21**); a middle portion **126** (e.g., a portion of the tube **122** configured to extend from the distal portion through the

ureteral openings **16** into the patient's bladder **10** and urethra **12**); and a proximal portion **128** (e.g., a portion of the tube **122** extending from the urethra **12** to an external fluid collection container and/or pump assembly). In one preferred example, the combined length of the proximal portion **128** and the middle portion **126** of the tube **122** is about 54 ± 2 cm. In some examples, the tube **122** terminates in another indwelling catheter and/or drainage lumen, such as in a drainage lumen of the bladder catheter **116**. In that case, fluid drains from the proximal end of the ureteral catheter **112, 114** and is directed from the body through the additional indwelling catheter and/or drainage lumen.

Exemplary Ureteral Retention Portions:

[0257] With continued reference to FIGS. **1, 2A, and 2B**, the distal portion **118** of the ureteral catheter **112** comprises a retention portion **130** for maintaining the distal end **120** of the catheter **112** at a desired fluid collection position proximate to or within the renal pelvis **20, 21** of the kidney **2, 4**. In some examples, the retention portion **130** is configured to be flexible and bendable to permit positioning of the retention portion **130** in the ureter and/or renal pelvis. The retention portion **130** is desirably sufficiently bendable to absorb forces exerted on the catheter **112** and to prevent such forces from being translated to the ureters. For example, if the retention portion **130** is pulled in the proximal direction P (shown in FIG. **3A**) toward the patient's bladder, the retention portion **130** can be sufficiently flexible to begin to unwind or be straightened so that it can be drawn through the ureter. Similarly, when the retention portion **130** can be reinserted into the renal pelvis or other suitable region within the ureter, it can be biased to return to its deployed configuration.

[0258] In some examples, the retention portion **130** is integral with the tube **122**. In that case, the retention portion **130** can be formed by imparting a bend or curl to the catheter body **122** that is sized and shaped to retain the catheter at a desired fluid collection location. Suitable bends or coils can include a pigtail coil, corkscrew coil, and/or helical coil. For example, the retention portion **130** can comprise one or more radially and longitudinally extending helical coils configured to contact and passively retain the catheter **112** within the ureter **6, 8** proximate to or within the renal pelvis **20, 21**. In other examples, the retention portion **130** is formed from a radially flared or tapered portion of the catheter body **122**. For example, the retention portion **130** can further comprise a fluid collecting portion, as shown in FIGS. **4A and 4B**, such as a tapered or funnel-shaped inner surface **186**. In other examples, the retention portion **130** can comprise a separate element connected to and extending from the catheter body or tube **122**.

[0259] The retention portion **130** can further comprise one or more perforated sections, such as drainage holes or ports **132** (shown in FIGS. **3A-3E**). A drainage port can be located, for example, at the open distal end **120, 121** of the tube **122**. In other examples, perforated sections and/or drainage ports **132** are disposed along the sidewall of the distal portion **118** of the catheter tube **122**. The drainage ports or holes can be used for assisting in fluid collection. In other examples, the retention portion **130** is solely a retention structure and fluid collection and/or imparting negative pressure is provided by structures at other locations on the catheter tube **122**.

[0260] Referring now to FIGS. 2A, 2B, and 3A-3E, exemplary retention portions 130 comprising a plurality of helical coils, such as one or more full coils 184 and one or more half or partial coils 183, are illustrated. The retention portion 130 is capable of moving between a contracted position and the deployed position with the plurality of helical coils. For example, a substantially straight guidewire can be inserted through the retention portion 130 to maintain the retention portion 130 in a substantially straight contracted position. When the guidewire is removed, the retention portion 130 can transition to its coiled configuration. In some examples, the coils 183, 184 extend radially and longitudinally from the distal portion 118 of the tube 122. With specific reference to FIGS. 2A and 2B, in a preferred exemplary embodiment, the retention portion 130 comprises two full coils 184 and one half coil 183. The outer diameter of the full coils 184, shown by line D1, can be about 18 ± 2 mm. The half coil 183 diameter D2 can be about 14 mm. The coiled retention portion 130 has a height H of about 16 ± 2 mm. The retention portion 130 can further comprise the one or more drainage holes 132 (shown in FIGS. 3A-3E) configured to draw fluid into an interior of the catheter tube 122. In some examples, the retention portion 130 can comprise six drainage holes, plus an additional hole at the distal tip 120 of the retention portion. The diameter of each of the drainage holes 132 (shown in FIGS. 3A-3E) can range from about 0.7 mm to 0.9 mm and, preferably, is about 0.83 ± 0.01 mm. The distance between adjacent drainage holes 132, specifically the linear distance between drainage holes 132 when the coils are straightened, can be about 22.5 ± 2.5 mm.

[0261] As shown in FIGS. 3A-3E, in another exemplary embodiment, the distal portion 118 of the drainage lumen proximal to the retention portion 130 defines a straight or curvilinear central axis L. In some examples, at least a half or first coil 183 and a full or second coil 184 of the retention portion 130 extend about an axis A of the retention portion 130. The first coil 183 initiates or begins at a point where the tube 122 is bent at an angle α ranging from about 15 degrees to about 75 degrees from the central axis L, as indicated by angle α , and preferably about 45 degrees. As shown in FIGS. 3A and 3B, prior to insertion in the body, the axis A can be coextensive with the longitudinal central axis L. In other examples, as shown in FIGS. 3C-3E, prior to insertion in the body, the axis A extends from and is curved or angled, for example at angle β , relative to the central longitudinal axis L.

[0262] In some examples, multiple coils 184 can have the same inner and/or outer diameter D and height H2. In that case, the outer diameter D1 of the coils 184 may range between 10 mm and 30 mm. The height H2 between coils 184 may be about 3 mm to 10 mm.

[0263] In other examples, the retention portion 130 is configured to be inserted in the tapered portion of the renal pelvis. For example, the outer diameter D1 of the coils 184 can increase toward the distal end 120 of the tube 122, resulting in a helical structure having a tapered or partially tapered configuration. For example, the distal or maximum outer diameter D1 of the tapered helical portion ranges from about 10 mm to about 30 mm, which corresponds to the dimensions of the renal pelvis. The height H2 of the retention portion 130 ranges from about 10 mm to about 30 mm.

[0264] In some examples, the outer diameter D1 and/or height H2 of the coils 184 can vary in a regular or irregular fashion. For example, the outer diameter D1 of coils or

height H2 between coils can increase or decrease by a regular amount (e.g., about 10% to about 25% between adjacent coils 184). For example, for a retention portion 130 having three coils (as shown, for example, in FIGS. 3A and 3B) an outer diameter D3 of a proximal-most coil or first coil 183 can be about 6 mm to 18 mm, an outer diameter D2 of a middle coil or second coil 185 can be about 8 mm to about 24 mm, and an outer diameter D1 of a distal-most or third coil 187 can be between about 10 mm and about 30 mm.

[0265] The retention portion 130 can further comprise the drainage ports 132 or holes disposed on or through the sidewall of the catheter tube 122 on or adjacent to the retention portion 130 to permit urine waste to flow from the outside of the catheter tube 122 to the inside of the catheter tube 122. The position and size of the drainage ports 132 can vary depending upon the desired flow rate and configuration of the retention portion. The diameter of the drainage ports 132 can range from about 0.005 mm to about 1.0 mm. The spacing between the drainage ports 132 can range from about 1.5 mm to about 5 mm. The drainage ports 132 can be spaced in any arrangement, for example, linear or offset. In some examples, the drainage ports 132 can be non-circular, and can have a surface area of about 0.00002 to 0.79 mm².

[0266] In some examples, as shown in FIG. 3A, the drainage ports 132 are located around the entire periphery of the sidewall of the catheter tube 122 to increase an amount of fluid that can be drawn into the drainage lumen 124 (shown in FIGS. 1, 2A, and 2B). In other examples, as shown in FIGS. 3B-3E, the drainage ports 132 can be disposed essentially only or only on the radially inwardly facing side of the coils 184 to prevent occlusion or blockage of the drainage ports 132, and the outwardly facing side of the coils may be essentially free of drainage ports 132 or free of drainage ports 132. For example, when negative pressure is induced in the ureter and/or renal pelvis, mucosal tissue of the ureter and/or kidney may be drawn against the retention portion 130 and may occlude some drainage ports 132 on the outer periphery of the retention portion 130. Drainage ports 132 located on the radially inward side of the retention structure would not be appreciably occluded when such tissues contact the outer periphery of the retention portion 130. Further, risk of injury to the tissues from pinching or contact with the drainage ports 132 can be reduced or ameliorated.

[0267] With reference to FIGS. 3C and 3D, other examples of ureteral catheters 112 having a retention portion 130 comprising a plurality of coils are illustrated. As shown in FIG. 3C, the retention portion 130 comprises three coils 184 extending about the axis A. The axis A is a curved arc extending from the central longitudinal axis L of the portion of the drainage lumen 181 proximal to the retention portion 130. The curvature imparted to the retention portion 130 can be selected to correspond to the curvature of the renal pelvis, which comprises a cornucopia-shaped cavity.

[0268] As shown in FIG. 3D, in another exemplary embodiment, the retention portion 130 can comprise two coils 184 extending about an angled axis A. The angled axis A extends at an angle from a central longitudinal axis L, and is angled, as shown by angle β , relative to an axis generally perpendicular to the central axis L of the portion of the drainage lumen. The angle β can range from about 15 to about 75 degrees (e.g., about 105 to about 165 degrees relative to the central longitudinal axis L of the drainage lumen portion of the catheter 112).

[0269] FIG. 3E shows another example of a ureteral catheter 112. The retention portion comprises three helical coils 184 extending about an axis A. The axis A is angled, as shown by angle β , relative to the horizontal. As in the previously-described examples, the angle β can range from about 15 to about 75 degrees (e.g., about 105 to about 165 degrees relative to the central longitudinal axis L of the drainage lumen portion of the catheter 112).

[0270] With reference to FIGS. 4A and 4B, in another example, a retention portion 130 of a ureteral catheter 112 comprises a catheter tube 122 having a widened and/or tapered distal end portion which, in some examples, is configured to be positioned in the patient's renal pelvis and/or kidney. For example, the retention portion 130 can be a funnel-shaped structure comprising an outer surface 185 configured to be positioned against the ureter and/or kidney wall and comprising an inner surface 186 configured to direct fluid toward a drainage lumen 124 of the catheter 112. The retention portion 130 can comprise a proximal end 188 adjacent to the distal end of the drainage lumen 124 and having a first diameter D1 and a distal end 190 having a second diameter D2 that is greater than the first diameter D1 when the retention portion 130 is in its deployed position. In some examples, the retention portion 130 is transitionable from a collapsed or compressed position to the deployed position. For example, the retention portion 130 can be biased radially outward such that when the retention portion 130 is advanced to its fluid collecting position, the retention portion 130 (e.g., the funnel portion) expands radially outward to the deployed state.

[0271] The retention portion 130 of the ureteral catheter 112 can be made from a variety of suitable materials that are capable of transitioning from the collapsed state to the deployed state. In one example, the retention portion 130 comprises a framework of tines or elongated members formed from a temperature sensitive shape memory material, such as nitinol. In some examples, the nitinol frame can be covered with a suitable waterproof material such as silicon to form a tapered portion or funnel. In that case, fluid is permitted to flow down the inner surface 186 of the retention portion 130 and into the drainage lumen 124. In other examples, the retention portion 130 is formed from various rigid or partially rigid sheets or materials bended or molded to form a funnel-shaped retention portion as illustrated in FIGS. 4A and 4B.

[0272] In some examples, the retention portion of the ureteral catheter 112 can include one or more mechanical stimulation devices 191 for providing stimulation to nerves and muscle fibers in adjacent tissues of the ureter(s) and renal pelvis. For example, the mechanical stimulation devices 191 can include linear or annular actuators embedded in or mounted adjacent to portions of the sidewall of the catheter tube 122 and configured to emit low levels of vibration. In some examples, mechanical stimulation can be provided to portions of the ureters and/or renal pelvis to supplement or modify therapeutic effects obtained by application of negative pressure. While not intending to be bound by theory, it is believed that such stimulation affects adjacent tissues by, for example, stimulating nerves and/or actuating peristaltic muscles associated with the ureter(s) and/or renal pelvis. Stimulation of nerves and activation of muscles may produce changes in pressure gradients or pressure levels in

surrounding tissues and organs which may contribute to or, in some cases, enhance therapeutic benefits of negative pressure therapy.

[0273] With reference to FIGS. 5A and 5B, according to another example, a retention portion 330 of a ureteral catheter 312 comprises a catheter tube 322 having a distal portion 318 formed in a helical structure 332 and an inflatable element or balloon 350 positioned proximal to the helical structure 332 to provide an additional degree of retention in the renal pelvis and/or fluid collection location. A balloon 350 can be inflated to pressure sufficient to retain the balloon in the renal pelvis or ureter, but low enough to avoid distending or damaging these structures. Suitable inflation pressures are known to those skilled in the art and are readily discernible by trial and error. As in previously-described examples, the helical structure 332 can be imparted by bending the catheter tube 322 to form one or more coils 334. The coils 334 can have a constant or variable diameter and height as described above. The catheter tube 322 further comprises a plurality of drainage ports 336 disposed on the sidewall of the catheter tube 322 to allow urine to be drawn into the drainage lumen 324 of the catheter tube 322 and to be directed from the body through the drainage lumen 324, for example on the inwardly facing and/or outwardly facing sides of the coil 334.

[0274] As shown in FIG. 5B, the inflatable element or balloon 350 can comprise an annular balloon-like structure having, for example, a generally heart-shaped cross section and comprising a surface or cover 352 defining a cavity 353. The cavity 353 is in fluid communication with an inflation lumen 354 extending parallel to the drainage lumen 324 defined by the catheter tube 322. The balloon 350 can be configured to be inserted in the tapered portion of the renal pelvis and inflated such that an outer surface 356 thereof contacts and rests against an inner surface of the ureter and/or renal pelvis. The inflatable element or balloon 350 can comprise a tapered inner surface 358 extending longitudinally and radially inward towards the catheter tube 322. The inner surface 358 can be configured to direct urine toward the catheter tube 322 to be drawn into the drainage lumen 324. The inner surface 358 can also be positioned to prevent fluid from pooling in the ureter, such as around the periphery of the inflatable element or balloon 350. The inflatable retention portion or balloon 350 is desirably sized to fit within the renal pelvis and can have a diameter ranging from about 10 mm to about 30 mm.

[0275] With reference to FIGS. 6 and 7, in some examples, an assembly 400 including a ureteral catheter 412 comprising a retention portion 410 is illustrated. The retention portion 410 is formed from a porous and/or sponge-like material that is attached to a distal end 421 of a catheter tube 422. The porous material can be configured to channel and/or absorb urine and direct the urine toward a drainage lumen 424 of the catheter tube 422. As shown in FIG. 7, the retention portion 410 can be a porous wedge shaped-structure configured for insertion and retention in the patient's renal pelvis. The porous material comprises a plurality of holes and/or channels. Fluid can be drawn through the channels and holes, for example, by gravity or upon inducement of negative pressure through the catheter 412. For example, fluid can enter the wedge-shaped retention portion 410 through the holes and/or channels and is drawn toward a distal opening 420 of the drainage lumen 424, for example, by capillary action, peristalsis, or as a result of the induce-

ment of negative pressure in the holes and/or channels. In other examples, as shown in FIG. 7, the retention portion **410** comprises a hollow, funnel structure formed from the porous sponge-like material. As shown by arrow A, fluid is directed down an inner surface **426** of the funnel structure into the drainage lumen **424** defined by the catheter tube **422**. Also, fluid can enter the funnel structure of the retention portion **410** through holes and channels in the porous sponge-like material of a sidewall **428**. For example, suitable porous materials can include open-celled polyurethane foams, such as polyurethane ether. Suitable porous materials can also include laminates of woven or non-woven layers comprising, for example, polyurethane, silicone, polyvinyl alcohol, cotton, or polyester, with or without antimicrobial additives such as silver, and with or without additives for modifying material properties such as hydrogels, hydrocolloids, acrylic, or silicone.

[0276] With reference to FIG. 8, according to another example, a retention portion **500** of a ureteral catheter **512** comprises an expandable cage **530**. The expandable cage **530** comprises one or more longitudinally and radially extending hollow tubes **522**. For example, the tubes **522** can be formed from an elastic, shape memory material such as nitinol. The cage **530** is configured to transition from a contracted state, for insertion through the patient's urinary tract, to a deployed state for positioning in the patient's ureters and/or kidney. The hollow tubes **522** comprise a plurality of drainage ports **534** which can be positioned on the tubes, for example, on radially inward facing sides thereof. The ports **534** are configured to permit fluid to flow or be drawn through the ports **534** and into the respective tubes **522**. The fluid drains through the hollow tubes **522** into a drainage lumen **524** defined by a catheter body **526** of the ureteral catheter **512**. For example, fluid can flow along the path indicated by the arrows **532** in FIG. 8. In some examples, when negative pressure is induced in the renal pelvis, kidneys, and/or ureters, portions of the ureter wall and/or renal pelvis may be drawn against the outward facing surfaces of the hollow tubes **522**. The drainage ports **534** are positioned and configured so as not to be appreciably occluded by ureteral structures upon application of negative pressure to the ureters and/or kidney.

Exemplary Urine Collection Assembly:

[0277] Referring now to FIGS. 1, 9A, and 11A, the urine collection assembly **100** further comprises a bladder catheter **116**. The distal ends **120**, **121** of the ureteral catheters **112**, **114** can be connected to the bladder catheter **116** to provide a single drainage lumen for urine, or the ureteral catheter(s) can drain via separate tube(s) from the bladder catheter **116**.

[0278] Exemplary Bladder Catheter

[0279] The bladder catheter **116** comprises a deployable seal and/or anchor **136** for anchoring, retaining, and/or providing passive fixation for indwelling portions of the urine collection assembly **100** and, in some examples, to prevent premature and/or untended removal of assembly components during use. The anchor **136** is configured to be located adjacent to the lower wall of the patient's bladder **10** (shown in FIG. 1) to prevent patient motion and/or forces applied to indwelling catheters **112**, **114**, **116** from translating to the ureters. The bladder catheter **116** comprises an interior of which defines a drainage lumen **140** configured to conduct urine from the bladder **10** to an external urine collection container **712** (shown in FIG. 19). In some

examples, the bladder catheter **116** size can range from about 8 Fr to about 24 Fr. In some examples, the bladder catheter **116** can have an external diameter ranging from about 2.7 to about 8 mm. In some examples, the bladder catheter **116** can have an internal diameter ranging from about 2.16 to about 6.2 mm. The bladder catheter **116** can be available in different lengths to accommodate anatomical differences for gender and/or patient size. For example, the average female urethra length is only a few inches, so the length of a tube **138** can be rather short. The average urethra length for males is longer due to the penis and can be variable. It is possible that woman can use bladder catheters **116** with longer length tubes **138** provided that the excess tubing does not increase difficulty in manipulating and/or preventing contamination of sterile portions of the catheter **116**. In some examples, a sterile and indwelling portion of the bladder catheter **116** can range from about 1 inch to 3 inches (for women) to about 20 inches for men. The total length of the bladder catheter **116** including sterile and non-sterile portions can be from one to several feet.

[0280] The catheter tube **138** can comprise one or more drainage ports **142** configured to be positioned in the bladder **10** for drawing urine into the drainage lumen **140**. For example, excess urine left in the patient's bladder **10** during placement of the ureteral catheters **112**, **114** is expelled from the bladder **10** through the ports **142** and drainage lumen **140**. In addition, any urine that is not collected by the ureteral catheters **112**, **114** accumulates in the bladder **10**, and can be conducted from the urinary tract through the drainage lumen **140**. The drainage lumen **140** may be pressurized to a negative pressure to assist in fluid collection or may be maintained at atmospheric pressure such that fluid is collected by gravity and/or as a result of partial contraction of the bladder **10**. In some examples, the ureteral catheters **112**, **114** may extend from the drainage lumen **140** of the bladder catheter **116** to facilitate and/or simplify insertion and placement of the ureteral catheters **112**, **114**.

[0281] With specific reference to FIG. 1, the deployable seal and/or anchor **136** is disposed at or adjacent to a distal end **148** of the bladder catheter **116**. The deployable anchor **136** is configured to transition between a contracted state for insertion into the bladder **10** through the urethra **12** and urethral opening **18** and a deployed state. The anchor **136** is configured to be deployed in and seated adjacent to a lower portion of the bladder **10** and/or against the urethral opening **18**. For example, the anchor **136** can be positioned adjacent to the urethral opening **18** to enhance suction of a negative pressure applied to the bladder **10** or, in the absence of negative pressure, to partially, substantially, or entirely seal the bladder **10** to ensure that urine in the bladder **10** is directed through the drainage lumen **140** and to prevent leakage to the urethra **12**. For a bladder catheter **116** including an 8 Fr to 24 Fr elongated tube **138**, the anchor **136** can be about 12 Fr to 32 Fr (e.g., having a diameter of about 4 mm to about 10.7 mm) in the deployed state, and preferably between about 24 Fr and 30 Fr. A 24 Fr anchor has a diameter of about 8 mm. It is believed that a 24 Fr anchor **136** would be a single size suitable for all or most patients. For a catheter **116** with a 24 Fr anchor **136**, a suitable length of the anchor **136** is between about 1.0 cm and 2.3 cm, and preferably about 1.9 cm (about 0.75 in).

[0282] Exemplary Bladder Anchor Structures:

[0283] With specific reference to FIGS. 1, 12A, and 13, an exemplary bladder anchor **136** in the form of an expandable

balloon 144 is illustrated. The expandable (e.g., inflatable) balloon 144 can be, for example, a spherical balloon of a Foley catheter. The balloon 144 can be about 1.0 cm to 2.3 cm in diameter, and preferably about 1.9 cm (0.75 in) in diameter. The balloon 144 is preferably formed from a flexible material including, for example, biocompatible polymers, polyvinyl chloride, polytetrafluoroethylene (PTFE) such as Teflon®, silicon coated latex, or silicon.

[0284] The balloon 144 is in fluid connection with an inflation lumen 146, and is inflated by introducing fluid into the balloon 144. In a deployed state, the balloon 144 can be a substantially spherical structure mounted to and extending radially outward from the catheter tube 138 of the bladder catheter 116 and comprising a central cavity or channel for the catheter tube 138 to pass through. In some examples, the catheter tube 138 extends through the cavity defined by the balloon 144, such that the open distal end 148 of the catheter tube 138 extends distally beyond the balloon 144 and toward the center of the bladder 10 (shown in FIG. 1). Excess urine collected in the bladder 10 can be drawn into the drainage lumen 140 through the distal open end 148 thereof.

[0285] As shown in FIGS. 1 and 12A, in one example, the ureteral catheters 112, 114 extend from the open distal end 148 of the drainage lumen 140. In another example, as shown in FIG. 14, the ureteral catheters 112, 114 extend through ports 172 or openings disposed on a sidewall of the catheter tube 138 at a position distal to the balloon 144. The ports 172 can be circular or oval shaped. The ports 172 are sized to receive the ureteral catheters 112, 114 and, accordingly, can have a diameter ranging from about 0.33 mm to about 3 mm. As shown in FIG. 13, in another example, the bladder catheter 116 is positioned next to the balloon 144, rather than extending through a central cavity defined by the balloon 144. As in other examples, the ureteral catheters 112, 114 extend through ports 172 in the sidewall of the bladder catheter 116 and into the bladder 10.

[0286] With reference to FIG. 12B, a cross-sectional view of the bladder catheter 116 and ureteral catheter(s) 112, 114 is shown. As shown in FIG. 12B, in one example, the bladder catheter 116 comprises a dual lumen catheter with the drainage lumen 140 at a central region thereof and a smaller inflation lumen 146 extending along the periphery of the catheter tube 138. The ureteral catheters 112, 114 are inserted or enclosed in the central drainage lumen 140. The ureteral catheters 112, 114 are single-lumen catheters having a sufficiently narrow cross section to fit within the drainage lumen 140. In some examples, as discussed above, the ureteral catheters 112, 114 extend through the entire bladder catheter 116. In other examples, the ureteral catheters 112, 114 terminate in the drainage lumen 140 of the bladder catheter 116, either at a position in the patient's ureter 12 or in an external portion of the drainage lumen 140. As shown in FIG. 12C, in another example, a bladder catheter 116a is a multi-lumen catheter that defines at least four lumens, namely a first lumen 112a for conducting fluid from the first ureteral catheter 112 (shown in FIG. 1), a second lumen 114a for conducting fluid from the second ureteral catheter 114 (shown in FIG. 1), a third lumen 140a for drainage of urine from the bladder 10 (shown in FIG. 1), and the inflation lumen 146a for conducting fluid to and from the balloon 144 (shown in FIG. 12A) for inflation and retraction thereof.

[0287] As shown in FIG. 15, another example of a catheter balloon 144 for use with a urine collection assembly 100 is illustrated. In the example of FIG. 15, the balloon 144 is

configured to be positioned partially within the patient's bladder 10 and partially within the urethra 12 to provide an enhanced bladder seal. A central portion 145 of the balloon 144 is configured to be radially contracted by the urethral opening 18, thereby defining a bulbous upper volume configured to be positioned in the lower portion of the bladder 10 and a bulbous lower volume configured to be positioned at the distal portion of the urethra 12. As in previously-described examples, the bladder catheter 116 extends through a central cavity defined by the balloon 144 and toward a central portion of the bladder 10 and includes drainage ports 142 for conducting urine from the bladder 10 through a drainage lumen 140 of the catheter 116. The drainage ports 142 can be generally circular or oval shaped and can have a diameter of about 0.005 mm to about 0.5 mm.

[0288] With reference again to FIGS. 9A and 9B, another example of a urine collection assembly 100 including a bladder anchor device 134 is illustrated. The bladder anchor device 134 comprises a bladder catheter 116 defining a drainage lumen 140, an inflation lumen 146, and an anchor 136, namely, another example of an expandable balloon 144, configured to be seated in a lower portion of the bladder 10. Unlike in the previously-described examples, the ports 142 configured to receive the ureteral catheters 112, 114 are disposed proximal to and/or below the balloon 144. The ureteral catheters 112, 114 extend from the ports 142 and, as in previously-described examples, extend through the ureteral orifices or openings of the bladder and into the ureters. When the anchor 136 is deployed in the bladder, the ports 142 are disposed in a lower portion of the bladder adjacent to the urethral opening. The ureteral catheters 112, 114 extend from the ports 172 and between a lower portion of the balloon 144 and the bladder wall. In some examples, the catheters 112, 114 may be positioned to prevent the balloon 144 and/or bladder wall from occluding the ports 142 so that excess urine collected in the bladder can be drawn into the ports 142 to be removed from the body.

[0289] With reference again to FIGS. 10A and 10B, in another example of a urine collection assembly 200, an expandable cage 210 anchors the assembly 200 in the bladder. The expandable cage 210 comprises a plurality of flexible members 212 or tines extending longitudinally and radially outward from a catheter body 238 of a bladder catheter 216 which, in some examples, can be similar to those discussed above with respect to the retention portion of the ureteral catheter of FIG. 8. The members 212 can be formed from a suitable elastic and shape memory material such as nitinol. In a deployed position, the members 212 or tines are imparted with a sufficient curvature to define a spherical or ellipsoid central cavity 242. The cage 210 is attached to an open distal open end 248 of the catheter tube or body 238, to allow access to a drainage lumen 240 defined by the tube or body 238. The cage 210 is sized for positioning within the lower portion of the bladder and can define a diameter and length ranging from 1.0 cm to 2.3 cm, and preferably about 1.9 cm (0.75 in).

[0290] In some examples, the cage 210 further comprises a shield or cover 214 over distal portions of the cage 210 to prevent or reduce the likelihood that tissue, namely, the distal wall of the bladder, will be caught or pinched as a result of contact with the cage 210 or member 212. More specifically, as the bladder contracts, the inner distal wall of the bladder comes into contact with the distal side of the cage 210. The cover 214 prevents the tissue from being

pinched or caught, may reduce patient discomfort, and protect the device during use. The cover **214** can be formed at least in part from a porous and/or permeable biocompatible material, such as a woven polymer mesh. In some examples, the cover **214** encloses all or substantially all of the cavity **242**. In that case, the cover **214** defines openings suitable for receiving the ureteral catheters **112**, **114**. In some examples, the cover **214** covers only about the distal $\frac{2}{3}$, about the distal half, or about the distal third portion or any amount, of the cage **210**. In that case, the ureteral catheters **112**, **114** pass through the uncovered portion of the cage **210**.

[0291] The cage **210** and cover **214** are transitionable from a contracted position, in which the members **212** are contracted tightly together around a central portion and/or around the bladder catheter **116** to permit insertion through a catheter or sheath to the deployed position. For example, in the case of a cage **210** constructed from a shape memory material, the cage **210** can be configured to transition to the deployed position when it is warmed to a sufficient temperature, such as body temperature (e.g., 37° C.). In the deployed position, the cage **210** has a diameter D that is preferably wider than the urethral opening, such that the cage **210** provides support for the ureteral catheters **112**, **114** and prevents patient motion from translating through the ureteral catheters **112**, **114** to the ureters. When the assembly **200** is deployed in the urinary tract, the ureteral catheter(s) **112**, **114** extend from the open distal end **248** of the bladder catheter **216**, past the longitudinally extending members **212** of the cage **210**, and into the bladder. Advantageously, the open (e.g., low profile) arrangement of the members **212** or tines facilitates manipulation of the ureteral catheters **112**, **114** from the bladder catheter **116** and through the bladder. Particularly, the open arrangement of the members **212** or tines does not obstruct or occlude the distal opening **248** and/or drainage ports of the bladder catheter **216**, making manipulation of the catheters **112**, **114** easier to perform.

[0292] With reference to FIG. 16, a portion of another example of a urine collection assembly **100b** is illustrated. The urine collection assembly **100b** comprises a first ureteral catheter **112b** and a second ureteral catheter **114b**. The assembly **100b** does not comprise a separate bladder drainage catheter as is provided in the previously-described examples. Instead, one of the ureteral catheters **112b** comprises a helical portion **127b** formed in the middle portion of the catheter **112b** (e.g., the portion of the catheter configured to be positioned in a lower portion of the patient's bladder). The helical portion **127b** comprises at least one and preferably two or more coils **176b**. The coils **176b** can be formed by bending a catheter tube **138b** to impart a desired coil configuration. A lower coil **178b** of the helical portion **127b** is configured to be seated against and/or adjacent to the urethral opening. Desirably, the helical portion **127b** has a diameter D that is larger than the urethral opening to prevent the helical portion **127b** from being drawn into the urethra. In some examples, a port **142b** or opening is disposed in the sidewall of the catheter tube **138b** for connecting the first ureteral catheter **112b** to the second ureteral catheter **114b**. For example, the second catheter **114b** can be inserted in the port **142b** to form a fluid connection between the first ureteral catheter **112b** and the second ureteral catheter **114b**. In some examples, the second catheter **114b** terminates at a position just inside a drainage lumen **140b** of the first catheter **112b**. In other examples, the second ureteral catheter **114b** is threaded through and/or extends along the

length of the drainage lumen **140b** of the first catheter **112b**, but is not in fluid communication with the drainage lumen **140b**.

[0293] With reference again to FIGS. 11A and 11B, another exemplary urine collection assembly **100** comprising a bladder anchor device **134** is illustrated. The assembly **100** includes ureteral catheters **112**, **114** and a separate bladder catheter **116**. More specifically, as in previously-described examples, the assembly **100** includes the ureteral catheters **112**, **114**, each of which comprise a distal portion **118** positioned in or adjacent to the right kidney and the left kidney, respectively. The ureteral catheters **112**, **114** comprise indwelling portions **118**, **126**, **128** extending through the ureters, bladder, and urethra. The ureteral catheters **112**, **114** further comprise an external portion **170** extending from the patient's urethra **12** to a pump assembly for imparting negative pressure to the renal pelvis and/or kidneys. The assembly **100** also includes a bladder anchor device **134** comprising a bladder catheter **116** and an anchor **136** (e.g., a Foley catheter) deployed in the bladder to prevent or reduce effects of patient motion from being translated to the ureteral catheters **112**, **114** and/or ureters. The bladder catheter **116** extends from the bladder **10**, through the urethra, and to a fluid collection container for fluid collection by gravity or negative pressure drainage. In some examples, an external portion of the tubing extending between a collection vessel **712** and a pump **710** (shown in FIG. 19) can comprise one or more filters for preventing urine and/or particulates from entering the pump. As in previously-described examples, the bladder catheter **116** is provided to drain excess urine left in the patient's bladder during catheter placement.

[0294] Exemplary Connectors and Clamps:

[0295] With reference to FIGS. 1, 11A, and 17A-17C, the assembly **100** further comprises a manifold or connector **150** for joining the two or more of the catheters **112**, **114**, **116** at a position outside the patient's body. In some examples, the connector **150** can be a clamp, manifold, valve, fastener, or other element of a fluid path set, as is known in the art, for joining a catheter to external flexible tubing. As shown in FIGS. 17A and 17B, the manifold or connector **150** comprises a two-piece body comprising an inner portion **151** mounted inside an outer housing **153**. The inner portion **151** defines channels for conducting fluid between inflow ports **154**, **155** and an outflow port **158**. The inflow port(s) **154**, **155** can comprise threaded sockets **157** configured to receive proximal portions of the catheters **112**, **114**. Desirably, the sockets **157** are a suitable size to securely receive and hold flexible tubing sized between 1 Fr and 9 Fr. Generally, a user cinches the sockets **157** around the respective catheter tubes **122** by spinning the socket **157** into the ports **154**, **155** in the direction of arrow A1 (shown in FIG. 17B).

[0296] Once the catheters **112**, **114** are mounted to the connector **150**, urine entering the connector **150** through the vacuum inflow ports **154**, **155** is directed through a fluid conduit in the direction of arrow A2 (shown in FIG. 17B) to the vacuum outflow port **158**. The vacuum outflow port **158** can be connected to the fluid collection container **712** and/or pump assembly **710** (shown in FIG. 19) by, for example, flexible tubing **166** defining a fluid flow path.

[0297] With specific reference to FIG. 17C, another exemplary connector **150** can be configured to connect three or more catheters **112**, **114**, **116** to outflow ports **158**, **162**. The connector **150** can comprise a structure or body having a

distal side 152 comprising two or more vacuum inflow ports 154, 155 configured to be connected to proximal ends of the ureteral catheters 112, 114, and a separate gravity drainage port 156 configured to connect to the proximal end of the bladder catheter 116. The vacuum ports 154, 155 and/or proximal ends of the ureteral catheters 112, 114 can comprise a specific configuration to ensure that the ureteral catheters 112, 114 are connected to the vacuum source and not to some other fluid collection assembly. Similarly, the gravity drainage port 156 and/or proximal end of the bladder catheter 116 can comprise another connector configuration to ensure that the bladder catheter 116 and not one of the ureteral catheters 112, 114 is permitted to drain by gravity drainage. In other examples, the ports 154, 155, 156 and/or proximal ends of the catheters 112, 114, 116 can include visual indicia to assist in correctly setting up the fluid collection system.

[0298] In some examples, urine received in the vacuum ports 154, 155 can be directed through a Y-shaped conduit to a single vacuum outflow port 158 located on a proximal side 160 of the connector 150. As in previously-described examples, the vacuum outflow port 158 can be connected to the fluid collection container 712 and/or pump 710 by suitable flexible tubing or other conduits for drawing urine from the body and for inducing negative pressure in the ureters and/or kidneys. In some examples, the outflow port 156 and/or connector 150 can be configured to attach only to vacuum sources or pumps operating within a predetermined pressure range or power level to prevent exposing the ureteral catheters 112, 114 to elevated levels or intensity of negative pressure. The proximal side 160 of the connector 150 can also comprise a gravity outflow port 162 in fluid communication with the inflow port 156. The gravity outflow port 162 can be configured to be connected directly to the urine collection container 712 for urine collection by gravity drainage.

[0299] With continued reference to FIG. 17C, in some examples, in order to facilitate system setup and implementation, the vacuum outflow port 158 and the gravity outflow port 162 are disposed in close proximity so that a single socket 164, bracket, or connector can be coupled to the connector 150 to establish fluid communication with each port 158, 162. The single socket or connector can be coupled to a multi-conduit hose or tube (e.g., flexible tubing 166) having a first conduit in fluid communication with the pump 710 and a second conduit in fluid communication with the collection container 712. Accordingly, a user can easily set up the external fluid collection system by inserting the single socket 164 in the connector 150 and connecting the respective conduits to one of the fluid collection container 712 and pump 710 (shown in FIG. 19). In other examples, a length of flexible tubing 166 is connected between the urine collection container 712 and the gravity outflow port 162, and a separate length of flexible tubing is connected between the pump 710 and the vacuum outflow port 158.

[0300] Exemplary Fluid Sensors:

[0301] With reference again to FIG. 1, in some examples, the assembly 100 further comprises sensors 174 for monitoring fluid characteristics of urine being collected from the ureters 6, 8 and/or bladder 10. As discussed herein in connection with FIG. 19, information obtained from the sensors 174 can be transmitted to a central data collection module or processor and used, for example, to control operation of an external device, such as the pump 710

(shown in FIG. 19). The sensors 174 can be integrally formed with one or more of the catheters 112, 114, 116 such as, for example, embedded in a wall of the catheter body or tube and in fluid communication with drainage lumens 124, 140. In other examples, one or more of the sensors 174 can be positioned in a fluid collection container 712 (shown in FIG. 19) or in internal circuitry of an external device, such as the pump 710.

[0302] Exemplary sensors 174 that can be used with the urine collection assembly 100 can comprise one or more of the following sensor types. For example, the catheter assembly 100 can comprise a conductance sensor or electrode that samples conductivity of urine. The normal conductance of human urine is about 5-10 mS/m. Urine having a conductance outside of the expected range can indicate that the patient is experiencing a physiological problem, which requires further treatment or analysis. The catheter assembly 100 can also comprise a flow meter for measuring a flow rate of urine through the catheter(s) 112, 114, 116. Flow rate can be used to determine a total volume of fluid excreted from the body. The catheter(s) 112, 114, 116 can also comprise a thermometer for measuring urine temperature. Urine temperature can be used to collaborate the conductance sensor. Urine temperature can also be used for monitoring purposes, as urine temperature outside of a physiologically normal range can be indicative of certain physiological conditions. In some examples, the sensors 174 can be urine analyte sensors configured to measure a concentration of creatinine and/or proteins in urine. For example, various conductivity sensors and optical spectrometry sensors may be used for determining analyte concentration in urine. Sensors based on color change reagent test strips may also be used for this purpose.

Method of Insertion of a Urine Collection Assembly:

[0303] Having described the urine collection assembly 100 including the ureteral catheter retention portions and bladder anchor device (e.g., a standard or modified Foley-type catheter), methods for insertion and deployment of the assemblies will now be discussed in detail.

[0304] With reference to FIG. 18A, steps for positioning a fluid collection assembly in a patient's body and, optionally, for inducing negative pressure in a patient's ureter and/or kidneys are illustrated. As shown at box 610, a medical professional or caregiver inserts a flexible or rigid cystoscope through the patient's urethra and into the bladder to obtain visualization of the ureteral orifices or openings. Once suitable visualization is obtained, as shown at box 612, a guidewire is advanced through the urethra, bladder, ureteral opening, ureter, and to a desired fluid collection position, such as the renal pelvis of the kidney. Once the guidewire is advanced to the desired fluid collection position, a ureteral catheter of the present invention (examples of which are discussed in detail above) is inserted over the guidewire to the fluid collection position, as shown at box 614. In some examples, the location of the ureteral catheter can be confirmed by fluoroscopy, as shown at box 616. Once the position of the distal end of the catheter is confirmed, as shown at box 618, the retention portion of the ureteral catheter can be deployed. For example, the guidewire can be removed from the catheter, thereby allowing the distal end and/or retention portion to transition to a deployed position. In some examples, the deployed distal end portion of the catheter does not entirely occlude the ureter and/or renal

pelvis, such that urine is permitted to pass outside the catheter and through the ureters into the bladder. Since moving the catheter can exert forces against urinary tract tissues, avoiding complete blockage of the ureters avoids application of force to the ureter sidewalls, which may cause injury.

[0305] After the ureteral catheter is in place and deployed, the same guidewire can be used to position a second ureteral catheter in the other ureter and/or kidney using the same insertion and positioning methods described herein. For example, the cystoscope can be used to obtain visualization of the other ureteral opening in the bladder, and the guidewire can be advanced through the visualized ureteral opening to a fluid collection position in the other ureter. A catheter can be drawn alongside the guidewire and deployed in the manner described herein. Alternatively, the cystoscope and guidewire can be removed from the body. The cystoscope can be reinserted into the bladder over the first ureteral catheter. The cystoscope is used, in the manner described above, to obtain visualization of the ureteral opening and to assist in advancing a second guidewire to the second ureter and/or kidney for positioning of the second ureteral catheter. Once the ureteral catheters are in place, in some examples, the guidewire and cystoscope are removed. In other examples, the cystoscope and/or guidewire can remain in the bladder to assist with placement of the bladder catheter.

[0306] Optionally, a bladder catheter can also be used. Once the ureteral catheters are in place, as shown at box 620, the medical professional or caregiver can insert a distal end of a bladder catheter in a collapsed or contracted state through the urethra of the patient and into the bladder. The bladder catheter can be a conventional Foley bladder catheter or a bladder catheter of the present invention as discussed in detail above. Once inserted in the bladder, as shown at box 622, an anchor connected to and/or associated with the bladder catheter is expanded to a deployed position. For example, when an expandable or inflatable catheter is used, fluid may be directed through an inflation lumen of the bladder catheter to expand a balloon structure located in the patient's bladder. In some examples, the bladder catheter is inserted through the urethra and into the bladder without using a guidewire and/or cystoscope. In other examples, the bladder catheter is inserted over the same guidewire used to position the ureteral catheters. Accordingly, when inserted in this manner, the ureteral catheters can be arranged to extend from the distal end of the bladder catheter and, optionally, proximal ends of the ureteral catheters can be arranged to terminate in a drainage lumen of the bladder catheter.

[0307] In some examples, the urine is permitted to drain by gravity from the urethra. In other examples, a negative pressure is induced in the ureteral catheter and/or bladder catheter to facilitate drainage of the urine.

[0308] With reference to FIG. 18B, steps for using the urine collection assembly for inducement of negative pressure in the ureter(s) and/or kidney(s) are illustrated. As shown at box 624, after the indwelling portions of the bladder and/or ureteral catheters are correctly positioned and anchoring/retention structures are deployed, the external proximal ends of the catheter(s) are connected to fluid collection or pump assemblies. For example, the ureteral catheter(s) can be connected to a pump for inducing negative pressure at the patient's renal pelvis and/or kidney. In a similar manner, the bladder catheter can be connected directly to a urine collection container for gravity drainage

of urine from the bladder or connected to a pump for inducing negative pressure at the bladder.

[0309] Once the catheter(s) and pump assembly are connected, negative pressure is applied to the renal pelvis and/or kidney and/or bladder through the drainage lumens of the ureteral catheters and/or bladder catheter, as shown at box 626. The negative pressure is intended to counter congestion mediated interstitial hydrostatic pressures due to elevated intra-abdominal pressure and consequential or elevated renal venous pressure or renal lymphatic pressure. The applied negative pressure is therefore capable of increasing flow of filtrate through the medullary tubules and of decreasing water and sodium re-absorption.

[0310] In some examples, mechanical stimulation can be provided to portions of the ureters and/or renal pelvis to supplement or modify therapeutic effects obtained by application of negative pressure. For example, mechanical stimulation devices, such as linear actuators and other known devices for providing, for example, vibration waves, disposed in distal portions of the ureteral catheter(s) can be actuated. While not intending to be bound by theory, it is believed that such stimulation effects adjacent tissues by, for example, stimulating nerves and/or actuating peristaltic muscles associated with the ureter(s) and/or renal pelvis. Stimulation of nerves and activation of muscles may produce changes in pressure gradients or pressure levels in surrounding tissues and organs which may contribute to or, in some cases, enhance therapeutic benefits of negative pressure therapy. In some examples, the mechanical stimulation can comprise pulsating stimulation. In other examples, low levels of mechanical stimulation can be provided continuously as negative pressure is being provided through the ureteral catheter(s). In other examples, inflatable portions of the ureteral catheter could be inflated and deflated in a pulsating manner to stimulate adjacent nerve and muscle tissue, in a similar manner to actuation of the mechanical stimulation devices described herein.

[0311] As a result of the applied negative pressure, as shown at box 628, urine is drawn into the catheter at the plurality of drainage ports at the distal end thereof, through the drainage lumen of the catheter, and to a fluid collection container for disposal. As the urine is being drawn to the collection container, at box 630, sensors disposed in the fluid collection system provide a number of measurements about the urine that can be used to assess the volume of urine collected, as well as information about the physical condition of the patient and composition of the urine produced. In some examples, the information obtained by the sensors is processed, as shown at box 632, by a processor associated with the pump and/or with another patient monitoring device and, at box 634, is displayed to the user via a visual display of an associated feedback device.

Exemplary Fluid Collection System:

[0312] Having described an exemplary urine collection assembly and method of positioning such an assembly in the patient's body, with reference to FIG. 19, a system 700 for inducing negative pressure to a patient's ureter(s) and/or kidney(s) will now be described. The system 700 can comprise the ureteral catheter(s), bladder catheter or the urine collection assembly 100 described hereinabove. As shown in FIG. 19, ureteral catheters 112, 114 and/or the bladder catheter 116 of the assembly 100 are connected to one or more fluid collection containers 712 for collecting

urine drawn from the renal pelvis and/or bladder. In some examples, the bladder catheter 116 and the ureteral catheters 112, 114 are connected to different fluid collection containers 712. The fluid collection container 712 connected to the ureteral catheter(s) 112, 114 can be in fluid communication with an external fluid pump 710 for generating negative pressure in the ureter(s) and kidney(s) through the ureteral catheter(s) 112, 114. As discussed herein, such negative pressure can be provided for overcoming interstitial pressure and forming urine in the kidney or nephron. In some examples, a connection between the fluid collection container 712 and pump 710 can comprise a fluid lock or fluid barrier to prevent air from entering the renal pelvis or kidney in case of incidental therapeutic or non-therapeutic pressure changes. For example, inflow and outflow ports of the fluid container can be positioned below a fluid level in the container. Accordingly, air is prevented from entering medical tubing or the catheter through either the inflow or outflow ports of the fluid container 712. As discussed previously, external portions of the tubing extending between the fluid collection container 712 and the pump 710 can include one or more filters to prevent urine and/or particulates from entering the pump 710.

[0313] As shown in FIG. 19, the system 700 further comprises a controller 714, such as a microprocessor, electronically coupled to the pump 710 and having or associated with computer readable memory 716. In some examples, the memory 716 comprises instructions that, when executed, cause the controller 714 to receive information from sensors 174 located on or associated with portions of the assembly 100. Information about a condition of the patient can be determined based on information from the sensors 174. Information from the sensors 174 can also be used to determine and implement operating parameters for the pump 710.

[0314] In some examples, the controller 714 is incorporated in a separate and remote electronic device in communication with the pump 710, such as a dedicated electronic device, computer, tablet PC, or smart phone. Alternatively, the controller 714 can be included in the pump 710 and, for example, can control both a user interface for manually operating the pump 710, as well as system functions such as receiving and processing information from the sensors 174.

[0315] The controller 714 is configured to receive information from the one or more sensors 174 and to store the information in the associated computer-readable memory 716. For example, the controller 714 can be configured to receive information from the sensor 174 at a predetermined rate, such as once every second, and to determine a conductance based on the received information. In some examples, the algorithm for calculating conductance can also include other sensor measurements, such as urine temperature, to obtain a more robust determination of conductance.

[0316] The controller 714 can also be configured to calculate patient physical statistics or diagnostic indicators that illustrate changes in the patient's condition over time. For example, the system 700 can be configured to identify an amount of total sodium excreted. The total sodium excreted may be based, for example, on a combination of flow rate and conductance over a period of time.

[0317] With continued reference to FIG. 19, the system 700 can further comprise a feedback device 720, such as a visual display or audio system, for providing information to

the user. In some examples, the feedback device 720 can be integrally formed with the pump 710. Alternatively, the feedback device 720 can be a separate dedicated or a multipurpose electronic device, such as a computer, laptop computer, tablet PC, smart phone, or other handheld electronic devices. The feedback device 720 is configured to receive the calculated or determined measurements from the controller 714 and to present the received information to a user via the feedback device 720. For example, the feedback device 720 may be configured to display current negative pressure (in mmHg) being applied to the urinary tract. In other examples, the feedback device 720 is configured to display current flow rate of urine, temperature, current conductance in mS/m of urine, total urine produced during the session, total sodium excreted during the session, other physical parameters, or any combination thereof.

[0318] In some examples, the feedback device 720 further comprises a user interface module or component that allows the user to control operation of the pump 710. For example, the user can engage or turn off the pump 710 via the user interface. The user can also adjust pressure applied by the pump 710 to achieve a greater magnitude or rate of sodium excretion and fluid removal.

[0319] Optionally, the feedback device 720 and/or pump 710 further comprise a data transmitter 722 for sending information from the device 720 and/or pump 710 to other electronic devices or computer networks. The data transmitter 722 can utilize a short-range or long-range data communications protocol. An example of a short-range data transmission protocol is Bluetooth®. Long-range data transmission networks include, for example, Wi-Fi or cellular networks. The data transmitter 722 can send information to a patient's physician or caregiver to inform the physician or caregiver about the patient's current condition. Alternatively, or in addition, information can be sent from the data transmitter 722 to existing databases or information storage locations, such as, for example, to include the recorded information in a patient's electronic health record (EHR).

[0320] With continued reference to FIG. 19, in addition to the urine sensors 174, in some examples, the system 700 further comprises one or more patient monitoring sensors 724. Patient monitoring sensors 724 can include invasive and non-invasive sensors for measuring information about the patient's urine composition, as discussed in detail above, blood composition (e.g., hematocrit ratio, analyte concentration, protein concentration, creatinine concentration) and/or blood flow (e.g., blood pressure, blood flow velocity). Hematocrit is a ratio of the volume of red blood cells to the total volume of blood. Normal hematocrit is about 25% to 40%, and preferably about 35% and 40% (e.g., 35% to 40% red blood cells by volume and 60% to 65% plasma).

[0321] Non-invasive patient monitoring sensors 724 can include pulse oximetry sensors, blood pressure sensors, heart rate sensors, and respiration sensors (e.g., a capnography sensor). Invasive patient monitoring sensors 724 can include invasive blood pressure sensors, glucose sensors, blood velocity sensors, hemoglobin sensors, hematocrit sensors, protein sensors, creatinine sensors, and others. In still other examples, sensors may be associated with an extracorporeal blood system or circuit and configured to measure parameters of blood passing through tubing of the extracorporeal system. For example, analyte sensors, such as capacitance sensors or optical spectroscopy sensors, may be asso-

ciated with tubing of the extracorporeal blood system to measure parameter values of the patient's blood as it passes through the tubing. The patient monitoring sensors 724 can be in wired or wireless communication with the pump 710 and/or controller 714.

[0322] In some examples, the controller 714 is configured to cause the pump 710 to provide treatment for a patient based information obtained from the urine analyte sensor 174 and/or patient monitoring sensors 724, such as blood monitoring sensors. For example, pump 710 operating parameters can be adjusted based on changes in the patient's blood hematocrit ratio, blood protein concentration, creatinine concentration, urine output volume, urine protein concentration (e.g., albumin), and other parameters. For example, the controller 714 can be configured to receive information about a blood hematocrit ratio or creatinine concentration of the patient from the patient monitoring sensors 724 and/or analyte sensors 174. The controller 714 can be configured to adjust operating parameters of the pump 710 based on the blood and/or urine measurements. In other examples, hematocrit ratio may be measured from blood samples periodically obtained from the patient. Results of the tests can be manually or automatically provided to the controller 714 for processing and analysis.

[0323] As discussed herein, measured hematocrit values for the patient can be compared to predetermined threshold or clinically acceptable values for the general population. Generally, hematocrit levels for females are lower than for males. In other examples, measured hematocrit values can be compared to patient baseline values obtained prior to a surgical procedure. When the measured hematocrit value is increased to within the acceptable range, the pump 710 may be turned off ceasing application of negative pressure to the ureter or kidneys. In a similar manner, the intensity of negative pressure can be adjusted based on measured parameter values. For example, as the patient's measured parameters begin to approach the acceptable range, intensity of negative pressure being applied to the ureter and kidneys can be reduced. In contrast, if an undesirable trend (e.g., a decrease in hematocrit value, urine output rate, and/or creatinine clearance) is identified, the intensity of negative pressure can be increased in order to produce a positive physiological result. For example, the pump 710 may be configured to begin by providing a low level of negative pressure (e.g., between about 0.1 mmHg and 10 mmHg). The negative pressure may be incrementally increased until a positive trend in patient creatinine level is observed. However, generally, negative pressure provided by the pump 710 will not exceed about 50 mmHg.

[0324] With reference to FIGS. 20A and 20B, an exemplary pump 710 for use with the system is illustrated. In some examples, the pump 710 is a micro-pump configured to draw fluid from the catheter(s) 112, 114 (shown, for example, in FIG. 1) and having a sensitivity or accuracy of about 10 mmHg or less. Desirably, the pump 710 is capable of providing a range of flow of urine between 0.05 ml/min and 3 ml/min for extended periods of time, for example, for about 8 hours to about 24 hours per day, for one (1) to about 30 days or longer. At 0.2 ml/min, it is anticipated that about 300 mL of urine per day is collected by the system 700. The pump 710 can be configured to provide a negative pressure to the bladder of the patient, the negative pressure ranging between about 0.1 mmHg and 50 mmHg or about 5 mmHg to about 20 mmHg (gauge pressure at the pump 710). For

example, a micro-pump manufactured by Langer Inc. (Model BT100-2J) can be used with the presently disclosed system 700. Diaphragm aspirator pumps, as well as other types of commercially available pumps, can also be used for this purpose. Peristaltic pumps can also be used with the system 700. In other examples, a piston pump, vacuum bottle, or manual vacuum source can be used for providing negative pressure. In other examples, the system can be connected to a wall suction source, as is available in a hospital, through a vacuum regulator for reducing negative pressure to therapeutically appropriate levels.

[0325] In some examples, the pump 710 is configured for extended use and, thus, is capable of maintaining precise suction for extended periods of time, for example, for about 8 hours to about 24 hours per day, for 1 to about 30 days or longer. Further, in some examples, the pump 710 is configured to be manually operated and, in that case, includes a control panel 718 that allows a user to set a desired suction value. The pump 710 can also include a controller or processor, which can be the same controller that operates the system 700 or can be a separate processor dedicated for operation of the pump 710. In either case, the processor is configured for both receiving instructions for manual operation of the pump and for automatically operating the pump 710 according to predetermined operating parameters. Alternatively, or in addition, operation of the pump 710 can be controlled by the processor based on feedback received from the plurality of sensors associated with the catheter.

[0326] In some examples, the processor is configured to cause the pump 710 to operate intermittently. For example, the pump 710 may be configured to emit pulses of negative pressure followed by periods in which no negative pressure is provided. In other examples, the pump 710 can be configured to alternate between providing negative pressure and positive pressure to produce an alternating flush and pump effect. For example, a positive pressure of about 0.1 mmHg to 20 mmHg, and preferably about 5 mmHg to 20 mmHg can be provided followed by a negative pressure ranging from about 0.1 mmHg to 50 mmHg.

Treatment for Removing Excess Fluid from a Patient with Hemodilution

[0327] According to another aspect of the disclosure, a method for removing excess fluid from a patient with hemodilution is provided. In some examples, hemodilution can refer to an increase in a volume of plasma in relation to red blood cells and/or a reduced concentration of red blood cells in circulation, as may occur when a patient is provided with an excessive amount of fluid. The method can involve measuring and/or monitoring patient hematocrit levels to determine when hemodilution has been adequately addressed. Low hematocrit levels are a common post-surgical or post-trauma condition that can lead to undesirable therapeutic outcomes. As such, management of hemodilution and confirming that hematocrit levels return to normal ranges is a desirable therapeutic result for surgical and post-surgical patient care.

[0328] Steps for removing excess fluid from a patient using the devices and systems described herein are illustrated in FIG. 24. As shown in FIG. 24, the treatment method comprises deploying a urinary tract catheter, such as a ureteral catheter, in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney, as shown at box 910. The catheter may be placed to avoid occluding the ureter and/or kidney. In some examples, a fluid collecting

portion of the catheter may be positioned in the renal pelvis of the patient's kidney. In some examples, a ureter catheter may be positioned in each of the patient's kidneys. In other examples, a urine collection catheter may be deployed in the bladder or ureter. In some examples, the ureteral catheter comprises one or more of any of the retention portions described herein. For example, the ureteral catheter can comprise a tube defining a drainage lumen comprising a helical retention portion and a plurality of drainage ports. In other examples, the catheter can include an inflatable retention portion (e.g., a balloon catheter), funnel-shaped fluid collection and retention portion, or a pigtail coil.

[0329] As shown at box 912, the method further comprises applying negative pressure to the ureter and/or kidney through the catheter to induce production of urine in the kidney(s) and to extract urine from the patient. Desirably, negative pressure is applied for a period of time sufficient to reduce the patient's blood creatinine levels by a clinically significant amount.

[0330] Negative pressure may continue to be applied for a predetermined period of time. For example, a user may be instructed to operate the pump for the duration of a surgical procedure or for a time period selected based on physiological characteristics of the patient. In other examples, patient condition may be monitored to determine when sufficient treatment has been provided. For example, as shown at box 914, the method may further comprise monitoring the patient to determine when to cease applying negative pressure to the patient's ureter and/or kidneys. In a preferred and non-limiting example, a patient's hematocrit level is measured. For example, patient monitoring devices may be used to periodically obtain hematocrit values. In other examples, blood samples may be drawn periodically to directly measure hematocrit. In some examples, concentration and/or volume of urine expelled from the body through the catheter may also be monitored to determine a rate at which urine is being produced by the kidneys. In a similar manner, expelled urine output may be monitored to determine protein concentration and/or creatinine clearance rate for the patient. Reduced creatinine and protein concentration in urine may be indicative of over-dilution and/or depressed renal function. Measured values can be compared to the predetermined threshold values to assess whether negative pressure therapy is improving patient condition, and should be modified or discontinued. For example, as discussed herein, a desirable range for patient hematocrit may be between 25% and 40%. In other preferred and non-limiting examples, as described herein, patient body weight may be measured and compared to a dry body weight. Changes in measured patient body weight demonstrate that fluid is being removed from the body. As such, a return to dry body weight represents that hemodilution has been appropriately managed and the patient is not over-diluted.

[0331] As shown at box 916, a user may cause the pump to cease providing negative pressure therapy when a positive result is identified. In a similar manner, patient blood parameters may be monitored to assess effectiveness of the negative pressure being applied to the patient's kidneys. For example, a capacitance or analyte sensor may be placed in fluid communication with tubing of an extracorporeal blood management system. The sensor may be used to measure information representative of blood protein, oxygen, creatinine, and/or hematocrit levels. Measured blood parameter values may be measured continuously or periodically and

compared to various threshold or clinically acceptable values. Negative pressure may continue to be applied to the patient's kidney or ureter until a measured parameter value falls within a clinically acceptable range. Once a measured values fails within the threshold or clinically acceptable range, as shown at box 916, application of negative pressure may cease.

Treatment of Patients Undergoing a Fluid Resuscitation Procedure

[0332] According to another aspect of the disclosure, a method for removing excess fluid for a patient undergoing a fluid resuscitation procedure, such as coronary graft bypass surgery, by removing excess fluid from the patient is provided. During fluid resuscitation, solutions such as saline solutions and/or starch solutions, are introduced to the patient's bloodstream by a suitable fluid delivery process, such as an intravenous drip. For example, in some surgical procedures, a patient may be supplied with between 5 and 10 times a normal daily intake of fluid. Fluid replacement or fluid resuscitation can be provided to replace bodily fluids lost through sweating, bleeding, dehydration, and similar processes. In the case of a surgical procedure such as coronary graft bypass, fluid resuscitation is provided to help maintain a patient's fluid balance and blood pressure within an appropriate rate. Acute kidney injury (AKI) is a known complication of coronary artery graft bypass surgery. AKI is associated with a prolonged hospital stay and increased morbidity and mortality, even for patients who do not progress to renal failure. See Kim, et al., *Relationship between a perioperative intravenous fluid administration strategy and acute kidney injury following off-pump coronary artery bypass surgery: an observational study*, *Critical Care* 19:350 (1995). Introducing fluid to blood also reduces hematocrit levels which has been shown to further increase mortality and morbidity. Research has also demonstrated that introducing saline solution to a patient may depress renal functional and/or inhibit natural fluid management processes. As such, appropriate monitoring and control of renal function may produce improved outcomes and, in particular, may reduce post-operative instances of AKI.

[0333] A method of treating a patient undergoing fluid resuscitation is illustrated in FIG. 25. As shown at box 1010, the method comprises deploying a ureteral catheter in the ureter and/or kidney of a patient such that flow of urine from the ureter and/or kidney is not prevented by occlusion of the ureter and/or kidney. For example, a fluid collecting portion of the catheter may be positioned in the renal pelvis. In other examples, the catheter may be deployed in the bladder or ureter. The catheter can comprise one or more of the ureter catheters described herein. For example, the catheter can comprise a tube defining a drainage lumen and comprising a helical retention portion and a plurality of drainage ports. In other examples, the catheter can include an inflatable retention portion (e.g., a balloon catheter) or a pigtail coil.

[0334] As shown at box 1012, optionally, a bladder catheter may also be deployed in the patient's bladder. For example, the bladder catheter may be positioned to seal the urethra opening to prevent passage of urine from the body through the urethra. The bladder catheter can include an inflatable anchor (e.g., a Foley catheter) for maintaining the distal end of the catheter in the bladder. As described herein, other arrangements of coils and helices may also be used to obtain proper positioning of the bladder catheter. The blad-

der catheter can be configured to collect urine which entered the patient's bladder prior to placement of the ureteral catheter(s). The bladder catheter may also collect urine which flows past the fluid collection portion(s) of the ureteral catheter and enters the bladder. In some examples, a proximal portion of the ureteral catheter may be positioned in a drainage lumen of the bladder catheter. In a similar manner, the bladder catheter may be advanced into the bladder using the same guidewire used for positioning of the ureteral catheter(s). In some examples, negative pressure may be provided to the bladder through the drainage lumen of the bladder catheter. In other examples, negative pressure may only be applied to the ureteral catheter(s). In that case, the bladder catheter drains by gravity.

[0335] As shown at box **1014**, following deployment of the ureteral catheter(s), negative pressure is applied to the ureter and/or kidney through the ureteral catheter(s). For example, negative pressure can be applied for a period of time sufficient to extract urine comprising a portion of the fluid provided to the patient during the fluid resuscitation procedure. As described herein, negative pressure can be provided by an external pump connected to a proximal end or port of the catheter. The pump can be operated continually or periodically dependent on therapeutic requirements of the patient. In some cases, the pump may alternate between applying negative pressure and positive pressure.

[0336] Negative pressure may continue to be applied for a predetermined period of time. For example, a user may be instructed to operate the pump for the duration of a surgical procedure or for a time period selected based on physiological characteristics of the patient. In other examples, patient condition may be monitored to determine when a sufficient amount of fluid has been drawn from the patient. For example, as shown at box **1016**, fluid expelled from the body may be collected and a total volume of obtained fluid may be monitored. In that case, the pump can continue to operate until a predetermined fluid volume has been collected from the ureteral and/or bladder catheters. The predetermined fluid volume may be based, for example, on a volume of fluid provided to the patient prior to and during the surgical procedure. As shown at box **1018**, application of negative pressure to the ureter and/or kidneys is stopped when the collected total volume of fluid exceeds the predetermined fluid volume.

[0337] In other examples, operation of the pump can be determined based on measured physiological parameters of the patient, such as measured creatinine clearance, blood creatinine level, or hematocrit ratio. For example, as shown at box **1020**, urine collected from the patient may be analyzed by one or more sensors associated with the catheter and/or pump. The sensor can be a capacitance sensor, analyte sensor, optical sensor, or similar device configured to measure urine analyte concentration. In a similar manner, as shown at box **1022**, a patient's blood creatinine or hematocrit level could be analyzed based on information obtain from the patient monitoring sensors discussed hereinabove. For example, a capacitance sensor may be placed in an existing extracorporeal blood system. Information obtained by the capacitance sensor may be analyzed to determine a patient's hematocrit ratio. The measured hematocrit ratio may be compared to certain expected or therapeutically acceptable values. The pump may continue to apply negative pressure to the patient's ureter and/or kidney until measured values within the therapeutically acceptable

range are obtained. Once a therapeutically acceptable value is obtained, application of negative pressure may be stopped as shown at box **1018**.

[0338] In other examples, as shown at box **2024**, patient body weight may be measured to assess whether fluid is being removed from the patient by the applied negative pressure therapy. For example, a patient's measured body-weight (including fluid introduced during a fluid resuscitation procedure) can be compared to a patient's dry body weight. As used herein, dry weights is defined as normal body weight measured when a patient is not over-diluted. For example, a patient who is not experiencing one or more of: elevated blood pressure, lightheadedness or cramping, swelling of legs, feet, arms, hands, or around the eyes, and who is breathing comfortably, likely does not have excess fluid. A weight measured when the patient is not experiencing such symptoms can be a dry body weight. Patient weight can be measured periodically until the measured weight approaches the dry body weight. When the measured weight approaches (e.g., is within between 5% and 10% of dry body weight), as shown at box **1018**, application of negative pressure can be stopped.

EXPERIMENTAL EXAMPLES

[0339] Inducement of negative pressure within the renal pelvis of farm swine was performed for the purpose of evaluating effects of negative pressure therapy on renal congestion in the kidney. An objective of these studies was to demonstrate whether a negative pressure delivered into the renal pelvis significantly increases urine output in a swine model of renal congestion. In Example 1, a pediatric Fogarty catheter, normally used in embolectomy or bronchoscopy applications, was used in the swine model solely for proof of principle for inducement of negative pressure in the renal pelvis. It is not suggested that a Fogarty catheter be used in humans in clinical settings to avoid injury of urinary tract tissues. In Example 2, the ureteral catheter **112** shown in FIGS. **2A** and **2B**, and including a helical retention portion for mounting or maintaining a distal portion of the catheter in the renal pelvis or kidney, was used.

Example 1

[0340] Method

[0341] Four farm swine **800** were used for purposes of evaluating effects of negative pressure therapy on renal congestion in the kidney. As shown in FIG. **21**, pediatric Fogarty catheters **812**, **814** were inserted to the renal pelvis region **820**, **821** of each kidney **802**, **804** of the four swine **800**. The catheters **812**, **814** were deployed within the renal pelvis region by inflating an expandable balloon to a size sufficient to seal the renal pelvis and to maintain the position of the balloon within the renal pelvis. The catheters **812**, **814** extend from the renal pelvis **802**, **804**, through a bladder **810** and urethra **816**, and to fluid collection containers external to the swine.

[0342] Urine output of two animals was collected for a 15 minute period to establish a baseline for urine output volume and rate. Urine output of the right kidney **802** and the left kidney **804** were measured individually and found to vary considerably. Creatinine clearance values were also determined.

[0343] Renal congestion (e.g., congestion or reduced blood flow in the veins of the kidney) was induced in the

right kidney **802** and the left kidney **804** of the animal **800** by partially occluding the inferior vena cava (IVC) with an inflatable balloon catheter **850** just above to the renal vein outflow. Pressure sensors were used to measure IVC pressure. Normal IVC pressures were 1-4 mmHg. By inflating the balloon of the catheter **850** to approximately three quarters of the IVC diameter, the IVC pressures were elevated to between 15-25 mmHg. Inflation of the balloon to approximately three quarters of IVC diameter resulted in a 50-85% reduction in urine output. Full occlusion generated IVC pressures above 28 mmHg and was associated with at least a 95% reduction in urine output.

[0344] One kidney of each animal **800** was not treated and served as a control (“the control kidney **802**”). The ureteral catheter **812** extending from the control kidney was connected to a fluid collection container **819** for determining fluid levels. One kidney (“the treated kidney **804**”) of each animal was treated with negative pressure from a negative pressure source (e.g., a therapy pump **818** in combination with a regulator designed to more accurately control the low magnitude of negative pressures) connected to the ureteral catheter **814**. The pump **818** was an Air Cadet Vacuum Pump from Cole-Parmer Instrument Company (Model No. EW-07530-85). The pump **818** was connected in series to the regulator. The regulator was an V-800 Series Miniature Precision Vacuum Regulator—1/8 NPT Ports (Model No. V-800-10-W/K), manufactured by Airtrol Components Inc.

[0345] The pump **818** was actuated to induce negative pressure within the renal pelvis **820**, **821** of the treated kidney according to the following protocol. First, the effect of negative pressure was investigated in the normal state (e.g., without inflating the IVC balloon). Four different pressure levels (-2, -10, -15, and -20 mmHg) were applied for 15 minutes each and the rate of urine produced and creatinine clearance were determined. Pressure levels were controlled and determined at the regulator. Following the -20 mmHg therapy, the IVC balloon was inflated to increase the pressure by 15-20 mmHg. The same four negative pressure levels were applied. Urine output rate and creatinine clearance rate for the congested control kidney **802** and treated kidney **804** were obtained. The animals **800** were subject to congestion by partial occlusion of the IVC for 90 minutes. Treatment was provided for 60 minutes of the 90 minute congestion period.

[0346] Following collection of urine output and creatinine clearance data, kidneys from one animal were subjected to gross examination then fixed in a 10% neutral buffered formalin. Following gross examination, histological sections were obtained, examined, and magnified images of the sections were captured. The sections were examined using an upright Olympus BX41 light microscope and images were captured using an Olympus DP25 digital camera. Specifically, photomicrograph images of the sampled tissues were obtained at low magnification (20x original magnification) and high magnification (100x original magnification). The obtained images were subjected to histological evaluation. The purpose of the evaluation was to examine the tissue histologically and to qualitatively characterize congestion and tubular degeneration for the obtained samples.

[0347] Surface mapping analysis was also performed on obtained slides of the kidney tissue. Specifically, the samples were stained and analyzed to evaluate differences in size of tubules for treated and untreated kidneys. Image processing techniques calculated a number and/or relative percentage of pixels with different coloration in the stained images. Cal-

culated measurement data was used to determine volumes of different anatomical structures.

[0348] Results

[0349] Urine Output and Creatinine Clearance

[0350] Urine output rates were highly variable. Three sources of variation in urine output rate were observed during the study. The inter-individual and hemodynamic variability were anticipated sources of variability known in the art. A third source of variation in urine output, upon information and belief believed to be previously unknown, was identified in the experiments discussed herein, namely, contralateral intra-individual variability in urine output.

[0351] Baseline urine output rates were 0.79 ml/min for one kidney and 1.07 ml/min for the other kidney (e.g., a 26% difference). The urine output rate is a mean rate calculated from urine output rates for each animal.

[0352] When congestion was provided by inflating the IVC balloon, the treated kidney urine output dropped from 0.79 ml/min to 0.12 ml/min (15.2% of baseline). In comparison, the control kidney urine output rate during congestion dropped from 1.07 ml/min to 0.09 ml/min (8.4% of baseline). Based on urine output rates, a relative increase in treated kidney urine output compared to control kidney urine output was calculated, according to the following equation:

$$\frac{(\text{Therapy Treated}/\text{Baseline Treated})}{(\text{Therapy Control}/\text{Baseline Control})} = \text{Relative increase}$$

$$(0.12 \text{ ml/min}/0.79 \text{ ml/min}) / (0.09 \text{ ml/min}/1.07 \text{ ml/min}) = 180.6\%$$

[0353] Thus, the relative increase in treated kidney urine output rate was 180.6% compared to control. This result shows a greater magnitude of decrease in urine production caused by congestion on the control side when compared to the treatment side. Presenting results as a relative percentage difference in urine output adjusts for differences in urine output between kidneys.

[0354] Creatinine clearance measurements for baseline, congested, and treated portions for one of the animals are shown in FIG. 22.

[0355] Gross Examination and Histological Evaluation

[0356] Based on gross examination of the control kidney (right kidney) and treated kidney (left kidney), it was determined that the control kidney had a uniformly dark red-brown color, which corresponds with more congestion in the control kidney compared to the treated kidney. Qualitative evaluation of the magnified section images also noted increased congestion in the control kidney compared to the treated kidney. Specifically, as shown in Table 1, the treated kidney exhibited lower levels of congestion and tubular degeneration compared to the control kidney. The following qualitative scale was used for evaluation of the obtained slides.

Congestion	
Lesion	Score
None:	0
Mild:	1
Moderate:	2

-continued

Congestion	
Lesion	Score
Marked:	3
Severe:	4

Tubular degeneration	
Lesion	Score
None:	0
Mild:	1
Moderate:	2
Marked:	3
Severe:	4

TABLE 1

Animal ID/Organ/Gross lesion	Slide number	Histologic lesions		
		Con- gestion	Tubular hyaline casts	Granu- lomas
6343/Left Kidney/Normal	R16-513-1	1	1	0
6343/Left Kidney/Normal with hemorrhagic streak	R16-513-2	1	1	0
6343/Right Kidney/Congestion	R16-513-3	2	2	1
6343/Right Kidney/Congestion	R16-513-4	2	1	1

[0357] As shown in Table 1, the treated kidney (left kidney) exhibited only mild congestion and tubular degeneration. In contrast, the control kidney (right kidney) exhibited moderate congestion and tubular degeneration. These results were obtained by analysis of the slides discussed below.

[0358] FIGS. 23A and 23B are low and high magnification photomicrographs of the left kidney (treated with negative pressure) of the animal. Based on the histological review, mild congestion in the blood vessels at the corticomedullary junction was identified, as indicated by the arrows. As shown in FIG. 23B, a single tubule with a hyaline cast (as identified by the asterisk) was identified.

[0359] FIGS. 23C and 23D are low and high resolution photomicrographs of the control kidney (right kidney). Based on the histological review, moderate congestion in the blood vessel at the corticomedullary junction was identified, as shown by the arrows in FIG. 23C. As shown in FIG. 23D, several tubules with hyaline casts were present in the tissue sample (as identified by asterisks in the image). Presence of a substantial number of hyaline casts is evidence of hypoxia.

[0360] Surface mapping analysis provided the following results. The treated kidney was determined to have 1.5 times greater fluid volume in Bowman's space and 2 times greater fluid volume in tubule lumen. Increased fluid volume in Bowman's space and the tubule lumen corresponds to increased urine output. In addition, the treated kidney was determined to have 5 times less blood volume in capillaries compared to the control kidney. The increased volume in the treated kidney appears to be a result of (1) a decrease in individual capillary size compared to the control and (2) an

increase in the number of capillaries without visible red blood cells in the treated kidney compared to the control kidney, an indicator of less congestion in the treated organ.

SUMMARY

[0361] These results indicate that the control kidney had more congestion and more tubules with intraluminal hyaline casts, which represent protein-rich intraluminal material, compared to the treated kidney. Accordingly, the treated kidney exhibits a lower degree of loss of renal function. While not intending to be bound by theory, it is believed that as severe congestion develops in the kidney, hypoxemia of the organ follows. Hypoxemia interferes with oxidative phosphorylation within the organ (e.g., ATP production). Loss of ATP and/or a decrease in ATP production inhibits the active transport of proteins causing intraluminal protein content to increase, which manifests as hyaline casts. The number of renal tubules with intraluminal hyaline casts correlates with the degree of loss of renal function. Accordingly, the reduced number of tubules in the treated left kidney is believed to be physiologically significant. While not intending to be bound by theory, it is believed that these results show that damage to the kidney can be prevented or inhibited by applying negative pressure to a catheter inserted into the renal pelvis to facilitate urine output.

Example 2

[0362] Method

[0363] Four (4) farm swine (A, B, C, D) were sedated and anesthetized. Vitals for each of the swine were monitored throughout the experiment and cardiac output was measured at the end of each 30-minute phase of the study. Ureteral catheters, such as the ureteral catheter 112 shown in FIGS. 2A and 2B, were deployed in the renal pelvis region of the kidneys of each of the swine. The deployed catheters were a 6 Fr catheter having an outer diameter of 2.0±0.1 mm. The catheters were 54±2 cm in length, not including the distal retention portion. The retention portion was 16±2 mm in length. As shown in the catheter 112 in FIGS. 2A and 2B, the retention portion included two full coils and one proximal half coil. The outer diameter of the full coils, shown by line D1 in FIGS. 2A and 2B, was 18±2 mm. The half coil diameter D2 was about 14 mm. The retention portion of the deployed ureteral catheters included six drainage holes, plus an additional hole at the distal end of the catheter tube. The diameter of each of the drainage holes was 0.83±0.01 mm. The distance between adjacent drainage holes 132, specifically the linear distance between drainage holes when the coils were straightened, was 22.5±2.5 mm.

[0364] The ureteral catheters were positioned to extend from the renal pelvis of the swine, through the bladder, and urethra, and to fluid collection containers external to each swine. Following placement of the ureteral catheters, pressure sensors for measuring IVC pressure were placed in the IVC at a position distal to the renal veins. An inflatable balloon catheter, specifically a PTS® percutaneous balloon catheter (30 mm diameter by 5 cm length), manufactured by NuMED Inc. of Hopkinton, N.Y., was expanded in the IVC at a position proximal to the renal veins. A thermodilution catheter, specifically a Swan-Ganz thermodilution pulmonary artery catheter manufactured by Edwards Lifesciences Corp. of Irvine, Calif., was then placed in the pulmonary artery for the purpose of measuring cardiac output.

[0365] Initially, baseline urine output was measured for 30 minutes, and blood and urine samples were collected for biochemical analysis. Following the 30-minute baseline period, the balloon catheter was inflated to increase IVC pressure from a baseline pressure of 1-4 mmHg to an elevated congested pressure of about 20 mmHg (+/-5 mmHg). A congestion baseline was then collected for 30 minutes with corresponding blood and urine analysis.

[0366] At the end of the congestion period, the elevated congested IVC pressure was maintained and negative pressure diuresis treatment was provided for swine A and swine C. Specifically, the swine (A, C) were treated by applying a negative pressure of -25 mmHg through the ureteral catheters with a pump. As in previously-discussed examples, the pump was an Air Cadet Vacuum Pump from Cole-Parmer Instrument Company (Model No. EW-07530-85). The pump was connected in series to a regulator. The regulator was a V-800 Series Miniature Precision Vacuum Regulator—1/8 NPT Ports (Model No. V-800-10-W/K), manufactured by Airtrol Components Inc. The swine were observed for 120 minutes, as treatment was provided. Blood and urine col-

tion, histological sections were obtained and examined, and magnified images of the sections were captured.

[0368] Results

[0369] Measurements collected during the Baseline, Congestion, and Treatment periods are provided in Table 2. Specifically, urine output, serum creatinine, and urinary creatinine measurements were obtained for each time period. These values allow for the calculation of a measured creatinine clearance as follows:

$$\text{Creatinine Clearance:CrCl} = \frac{\text{Urine Output (ml/min)} * \frac{\text{Urinary Creatinine (mg/dl)}}{\text{Serum Creatinine (mg/dl)}}}{}$$

In addition, Neutrophil gelatinase-associated lipocalin (NGAL) values were measured from serum samples obtained for each time period and Kidney Injury Molecule 1 (KIM-1) values were measured from the urine samples obtained for each time period. Qualitative histological findings determined from review of the obtained histological sections are also included in Table 2.

TABLE 2

Treatment assignment	Animal			
	A Treatment	B Control	C Treatment	D Control
Baseline:				
Urine output (ml/min)	3.01	2.63	0.47	0.98
Serum creatinine (mg/dl)	0.8	0.9	3.2	1.0
Creatinine clearance (ml/min)	261	172	5.4	46.8
Serum NGAL (ng/ml)	169	*	963	99
Urinary KIM-1 (ng/ml)	4.11	*	3.59	1.16
Congestion:				
Urine output (ml/min)	0.06 (2%)	0.53 (20%)	0.12 (25%)	0.24 (25%)
Serum creatinine (mg/dl)	1.2 (150%)	1.1 (122%)	3.1 (97%)	1.2 (120%)
Creatinine clearance (ml/min)	1.0 (0.4%)	30.8 (18%)	1.6 (21%)	16.2 (35%)
Serum NGAL (ng/ml)	102 (60%)	*	809 (84%)	126 (127%)
Urinary KIM-1 (ng/ml)	24.3 (591%)	*	2.2 (61%)	1.39 (120%)
Treatment:				
Urine output (ml/min)	0.54 (17%)		0.47 (101%)	0.35 (36%)
Serum creatinine (mg/dl)	1.3 (163%)		3.1 (97%)	1.7 (170%)
Creatinine clearance (ml/min)	30.6 (12%)	**	18.3 (341%)	13.6 (29%)
Serum NGAL (ng/ml)	197 (117%)		1104 (115%)	208 (209%)
Urinary KIM-1 (ng/ml)	260 (6326%)		28.7 (799%)	233 (20000%)
Histological findings:				
Blood volume in capillary space	2.4%		0.9%	4.0%
Hyaline casts	Mild/Mod	**	None	Mod
Degranulation	Mild/Mod		None	Mod

Data are raw values (% baseline)
 * not measured
 ** confounded by phenylephrine

lection were performed every 30 minutes, during the treatment period. Two of the swine (B, D) were treated as congested controls (e.g., negative pressure was not applied to the renal pelvis through the ureteral catheters), meaning that the two swine (B, D) did not receive negative pressure diuresis therapy.

[0367] Following collection of urine output and creatinine clearance data for the 120-minute treatment period, the animals were sacrificed and kidneys from each animal were subjected to gross examination. Following gross examina-

[0370] Animal A:

[0371] The animal weighed 50.6 kg and had a baseline urine output rate of 3.01 ml/min, a baseline serum creatinine of 0.8 mg/dl, and a measured CrCl of 261 ml/min. It is noted that these measurements, aside from serum creatinine, were uncharacteristically high relative to other animals studied. Congestion was associated with a 98% reduction in urine output rate (0.06 ml/min) and a >99% reduction in CrCl (1.0 ml/min). Treatment with negative pressure applied through the ureteral catheters was associated with urine output and

CrCl of 17% and 12%, respectively, of baseline values, and 9× and >10×, respectively, of congestion values. Levels of NGAL changed throughout the experiment, ranging from 68% of baseline during congestion to 258% of baseline after 90 minutes of therapy. The final value was 130% of baseline. Levels of KIM-1 were 6 times and 4 times of baseline for the first two 30-minute windows after baseline assessment, before increasing to 68×, 52×, and 63× of baseline values, respectively, for the last three collection periods. The 2-hour serum creatinine was 1.3 mg/dl. Histological examination revealed an overall congestion level, measured by blood volume in capillary space, of 2.4%. Histological examination also noted several tubules with intraluminal hyaline casts and some degree of tubular epithelial degeneration, a finding consistent with cellular damage.

[0372] Animal B:

[0373] The animal weighed 50.2 kg and had a baseline urine output rate of 2.62 ml/min and a measured CrCl of 172 ml/min (also higher than anticipated). Congestion was associated with an 80% reduction in urine output rate (0.5 ml/min) and an 83% reduction in CrCl (30 ml/min). At 50 minutes into the congestion (20 minutes after the congestion baseline period), the animal experienced an abrupt drop in mean arterial pressure and respiration rate, followed by tachycardia. The anesthesiologist administered a dose of phenylephrine (75 mg) to avert cardiogenic shock. Phenylephrine is indicated for intravenous administration when blood pressure drops below safe levels during anesthesia. However, since the experiment was testing the impact of congestion on renal physiology, administration of phenylephrine confounded the remainder of the experiment.

[0374] Animal C:

[0375] The animal weighed 39.8 kg and had a baseline urine output rate of 0.47 ml/min, a baseline serum creatinine of 3.2 mg/dl, and a measured CrCl of 5.4 ml/min. Congestion was associated with a 75% reduction in urine output (0.12 ml/min) and a 79% reduction in CrCl (1.6 ml/min). It was determined that baseline NGAL levels were >5× the upper limit of normal (ULN). Treatment with negative pressure applied to the renal pelvis through the ureteral catheters was associated with a normalization of urine output (101% of baseline) and a 341% improvement in CrCl (18.2 ml/min). Levels of NGAL changed throughout the experiment, ranging from 84% of baseline during congestion to 47% to 84% of baseline between 30 and 90 minutes. The final value was 115% of baseline. Levels of KIM-1 decreased 40% from baseline within the first 30 minutes of congestion, before increasing to 8.7×, 6.7×, 6.6×, and 8× of baseline values, respectively, for the remaining 30-minute windows. Serum creatinine level at 2 hours was 3.1 mg/dl. Histological examination revealed an overall congestion level, measured by blood volume in capillary space, of 0.9%. The tubules were noted to be histologically normal.

[0376] Animal D:

[0377] The animal weighed 38.2 kg and had a baseline urine output of 0.98 ml/min, a baseline serum creatinine of 1.0 mg/dl, and a measured CrCl of 46.8 ml/min. Congestion was associated with a 75% reduction in urine output rate (0.24 ml/min) and a 65% reduction in CrCl (16.2 ml/min). Continued congestion was associated with a 66% to 91% reduction of urine output and 89% to 71% reduction in CrCl. Levels of NGAL changed throughout the experiment, ranging from 127% of baseline during congestion to a final value of 209% of baseline. Levels of KIM-1 remained between 1×

and 2× of baseline for the first two 30-minute windows after baseline assessment, before increasing to 190×, 219×, and 201× of baseline values for the last three 30-minute periods. The 2-hour serum creatinine level was 1.7 mg/dl. Histological examination revealed an overall congestion level 2.44× greater than that observed in tissue samples for the treated animals (A, C) with an average capillary size 2.33 times greater than that observed in either of the treated animals. The histological evaluation also noted several tubules with intraluminal hyaline casts as well as tubular epithelial degeneration, indicating substantial cellular damage.

SUMMARY

[0378] While not intending to be bound by theory, it is believed that the collected data supports the hypothesis that venous congestion creates a physiologically significant impact on renal function. In particular, it was observed that elevation of the renal vein pressure reduced urine output by 75% to 98% within seconds. The association between elevations in biomarkers of tubular injury and histological damage is consistent with the degree of venous congestion generated, both in terms of magnitude and duration of the injury.

[0379] The data also appears to support the hypothesis that venous congestion decreases the filtration gradients in the medullary nephrons by altering the interstitial pressures. The change appears to directly contribute to the hypoxia and cellular injury within medullary nephrons. While this model does not mimic the clinical condition of AKI, it does provide insight into the mechanical sustaining injury.

[0380] The data also appears to support the hypothesis that applying negative pressure to the renal pelvis through ureteral catheters can increase urine output in a venous congestion model. In particular, negative pressure treatment was associated with increases in urine output and creatinine clearance that would be clinically significant. Physiologically meaningful decreases in medullary capillary volume and smaller elevations in biomarkers of tubular injury were also observed. Thus, it appears that by increasing urine output rate and decreasing interstitial pressures in medullary nephrons, negative pressure therapy may directly decrease congestion. While not intending to be bound by theory, by decreasing congestion, it may be concluded that negative pressure therapy reduces hypoxia and its downstream effects within the kidney in a venous congestion mediated AKI.

[0381] The experimental results appear to support the hypothesis that the degree of congestion, both in terms of the magnitude of pressure and duration, is associated with the degree of cellular injury observed. Specifically, an association between the degree of urine output reduction and the histological damage was observed. For example, treated Swine A, which had a 98% reduction in urine output, experienced more damage than treated Swine C, which had a 75% reduction in urine output. As would be expected, control Swine D, which was subjected to a 75% reduction in urine output without benefit of therapy for two and a half hours, exhibited the most histological damage. These findings are broadly consistent with human data demonstrating an increased risk for AKI onset with greater venous congestion. See e.g., Legrand, M. et al., *Association between systemic hemodynamics and septic acute kidney injury in critically ill patients: a retrospective observational study*. *Critical Care* 17:R278-86, 2013.

Example 3

[0382] Method

[0383] Inducement of negative pressure within the renal pelvis of farm swine was performed for the purpose of evaluating effects of negative pressure therapy on hemodilution of the blood. An objective of these studies was to demonstrate whether a negative pressure delivered into the renal pelvis significantly increases urine output in a swine model of fluid resuscitation.

[0384] Two pigs were sedated and anesthetized using ketamine, midazolam, isoflurane and propofol. One animal (#6543) was treated with a ureteral catheter and negative pressure therapy as described herein. The other, which received a Foley type bladder catheter, served as a control (#6566). Following placement of the catheters, the animals were transferred to a sling and monitored for 24 hours.

[0385] Fluid overload was induced in both animals with a constant infusion of saline (125 mL/hour) during the 24 hour follow-up. Urine output volume was measured at 15 minute increments for 24 hours. Blood and urine samples were collected at 4 hour increments. As shown in FIG. 21, a therapy pump 818 was set to induce negative pressure within the renal pelvis 820, 821 (shown in FIG. 21) of both kidneys using a pressure of -45 mmHg (+/-2 mmHg).

[0386] Results

[0387] Both animals received 7 L of saline over the 24 hour period. The treated animal produced 4.22 L of urine while the control produced 2.11 L. At the end of 24 hours, the control had retained 4.94 L of the 7 L administered, while the treated animal retained 2.81 L of the 7 L administered. FIG. 26 illustrates the change in serum albumin. The treated animal had a 6% drop in the serum albumin concentration over 24 hours, while the control animal had a 29% drop.

SUMMARY

[0388] While not intending to be bound by theory, it is believed that the collected data supports the hypothesis that fluid overload induces clinically significant impact on renal function and, consequently induces hemodilution. In particular, it was observed that administration of large quantities of intravenous saline cannot be effectively removed by even healthy kidneys. The resulting fluid accumulation leads to hemodilution. The data also appears to support the hypothesis that applying negative pressure diuresis therapy to fluid overloaded animals can increase urine output, improve net fluid balance and decrease the impact of fluid resuscitation on development of hemodilution.

[0389] The preceding examples and embodiments of the invention have been described with reference to various examples. Modifications and alterations will occur to others upon reading and understanding the foregoing examples. Accordingly, the foregoing examples are not to be construed as limiting the disclosure.

What is claimed is:

1. A method for increasing urine output rate from a patient having venous congestion, the method comprising:

deploying a urinary catheter into the patient such that flow of urine from the ureter and/or kidney is transported within a drainage lumen of the catheter;

applying negative pressure to the ureter and/or kidney through the drainage lumen of the catheter to extract urine from the patient;

periodically examining a leg of the patient to determine the extent of peripheral edema; and

if the peripheral edema is less than or equal to Grade 1, in which a depth of an indentation in the leg of the patient is about 2 mm or less after tissue perfusion time of 3 seconds, ceasing the application of the negative pressure to the ureter and/or kidney.

2. The method according to claim 1, wherein the patient has a central venous pressure greater than 6 mm Hg, or greater than about 8 mm Hg, prior to application of the method.

3. The method according to claim 1, wherein the urinary catheter comprises (a) a proximal portion; and (b) a distal portion, the distal portion comprising a retention portion that comprises at least one drainage hole(s), port(s) or perforation(s) and is configured to establish an outer periphery that inhibits mucosal tissue from occluding the at least one drainage hole(s), port(s) or perforation(s) upon application of the negative pressure through the catheter.

4. The method according to claim 1, wherein the urinary catheter comprises a drainage lumen comprising a proximal portion configured to extend outside of the patient's body, and a distal portion configured to be positioned in a patient's kidney, renal pelvis and/or in the ureter adjacent to the renal pelvis, the distal portion comprising a retention portion, the retention portion comprising at least one drainage hole(s), port(s) or perforation(s) on a sidewall of the retention portion of the distal portion of the drainage lumen for permitting fluid flow into the drainage lumen, wherein the proximal portion of the drainage lumen is essentially free of or free of drainage hole(s), port(s) or perforation(s).

5. The method according to claim 4, wherein the at least one drainage hole(s), port(s) or perforation(s) is on an inwardly facing side of the sidewall of the retention portion.

6. The method according to claim 1, wherein the urinary catheter comprises a drainage lumen comprising a proximal portion configured to extend outside of the patient's body, and a distal portion configured to be positioned in a patient's kidney, renal pelvis and/or in the ureter adjacent to the renal pelvis, the distal portion comprising a retention portion, the retention portion comprising at least one coil(s).

7. The method according to claim 6, wherein the retention portion comprises at least two coils, each of the at least two coils comprising a radially inwardly facing side comprising at least one of the drainage hole(s), port(s) or perforation(s) and an outwardly facing side which is essentially free or free of drainage hole(s), port(s) or perforation(s).

8. The method according to claim 7, wherein the at least two coil(s) comprises at least a first coil having a first diameter; and at least a second coil having a second diameter, the first diameter being less than the second diameter, the second coil being closer to an end of the distal portion of the drainage lumen than the first coil.

9. The method according to claim 7, wherein the radially inwardly facing side of at least one of the at least two coils comprises at least one of the drainage hole(s), port(s) or perforation(s).

10. The method according to claim 7, wherein a total surface area of drainage hole(s), port(s) or perforation(s) on the radially inwardly facing side of at least one of the at least two coils is greater than a total surface area of drainage port(s) hole(s), port(s) or perforation(s) on the outwardly facing side of the same at least one of the at least two coils.

11. The method according to claim **1**, further comprising deploying a bladder catheter in the patient's bladder for receiving urine which passes through the ureter and enters the bladder.

12. The method according to claim **1**, further comprising ceasing application of negative pressure when a total volume of fluid extracted from the patient and collected from the urinary catheter exceeds a predetermined fluid volume.

13. The method according to claim **12**, wherein excess fluid is provided to the patient during a fluid resuscitation procedure performed for the patient.

14. The method according to claim **13**, wherein removing the excess fluid from the patient is provided as a treatment for systemic fluid volume management associated with acute heart failure or as a treatment provided to the patient during a coronary graft bypass procedure.

* * * * *