

- Presentable KeyLED[™] Packaging
- KeyLED[™] flashlight uses four LR1120 Batteries ٠
- Flashlight Weight: 0.6oz, Flashlight with Case Weight: 2.0oz •

• Ambient Operating Temperature Range: ~-22°F to ~+122°F [~-30°C to ~+50°C]

Applications:

- Map Reading
 - Instrument and Watch Illumination
 - Military and Police Operations
 - Astronomers
 - Emergency Lighting
 - Cabin Lighting While Driving at Night
 - Illuminating Keyholes
 - Restaurant Menu Reading



Financing

Credit Application Financing Overview Financing Brochure Financing Application Balboa Press Release Incandescent to LED Cross RefVideosLight Plot Request FormPhotosReps WantedIn the N

Tools

Media

Photos Catalog & Photos Catalog R In the News Tech Not Lighting knowLEDge 101 Why LEDs Global Citizenship Think Gre American Fund for Human Development Warranty Press Releases

Info

Catalog & Literature RoHS Catalog Request Form NSN Tech Notes Minor Why LEDs? ISO 90 Think Green with LEDs OSHA

ISO/Certs

RoHS NSN Minority Owned ISO 9001:2008 OSHA





Site Map Privacy Policy Warranty Terms & Conditions Contact Us

Rep Tools: 📼 🗐 🛄

23105 Kashiwa Ct, Torrance, CA 90505 - PH: (800) 579-4875 (310) 534-1505 - FAX: (310) 534-1424

All images and pictures and text on our website is Copyrighted property of LEDtronics.

No-one is authorized to use our pictures, images, catalogs or text without our explicit written approval. Copyright © 1997-2016 LEDtronics, Inc., All Rights Reserved.