



- F. Signature Sports Flooring Top Coat is a pigmented two (2) component, UV, abrasion resistant polyurethane top coating. It comes in ten (10) standard colors (matte finish).
- G. Signature Sports Flooring Game Line Paint is a two component, high solids, polyurethane, mat line paint. It comes in seven (7) standard colors.
- H. OPTION: Vinyl wall base 4" (102mm) high; select color: black or brown.

PART 3 – EXECUTION

3.1 INSPECTION

- A. Surface Inspection
 1. Refer to specific Signature Sports Flooring substrate specifications.
 2. The existing system shall be inspected with the owner to determine if repairs are needed. The installer shall perform tests for moisture and adhesion prior to application.
 - a. Report adverse conditions to the owner or his/her representative in writing.
 - b. Report any discrepancies or repairs needed to the general contractor.
- B. The substrate surface shall be broom cleaned by general contractor.
- C. Installer shall document all working conditions provided in general specifications before installation begins.

3.2 INSTALLATION

- A. Basemat
 1. Unroll basemat and allow to relax. Do not cut basemat to final dimensions until laid into adhesive.
 2. Thoroughly mix the two-component polyurethane adhesive and apply directly to the concrete subfloor with a notched trowel per manufacturer's instructions.
 3. Install basemat into freshly applied adhesive. Do not allow compression fit at any seams. Roll basemat with an 80 pound (37kg) roller and repeat the rolling process on the entire mat 45 minutes after installation. Allow adhesive to cure before proceeding to seal coat.