

PRIMO SYNTHETIC ROOFING UNDERLAYMENT



BENEFITS

PRIMO SYNTHETIC ROOFING UNDERLAYMENT is a highly engineered, mechanically attached, coated woven synthetic roofing underlayment for sloped roofs. It is specifically manufactured to replace #15 felt.

COVERAGE

Approximately 950 sq. ft. per roll or less depending upon overlap and roof design.

USES

PRIMO SYNTHETIC ROOFING UNDERLAYMENT is used under asphalt shingles, tile or metal roofs

PREPARATION

The deck surface must be dry and free of dust, dirt, loose nails, debris and other protrusions. Ensure the deck has no voids, damaged or unsupported areas. Damaged sheathing must be replaced.



PRODUCT DATA ASTM D6222-11 Type I, Grade G

	PRIMO Typical
Roll Width, ft	4 ft
Roll Length, ft	250 ft
Roll Weight, lbs	19 lbs
Roll Size, sq ft	10 sq ft
Rolls Per pallet	72 rolls
Pallet Weight lbs	1368 lbs

PRECAUTIONS

PRIMO SYNTHETIC ROOFING UNDERLAYMENT is not designed to replace the primary roof covering material. Or for indefinite outdoor exposure and it is recommended that installation of the final roof covering takes place within 3 months.

