

PrimeSourceOPC

Revision Level: 000 Art File No. 1901-027

Proof Rev. Level: 1 **PLEASE CHECK ONE**

Customer: Solo Solutions Please resubmit new proof with changes noted

Proof Date: 01/17/19 Approved / Proceed with order

PLEASE CHECK ONE: Does this label need to match a previously printed label? Yes No

Proof Approved by: _____

Approval Date: _____ Comments: _____

PLEASE READ CAREFULLY!


Please review this proof carefully, including all the copy. What you see on this proof is exactly what will be printed. We want everything right the first time. Please keep these facts in mind:

*If an error to the copy is approved and printed, it will be necessary to charge you for the production costs.

*Proofs returned quickly get the earliest press dates.

*If no proof is returned within 90 days, we must invoice you for art charges.

Job Description:	One Boat Gallon	Printing Method:	Digital
Size (W x H):	5.00" X 12.0" - Rectangle	Material 1:	2.6Mil White BOPP NTC
Die #:	R13097*M	Material 2:	-
	Core Dia: 3"		



- Black
- Cyan
- Magenta
- Yellow

500 Labels Per Roll

Please inspect this proof and respond by fax to **PrimeSourceOPC 336-661-3313**.

Should you have any questions please call PrimeSourceOPC 336-661-3300.

Thank you.

4 X CR = .125"

5.00"

Dieline (Does not print)

Label Carrier (Does not print)

WATER BASED & BIODEGRADABLE



BIODEGRADABLE

ONE BOAT

SUPER CLEANER

A Total Boat Super Cleaner

- Fiberglass, Wood
- Galley, Carpet
- Bilge Pump, Engine Room

Made in U.S.A by

SOLO SOLUTIONS, INC.

P.O. BOX 2584
KERNERSVILLE, N.C. 27285

*This Product Meets USDA Performance Standards for (A1), (A4), (A5), and (A8) Type Products.

1 Gallon (3.78L)

CAUTION: May cause eye and skin irritation. See precautions on back. Keep away from children.

One Boat Super Cleaner is an amazing technological breakthrough that removes marine mold, oil & gas spills and general dirt from a variety of surfaces without scrubbing. This single product removes oil, grease and heavy soils from boats, equipment, decking, trailers, concrete, and more. The surfactants in One Boat are biodegradable.

DIRECTIONS FOR USE

Boat Washing. Pour 1-2oz per gallon of water into a bucket (hot water will increase efficiency). Apply to a cool surface, using a clean sponge, washing brush or wash mitt. Before solution dries, rinse with a flow of water (not spray) so water sheets off surface. Wipe dry with a clean chamois.

Black Streak Removal. Spray onto area affected with water spots and water stains. Allow product to remain for some time on extremely hard to remove stains. Agitate lightly with a Boat Body Brush with medium to soft flagged tip bristles. Rinse. After removing water spots and stains, apply Polish & Sealant to create a protective barrier against the water stains.

Tools & Equipment. 4-6 ounces in a 32 ounce spray bottle, fill with water. For heavy mildew or oil spills use full strength for quick results.

Complete Galley Cleaning. Cleans Grease and Grime and Mold and Mildew. Dirty Pots, Grill Cleaning, Deep Fryer Cleaning/Boil Out, Cooler Cleaning, Bathrooms. Clean as directed and rinse thoroughly with water.

Equipment & General Degreasing. For heavy soils use full strength. For light soils pour 4 oz. into a spray bottle and fill with water. Spray on, then wipe or rinse off.

MARINE CRAFT
Boats, Yachts, Jetskis, Canoes, Surfboards, Paddleboards, Boat Trailers, Boating Equipment

SURFACES
Fibreglass, Vinyl, Indoor and Outside Carpeting, Rubber, Teak, Acrylic, Canvas, Stainless Steel.

OUTDOOR / EXTERIOR Jetty's, Docks, Piers, Wooden Decks, Concrete, Asphalt, Parking Lots, Sidewalks, Driveways, Siding, Roofing, Dumpster Areas, Trash Receptacles, Gas Pumps, Building Exteriors, Algae Covered Items

FLOORS Tile, Ceramic, Linoleum, Porcelain, Vinyl, Concrete, Indoor and Outside Carpeting, Quarry Tile and Stone

GENERAL CLEANING Galleys, Cockpits, Bilge, Seating, Showers, Tubs, Appliances, Counter Tops, Sinks, Microwaves, Plastics

Safe in boat septic systems. Will not hurt plumbing nor rubber seals.





PRECAUTIONS
Always sample test on an inconspicuous area before use.
Do not use if temperature will be below freezing o(32F). Do not use on deteriorating pavement. Avoid use on aluminum, galvanized steel or soft metal surfaces. Use caution. Surfaces may be slippery when wet. *For industrial and institutional use only.* As with all cleaning products follow regulations for discharge and disposal.

FIRST AID

EYES: Immediately flush eyes with cool running water for at least 15 minutes. Remove any contact lenses before flushing. If irritation persists, call a physician.

IF SWALLOWED: DO NOT induce vomiting. Rinse mouth. Drink 1 to 2 glasses of milk or water. Call a physician.

SKIN CONTACT: Wash off with water.

12.00"