



360T
LOT NO. L-812807
781-27 MB

HAZARD
GHS02 (Flammable liquid)
GHS03 (Corrosive)
GHS05 (Oxidizing liquid)

PRECAUTIONS
P201 (Identify the hazard)
P202 (Read the label)
P231 (Store in a cool, well-ventilated area)
P232 (Use non-flammable pusher or pump)
P233 (Keep container tightly closed)
P234 (Use only the recommended extraction method)
P240 (Wear protective gloves)
P241 (Wear eye protection)
P242 (Wear protective clothing)
P243 (Wear respiratory protection)
P244 (Wear protective footwear)
P273 (Prevent release to the environment)

SAFETY
S2 (Keep away from heat, open flames, and other sources of ignition)
S3 (Do not breathe vapors/mist/gases/dust/fumes/spray)
S4 (Wash thoroughly after handling)

REGULATORY INFORMATION
NFPA 704: 2-1-1
DOT: 3 (Flammable liquid)
UN: 1202 (Flammable liquid)
Hazardous material label: 2 (Flammable liquid)
Hazardous material label: 3 (Corrosive)
Hazardous material label: 5 (Oxidizing liquid)

MANUFACTURER
SIMPSON

業務用

FOR INDUSTRIAL USE



360T

LOT NO. L-123456

NET 17 kg



危険



Danger



《危険有害性情報》

- ・引火性の高い液体及び蒸気
- ・強い眼刺激
- ・吸入すると有害
- ・呼吸器への刺激のおそれ
- ・眠気又はめまいのおそれ
- ・水生生物に有害

Hazard Statements:

- ・Highly flammable liquid and vapor.
- ・Causes serious eye irritation.
- ・Harmful if inhaled.
- ・May cause respiratory irritation.
- ・May cause drowsiness or dizziness.
- ・Harmful to aquatic life.

【安全対策】

熱/火花/裸火/高温のもののような着火源から遠ざけること。一禁煙。
容器を密閉しておくこと。
粉じん/煙/ガス/ミスト/蒸気/スプレーを吸入しないこと。
保護手袋/保護衣/保護眼鏡/保護面を着用すること。

【応急措置】

ばく露またはばく露の懸念がある場合：医師に連絡すること。

【保管】

換気が良く、5~40℃の場所で保管すること。

【廃棄】

内容物/容器は地域/地方/国/国際法律に従って廃棄すること。

詳細な内容が必要な場合は、安全データシート (SDS) をご参照下さい。

PREVENTIONS

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear protective gloves/protective clothing/eye protection /face protection.

RESPONSE

IF exposed or concerned: Call a POISON CENTER/doctor.

STORAGE

Store in a well-ventilated place at temperatures between 5°C and 40°C.

DISPOSAL

Dispose of contents/container in accordance with local/regional /national/international regulations.

For further information, please consult SDS.

危険物 第四類 第一石油類 危険等級Ⅱ 火気厳禁



日本製紙株式会社

NIPPON PAPER INDUSTRIES CO.,LTD.

ケミカル営業本部 ケミカル営業一部

CHEMICAL SALES DIV. CHEMICAL SALES DEPT. I

〒101-0062 東京都千代田区神田駿河台4-6

4-6, KANDASURUGADAI, CHIYODA-KU, TOKYO 101-0062, JAPAN

TEL.03-6665-5940 FAX.03-6665-0360

TEL.+81-(0)3-6665-5940 FAX.+81-(0)3-6665-0360