



# VersaStrip LED Light



2x5500 lms | 120-277VAC | Model 54598142 | Part ST-4-55-840-MV-D

- > Energy Saving 110 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > 5 Year Limited Warranty
- > Shatterproof PMMA Lens Will not Discolor over time
- > One Product = Many Solutions!
- > High Power 4' Strip Single or Side by Side
- > 8' End-to-End Strip Joining Brackets Included
- > Linear High Bay Great for Warehouse Aisle Lighting
- > Custom 0-10V Motion Sensor Available



## SPECIFICATIONS

Model	54598142
Part	ST-4-55-840-MV-D
Certification	54598142
Description	2x4' LED Strip Light
Input Voltage (VAC)	120-277V
Wattage	2x50W
Dimmable	0-10V Dimmable
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	2x5500lm
CCT <sup>3</sup>	4000K
Location Rating	UL Damp
CRI <sup>4</sup>	≥80
Beam Angle Operating	110
Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
Operating Frequency (Hz)	50/60Hz

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%)
- 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra





# VersaStrip LED Light



2x5500 lms | 120-277VAC | Model 54598142 | Part ST-4-55-840-MV-D

## SHIPPING INFORMATION

Model	54598142
Part	ST-4-55-840-MV-D
UPC	849489060125
Product Dimensions (L x W x H in.)	48 x 4 1/8 x 2 1/2
Product Dimensions (L x W x H cm.)	122 x 5 3/8 x 7 1/2
Product Weight (lbs.)	7.5
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489060120
Master Carton Dimensions (L x W x H in.)	50 x 11 x 7
Master Carton Dimensions (L x W x H cm.)	127 x 29 x 17
Master Carton Weight (lbs)	7.26
Pallet Quantity	N/A

## COMPATIBILITY

### Dimmers:

Lutron: DDTV, DVSTV, NFTV, NTSTV-DV

Leviton: IP710

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

ETi Solid State Lighting, Inc.  
720 Northgate Parkway  
Wheeling, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256