



Long-Term Support
World Class Quality

PRODUCTS

SUPPORT

CONTACT US

SAMPLE & BUY



LPDDR4 and LPDDR4X SDRAM



- Low-voltage supplies: 1.8V, 1.1V
- I/O at 1.1V (LPDDR4) or 0.6V (LPDDR4X)
- Clock Frequency Range : 10MHz to 1600MHz
 - Data rates from : 20Mbps to 3200 Mbps per I/O
- 16n Pre-fetch DDR Architecture
- Multiplexed, double data rate, command/address inputs
- ZQ Calibration
- Mobile features for lower power
- Long-term support

LPDDR4 SDRAM

- LPDDR4 SDRAM
- LPDDR4X SDRAM
- LPDDR4 with ECC SDRAM
- LPDDR4X with ECC SDRAM

More Mobile DRAM Products

- Mobile LPDDR2 SDRAM
- Mobile DDR SDRAM
- Low Voltage/Mobile SDR SDRAM

LPDDR4 SDRAM

| Den | Org | Type | Part Number | Buy | Vcc | Speed | Pkg(Pins) | Status | Models |
|-----|-----------------------|--------|-------------------------------|-----|-----------|-------|-----------|---------|--------|
| 2G | Single Channel (1x16) | LPDDR4 | IS43LQ16128A, IS46LQ16128A | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two Channel (2x16) | LPDDR4 | IS43LQ32640A, IS46LQ32640A | | 1.1V/1.8V | 3200 | BGA(200) | S=Q3/20 | IBIS |
| 4G | Single Channel (1x16) | LPDDR4 | IS43LQ16256A, IS46LQ16256A | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two channel (2x16) | LPDDR4 | IS43LQ32128A, IS46LQ32128A | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| 8G | Two channel (2x16) | LPDDR4 | IS43LQ32256A, IS46LQ32256A | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |

LPDDR4X SDRAM

| Den | Org | Type | Part Number | Buy | Vcc | Speed | Pkg(Pins) | Status | Models |
|-----|-----------------------|---------|---------------------------------|-----|----------------|-------|-----------|---------|--------|
| 2G | Single channel (1x16) | LPDDR4X | IS43LQ16128AL, IS46LQ16128AL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two Channel (2x16) | LPDDR4X | IS43LQ32640AL, IS46LQ32640AL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | S=Q3/20 | IBIS |
| 4G | Single Channel (1x16) | LPDDR4X | IS43LQ16256AL, IS46LQ16256AL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two channel (2x16) | LPDDR4X | IS43LQ32128AL, IS46LQ32128AL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| 8G | Two channel (2x16) | LPDDR4X | IS43LQ32256AL, IS46LQ32256AL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |

LPDDR4 with ECC SDRAM

| Den | Org | Type | Part Number | Buy | Vcc | Speed | Pkg(Pins) | Status | Models |
|-----|-----------------------|--------|---------------------------------|-----|-----------|-------|-----------|---------|--------|
| 2G | Single Channel (1x16) | LPDDR4 | IS43LQ16128EA, IS46LQ16128EA | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two Channel (2x16) | LPDDR4 | IS43LQ32640EA, IS46LQ32640EA | | 1.1V/1.8V | 3200 | BGA(200) | S=Q4/20 | IBIS |
| 4G | Single Channel (1x16) | LPDDR4 | IS43LQ16256EA, IS46LQ16256EA | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two channel (2x16) | LPDDR4 | IS43LQ32128EA, IS46LQ32128EA | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| 8G | Two channel (2x16) | LPDDR4 | IS43LQ32256EA, IS46LQ32256EA | | 1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |



LPDDR4X with ECC SDRAM

| Den | Org | Type | Part Number | Buy | Vcc | Speed | Pkg(Pins) | Status | Models |
|-----|-----------------------|---------|-----------------------------------|-----|----------------|-------|-----------|---------|--------|
| 2G | Single channel (1x16) | LPDDR4X | IS43LQ16128EAL, IS46LQ16128EAL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two Channel (2x16) | LPDDR4X | IS43LQ32640EAL, IS46LQ32640EAL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | S=Q4/20 | IBIS |
| 4G | Single Channel (1x16) | LPDDR4X | IS43LQ16256EAL, IS46LQ16256EAL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| | Two channel (2x16) | LPDDR4X | IS43LQ32128EAL, IS46LQ32128EAL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |
| 8G | Two channel (2x16) | LPDDR4X | IS43LQ32256EAL, IS46LQ32256EAL | | 0.6V/1.1V/1.8V | 3200 | BGA(200) | Prod | IBIS |



Notes:

- Simulation Models not listed above may be available upon [request](#)
- S = Sample, Prod = Production
- NR = Not Recommended for new designs
- [IF YOU DON'T SEE A PRODUCT YOU ARE INTERESTED IN AND HAVE A SPECIAL REQUEST, CONTACT US AND LET US KNOW](#)
- Integrated Silicon Solution, Inc. does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless Integrated Silicon Solution, Inc. receives written assurance to its satisfaction, that:
 - a. the risk of injury or damage has been minimized;
 - b. the user assume all such risks; and
 - c. potential liability of Integrated Silicon Solution, Inc is adequately protected under the circumstances

PRODUCTS

DRAM
 Mobile DRAM
 SRAM
 Flash
 Wafer Level Memory Solutions

ANALOG & MIXED SIGNAL
 PRODUCTS

SUPPORT

Product Selector Guides
 Quality and Reliability
 RoHS & CMRT Statement
 Chipset Solutions
 Development & Evaluation Boards
 White Papers & Articles
 Contact ISSI
 Programmer Support

CONTACT US

Representatives
 Authorized Distributors
 ISSI Sales Offices
 Product Question
 Application Question
 Contact ISSI
 Biznet

COMPANY

Company Profile
 Corporate Offices
 Career Opportunities



Terms of Use | Privacy Policy | © 2020 Integrated Silicon Solution Inc. All Rights Reserved.

