Home / Products

# Products

## Durable Fixtures For Demanding Environments

FX Lighting provides businesses with patented products and design solutions. The results deliver application-specific lighting levels to increase energy savings, reduce maintenance, improve morale, safety, and productivity to reduce the total cost of ownership. Our products are waterproof, temperature resistant from -40 degrees to +149 degrees Fahrenheit (-40 degrees to +65 degrees Celsius) and can withstand pressure washing up to 1600 PSI.



**POSEIDON™** 

NSF, IP66, IP69K, Linear Task Light


### **AURORA**<sup>TM</sup>

NSF, IP66 Cold Storage, Linear High-Bay





View Poseidon



**ULTRA**<sup>TM</sup>

NSF, IP66, High-Bay



| View | Nova |
|------|------|

| IP*                   | IP67 Dust-Tight and Waterproof<br>Rated |
|-----------------------|---|
| NSF                   | Splash Zone Listed                      |
| POWER WASHING         | Up to 1600 PSI                          |
| AMBIENT TEMP          | -40°F to 149°F (-40°C to 65°C)          |
| OPERATING<br>VOLTAGE  | 120-480 V                               |
| INPUT FREQUENCY       | 50/60 Hz                                |
| LUMEN OUTPUT<br>RANGE | 18,000-39,000 lumens                    |
| EFFICIENCY            | Up to 150 LPW                           |
| DIMMING               | 0-10V                                   |

| IP*   | IP66 and IP69K Dust-Tight and<br>Waterproof Rated |
|-------|---|
| NSF   | Splash Zone Listed                                |
| DOWED |   |

| NSF                   | Splash Zone Listed            |
|-----------------------|-------------------------------|
| POWER<br>WASHING      | Up to 1600 PSI                |
| AMBIENT TEMP          | -4°F to 122°F (-20°C to 50°C) |
| OPERATING<br>VOLTAGE  | 120-277 V                     |
| INPUT<br>FREQUENCY    | 50/60 Hz                      |
| LUMEN OUTPUT<br>RANGE | 7,500-20,000 lumens           |
| EFFICIENCY            | Up to 130 LPW                 |
| DIMMING               | 0-10V                         |

### View Ultra

| IP                    | IP66 Dust-Tight and Waterproof<br>Rated |
|-----------------------|---|
| NSF                   | Splash Zone Listed                      |
| POWER WASHING         | Up to 1600 PSI                          |
| AMBIENT TEMP          | -40°F to 131°F (-40°C to 55°C)          |
| OPERATING<br>VOLTAGE  | 120-277 V                               |
| INPUT FREQUENCY       | 50/60 Hz                                |
| LUMEN OUTPUT<br>RANGE | 16,000-24,000 lumens                    |
| EFFICIENCY            | Up to 160 LPW                           |
| DIMMING               | 0-10V                                   |

### View Aurora

| IP                    | IP66 Dust-Tight and Waterproof<br>Rated |
|-----------------------|---|
| NSF                   | Splash Zone Listed                      |
| POWER WASHING         | Up to 1600 PSI                          |
| AMBIENT TEMP          | -40°F to 131°F (-40°C to 55°C)          |
| OPERATING<br>VOLTAGE  | 120-480 V                               |
| INPUT FREQUENCY       | 50/60 Hz                                |
| LUMEN OUTPUT<br>RANGE | 15,000-62,000 lumens                    |
| EFFICIENCY            | Up to 155 LPW                           |
| DIMMING               | 0-10V                                   |

## **Start Your Risk-Free Trial**

Try any of our products risk-free for 90 days.

Claim Now

Products Nova™ Poseidon™ Ultra™

Aurora™

Industries

Food and Beverage Processing Manufacturing and Distribution Environments Poultry and Livestock Farming

Services About

Contact Warranty Request



Subscribe to our newsletter

Email

SIGN UP

