



Electrical & Lighting Products
Since 1994 Your #1 Source

888-777-6678
Mon-Fri 8AM-5PM EST

Huge Inventory!
(Ship Within 24 Hours)

No Sales Tax!
(Except NY State)

Free Shipping!
(Orders Over \$100)

Member Sign In

- Home
- Online Ordering
- E-Catalog
- About Us
- Customer Service
- Track My Order

Product Search

Morris# or Keyword Search

Cross Reference

Competitor Name Search

Email Sign Up



- Alphabetic Index
- New Products
- A) Connectors
- B) Grounding
- C) Tape
- D) Wire Management
- E) Boxes
- F) Fittings
- G) Equipment Mounting
- H) HVAC
- I) Motors & Controls
- J) Cements & Flashings
- K) Tools
- L) Wiring Devices
- M) Lighting

Indoor Lighting

LED Linear Low/High Bay	LED Hi-Bay	Panel Lights	LED Troffer	LED Strip Lighting	LED Wraps	LED Vaporlight	LED Shop Lighting
Under Cabinet Light LED	LED Flex Strips	LED JellyJar	LED Retrofit Lamps	LED Recessed Lighting	LED Decorative Lighting	Track Lighting	Motion Activated Closet Light
Lampholders	LED WorkLight	Temporary Lights					



ONE SOURCE...
ELECTRICAL & LIGHTING

Electrical & Lighting Products
Since 1934 Your #1 Source

888-777-6678
Mon-Fri 9AM-5PM EST

Huge Inventory!
(Ship Within 24 Hours)

No Sales Tax!
(Except NY State)

Free Shipping!
(Orders Over \$100)

Member Sign In

- Home
- Online Ordering
- E-Catalog
- About Us
- Customer Service
- Track My Order

Product Search

Morris# or Keyword Search

Cross Reference

Competitor Name Search

[Email Sign Up](#)



Alphabetic Index

New Products

A) Connectors

B) Grounding

C) Tape

D) Wire Management

E) Boxes

F) Fittings

G) Equipment Mounting

H) HVAC

I) Motors & Controls

J) Cements & Flashings

K) Tools

L) Wiring Devices

M) Lighting

N) Exit & Emergency Lighting

Linear High Bay Gen 5

[Email a Friend](#)



[View Larger](#)

Linear High Bay Gen 5 - Use Linear High Bay Gen 5 for replacement of conventional Fluorescent 4 & 6 lamp T8 & T5 High Bay Lighting where Emergency Battery Backup or Motion Sensing is required.

Linear High Bay Gen 5 features include:

- Applications include manufacturing, warehousing, & other large indoor spaces where T12, T8 & T5 High Bay Lighting is being replaced
- Emergency Backup & Motion Sensor Capable (Sold Separately)
- Dimmable: 0-10V
- CRI: >80
- Power Factor: > 90
- Operating Temperature: -40°F to 122°F
- IP20 Rated
- Beam Angle: 90°
- 50,000+ Hour Life Expectancy
- DLC Listed
- UL listed
- 5 Year Warranty
- Order Qty of 1 = 1 Piece

[Click on Cat Number in Chart Below for Spec Sheets, Instruction Sheets, and IES files](#)

WARNING:
Cancer and Reproductive Harm
www.P65Warning.ca.gov

Below is more info on our Linear High Bay Gen 5 replacement of conventional Fluorescent 4 & 6 lamp T8 & T5 High Bay Lighting

[View Catalog PDF Page](#)

[ADD TO ORDER](#)

Cat No	Spec Sheet	Old Cat#	Watts	Lumens	Voltage	Dimmable	Lens	Length	Width	Depth	Case Qty	Price	Quantity	Quantity Available
71708A		71708	110W	15,303	120-277V	0-10V	Frosted	24-3/4"	11-3/4"	1-7/8"	1	\$175.0000	<input type="text"/>	Call Factory for Availability
71709A		-	165W	22,663	120-277V	0-10V	Frosted	24-3/4"	11-3/4"	1-7/8"	1	\$247.5000	<input type="text"/>	Call Factory for Availability

[View Catalog PDF Page](#)

[ADD TO ORDER](#)



Electrical & Lighting Products
Since 1994 Your #1 Source

888-777-6678
Mon-Fri 8AM-5PM EST

Huge Inventory!
(Ship Within 24 Hours)

No Sales Tax
(Except NY State)


Free Shipping!
(Orders Over \$100)

Member Sign In

- Home
- Online Ordering
- E-Catalog
- About Us
- Customer Service
- Track My Order

Product Search
Morris# or Keyword

Cross Reference
Competitor Name



- Alphabetic Index
- New Products
- A) Connectors
- B) Grounding
- C) Tape
- D) Wire Management
- E) Boxes
- F) Fittings
- G) Equipment Mounting
- H) HVAC
- I) Motors & Controls
- J) Cements & Flashings
- K) Tools
- L) Wiring Devices
- M) Lighting
- N) Exit & Emergency Lighting

LED ECO-Flood Light



[View Larger](#)

LED ECO-Flood Light - These Energy Efficient LED Floodlights Fixtures Feature Economical and Long Life LED Light Source.

LED ECO-Flood Light features include:

- Lumiled LUXEON 3030 LEDs
- Integral Cooling Fin releases heat efficiently to maintain the Life of LED's & LED Driver
- Corrosion resistant Die Cast Aluminum Housing
- Polycarbonate Lens
- Superior Architectural Powder Coat Finish
- Housing Color: Bronze or White
- Stainless Steel hardware
- Available with 1/2" Knuckle, Yoke(bracket), Slipfitter, or Trunion mount
- Photo Control can be installed on Slipfitter Mount
- 0-10V/PWM/VR Dimmable 80 thru 150W
- Voltage: 120/208/240/277VAC or 347/480VAC
- CRI: >80
- Color Temperature: 3000K or 5000K
- Light Pattern: Type II 120° x 90° Beam Angle
- Operating Temperature: -40°F to 131°F
- 50,000+ Hour life expectancy
- IP65 rated(Nema 4X) Dust & Water tight
- cULus Listed for Wet Locations
- DLC Listed
- 5 Year Warranty
- Order Qty of 1 = 1 Piece

Click on Cat Number in Chart Below for Spec Sheets, LM70, and IES files

WARNING:
Cancer and Reproductive Harm
www.P65Warning.ca.gov

Below is more info on our LED ECO-Flood Light

[View Catalog PDF Page](#)

[ADD TO ORDER](#)

Cat No	Spec Sheet	Old Cat#	Mounting	Voltage	Finish	Watts	Lumens	Color Temp	Height	Width	Depth	Price	Quantity	Quantity Available
71334A		71334	1/2" Adj. Knuckle	120-277	Bronze	12	1423	5000K	5-5/8"	4-3/4"	2-5/8"	\$80.0000	<input type="text"/>	In Stock
71135A		-	1/2" Adj. Knuckle	120-277	White	12	1423	5000K	5-5/8"	4-3/4"	2-5/8"	\$80.0000	<input type="text"/>	In Stock
71336A		71338	1/2" Adj. Knuckle	120-277	Bronze	12	1302	3000K	5-5/8"	4-3/4"	2-5/8"	\$80.0000	<input type="text"/>	In Stock
71337A		-	1/2" Adj. Knuckle	120-277	White	12	1302	3000K	5-5/8"	4-3/4"	2-5/8"	\$80.0000	<input type="text"/>	In Stock



Electrical & Lighting Products Since 1984 Your #1 Source

888-777-6678 Mon-Fri 8AM-5PM EST

Huge Inventory! (Ship Within 24 Hours)

No Sales Tax (Except NY State)

Free Shipping (Orders Over \$100)

Member Sign In

- Home
- Online Ordering
- E-Catalog
- About Us
- Customer Service
- Track My Order

Product Search

Morris# or Keyword Search

Cross Reference

Competitor Name Search

Email Sign Up



- Alphabetic Index
- New Products
- A) Connectors
- B) Grounding
- C) Tape
- D) Wire Management
- E) Boxes
- F) Fittings
- G) Equipment Mounting
- H) HVAC
- I) Motors & Controls
- J) Cements & Flashings
- K) Tools
- L) Wiring Devices
- M) Lighting
- N) Exit & Emergency Lighting

N) Exit & Emergency Lighting

Exit Signs	Die Cast Aluminum Exit Signs	Edge Lit Exit Signs	LED Combos	LED Incandescent LED Emergencies Combos	LED Emergencies	Recessed Emergencies	Hi-Capacity Emergencies
Wet Location Exits Emergencies	LED Remote Lampheads	Incandescent Remote Lampheads	Exit & Emergency Vandalism Guards	Emergency Lighting Ballasts	New York City Code	Chicago Code	

Morris Products Inc.
 A DiversiTech Company
 53 Carey Road
 Queensbury, NY 12804
 info@morrisproducts.com
 Toll-Free: 888-777-6678
 Fax: 518-743-0536

- Links
- Home
 - Online Catalog
 - E Catalog
 - Resources
 - Diversitech Company Locations
 - Sales Agents
 - Track My Order
 - Lighting Layout Tool
 - Customer Service

PayPal CREDIT
 Buy now. Pay over time.
 Check out with PayPal and choose PayPal Credit.
 US customers only. Subject to credit approval. See terms.



Electrical & Lighting Products
 Since 1994 Your #1 Source

888-777-6678
 Mon-Fri 8AM-5PM EST

Huge Inventory!
 (Ship Within 24 Hours)

No Sales Tax!
 (Except NY State)

Free Shipping!
 (Orders Over \$100)

Member Sign In

Home Online Ordering E-Catalog About Us Customer Service Track My Order

Product Search

Morristalk or Keyword Search

Cross Reference

Competitor Name Search

Email Sign Up



- Alphabetic Index
- New Products
- A) Connectors
- B) Grounding
- C) Tape
- D) Wire Management
- E) Boxes
- F) Fittings
- G) Equipment Mounting
- H) HVAC
- I) Motors & Controls
- J) Cements & Flashings
- K) Tools
- L) Wiring Devices
- M) Lighting
- N) Exit & Emergency Lighting

LED Exit Sign



View Larger

- LED Exit Sign - This classic LED Exit Sign is clear and highly visible.
- LED Exit Sign features include:
- Superior Quality Exit Sign Combined with LED Energy Saving Technology In a Low-Profile, Unobtrusive Design
 - Standard AC Only and Emergency (battery Backup) Units Available
 - Completely Self-Contained
 - Fully Automatic Operation
 - Compact, Low Profile Design in Neutral Finish
 - Push to Test Switch in Battery Backup Units
 - Automatic, Low Voltage Disconnect (LVD)
 - 120 or 277 VAC Operation
 - Injection-Molded, V-O Flame Retardant, High Impact, Thermoplastic Housing
 - Charge Rate/Power On LED Indicator Light
 - Energy Consumption of Less than 4 Watts for Red Letters and Less than 2 Watts for Green Letters
 - Listed for Damp Location
 - Universal Mounting Canopy & 2 Face Plates for Wall, Side or Top Installation
 - 2.4V 400mAh Ni-Cad Battery On Standard Units
 - 3.6V 1800mAh Ni-Cad Battery On High Output & Remote Capable Units
 - 90 Minute Battery Run Time
 - Models 73022 - 73025 have Remote Capability for up to 2 Additional LED Remote Lamp Heads:
 - 2 heads - 3 hours operation (Base Unit)
 - 3 heads - 2 hours operation (Base Unit + 1 Head)
 - 4 heads - 1.5 hours operation (Base Unit + 2 Heads)
 - CAUTION: Use only LED Remote Lamp Heads with Remote Capable Units
 - UL 924 Listed
 - 5 Year Warranty
 - Order Qty of 1 = 1 Piece

WARNING:
 Cancer and Reproductive Harm
www.P65Warning.ca.gov

Below is more info on our LED Exit Sign

View Catalog PDF Page

ADD TO ORDER

Cat No	Spec Sheet	Voltage	Type	LED Color	Housing	Battery Backup	Min Order Qty	Price	Quantity	Quantity Available
73010		120/277	Standard	Red	White	No	1 Piece	\$30.0000	<input type="text"/>	In Stock
73012		120/277	Standard	Red	White	Yes	1 Piece	\$31.2500	<input type="text"/>	In Stock