

FUSION

P12-250-10

NSF-1 Tested to NSF/ANSI Standards
 Produces 110 Gallons Safe Drinking Water
 (over 100 litros de agua potable segura)

PERFORMANCE CLAIMS

NSF/ANSI PROTOCOL P231	% Reduction
Chlorine	99.9999%
Chlorine Dioxide	99.99%
NSF/ANSI STANDARD 401 (Total Dissolved Solids)	99.95%
Lead	99.30%
Mercury	98.23%
Nitrate	99.80%
Iron	95.38%
Copper	90.29%
Calcium	96.29%
Magnesium	99.43%
Sulfate	98.04%
Fluoride	98.51%
Phosphate	97.25%
Strontium	99.24%
NSF/ANSI STANDARD 53 (Total Organic Carbon)	99.51%
NSF/ANSI STANDARD 53 (Total Organic Halogen)	97.25%
NSF/ANSI STANDARD 53 (Total Organic Nitrogen)	99.24%
NSF/ANSI STANDARD 42 (Total Dissolved Solids)	99.99%
NSF/ANSI STANDARD 42 (Sediments, Rust, Dirt)	97.60%

WARNING - Aluminum Operating
 Temperature: 125°F/52°C, Maximum
 Operating Pressure: 250 psig/17 bar.

ADVERTENCIA - Temperatura máxima de funcionamiento: 125°F/52°C, presión máxima de funcionamiento: 250 psig/17 bar.



Water Filter
 Kinetico Water Systems Corp.
 10000 Highway Road
 Independence, MO 64050 USA

Directions for use:

Place cartridge in an appropriate housing and flush for a minimum of 20 minutes prior to use. Use only with microbiologically safe and adequately disinfected water.