

BRK-LED4-ECO Series

4" Recessed LED Retrofit Trim

DESCRIPTION

4" Recessed downlight retrofit trim with integrated LED power supply and thermal management system. Designed to fit most standard 4" recessed housings.

SPECIFICATIONS

Construction:

- Heat sink and aluminum PCB optimize thermal management
- Durable thermoplastic construction
- E26 Medium screw-base Edison connector provides easy retrofit of incandescent housings
- 4" Square baffle snap-in (accessory)

Optics/LEDs:

- Long-life LEDs with up to 50,000 hours at 70% lumen maintenance
- Choice of 2700K (±145), 3000K (±175), 3500K (±225) or 4000K (±275) color temperatures with 80 CRI
- Produces 550-730 lumens output from luminaire
- Uses high-power, high-quality Cree LEDs

Electrical:

- LED driver dimmable down to 10% with most dimmers
- Save 75% compared to incandescent sources
- 120VAC, 50/60Hz
- Includes socket adapter
- 8 Watts power consumption
- Operating temperatures: -20°C to 40°C (-4°F to 104°F)

Installation:

- Compatible with most 4" recessed cans
- Compatible with non-insulated and airtight ceilings
- Easy installation with integral clips
- Tool-less installation
- Compatible with [BL4ICLED-NND Series](#) 4" recessed housings

Testing & Compliance:

- Tested in accordance with IESNA LM79 & LM80
- ETL Listed for Wet Locations (US and Canada)
- Energy Star Qualified
- Passes FCC Class B

Warranty:

- Five Year Warranty (Terms and Conditions Apply)

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____





Specs at a Glance	
Configuration	BRK-LED4-ECO
Lumens (lm)	550-730
CCT (K)	2700K, 3000K, 3500K, 4000K
CRI	≥80
Input Voltage	120VAC, 50/60Hz
Operating Temp	-20°C to 40°C (-4°F to 104°F)
Certifications	ETL Listed, Energy Star Qualified, Passes FCC Class B
Warranty	5 Years

Note: Environment and application will affect performance. Typical values and 25°C used for testing. Specifications subject to change without notice.

Ordering Information (Example: BRK-LED4-BW-27-ECO)

Series	Color	CCT	Accessory
BRK-LED4	BW = White Baffle	27-ECO = 2700K	LED4-TRMPLT-ECO-SQ = Square Trim (snap-on)
		3-ECO = 3000K	
		35-ECO = 3500K	
		4-ECO = 4000K	

Dimensions



Trim Accessory

