



Bobcat



Bobcat

7324821

VX2T 7324821 10010311
16" x 192CU FT 054CU II
MFG Y BOECAT CO USA

JOB6019

BOMMESE

FADE00



7324321

BOBCAT

FAR60





BOBCAT

Bobcat
Bobcat





Bobcat®

▲ DANGER
ROTATING SHAFT WILL
CAUSE SEVERE INJURY
OR DEATH
Keep shields and guards
in place.

▲ WARNING
OVERSPEEDING OR
IMPROPER OPERATION CAN
CAUSE SERIOUS
INJURY OR DEATH
Do not exceed rated RPM.
Operator's Manual



Bobcat.

West Fargo, ND 58078 USA
www.bobcat.com

MADE IN USA WITH DOMESTIC AND FOREIGN COMPONENTS



SERIAL NO.

* B4UP00671 *

MODEL

ROTARY CUTTER 72



Bobcat®



Bobcat®



⚠ DANGER

Read and understand the operator's manual before operating this machine. Failure to do so may result in injury or death.

Always use proper operating techniques. Do not over-extend the machine's capabilities. Do not attempt to lift or move loads that are not properly secured or balanced.

Always use proper tie-down technique. Use the correct number and placement of tie-downs to secure the load. Do not exceed the rated capacity of the tie-downs.

Always use proper hitching technique. Make sure the hitch is properly secured and the load is properly balanced before towing.

⚠ DANGER

Read and understand the operator's manual before operating this machine. Failure to do so may result in injury or death.

Always use proper operating techniques. Do not over-extend the machine's capabilities. Do not attempt to lift or move loads that are not properly secured or balanced.

Always use proper tie-down technique. Use the correct number and placement of tie-downs to secure the load. Do not exceed the rated capacity of the tie-downs.

Always use proper hitching technique. Make sure the hitch is properly secured and the load is properly balanced before towing.

⚠ DANGER

Read and understand the operator's manual before operating this machine. Failure to do so may result in injury or death.

Always use proper operating techniques. Do not over-extend the machine's capabilities. Do not attempt to lift or move loads that are not properly secured or balanced.

Always use proper tie-down technique. Use the correct number and placement of tie-downs to secure the load. Do not exceed the rated capacity of the tie-downs.

Always use proper hitching technique. Make sure the hitch is properly secured and the load is properly balanced before towing.





FAIR 20



& DANGER
AVOID BLAST OR DEATH
Always use proper tie-off technique.

H15-2A

Soil Conditioner

MADE IN USA

MODEL 48SCM

YEAR 2021

SERIAL NO. *651503918 *

585 lbs (265 kg)



N/A



3500 psi (241 bar)



N/A

WITH DOMESTIC AND FOREIGN COMPONENTS.

Capacity of machine and attachment combination may be less than capacity shown on attachment. Check machine nameplate and load capacity information furnished by the manufacturer for approved use. The capacity of machine and attachment must be compiled with Attachments that are approved for use with Rough Terrain Forklift Trucks comply with ANSI/ITSDF B56.6-2005 and EN-1459-1999.



Bobcat.

P.O. Box 6000
West Fargo, ND 58078 USA
www.bobcat.com




Bobcat

FOR A LIST OF UNITED STATES PATENTS
THAT COVER THIS PRODUCT, GO TO:
www.bobcat.com/patents

SW 19

7245504A enUS



NOT A STEER



▲ DANGER
AVOID INJURY OR DEATH
Operators must stay 20 feet (6 m) away from
hand auger.



Bobcat



NOVASTAR

WARNING: This attachment is not to be used for lifting or carrying loads. It is designed for use as a pallet fork only. See the operator's manual for more information.

...A STEP





NOT A STEP

⚠ DANGER
AVOID INJURY OR DEATH
Do not touch the hydraulic lines.

743
0009

FAK20

116-21 M5HA-1C-293/1





⚠ DANGER
AVOID INJURY OR DEATH
Bystanders must stay 20 feet (6 m) away from chain and auger.

NOT A STEP

MGFA IC-293/1

FAR 20

7432
6400

8
13

Trencher

MADE IN USA

MODEL LT313 Trencher

YEAR 2021

SERIAL NO. *045417400 *

1346 lbs (611 kg)

2150 in (546 mm) 4000 psi (276 bar) N/A

Capacity of machine and attachment combination may be less than capacity shown on attachment. Check machine and load capacity information furnished by the manufacturer for approved use. The capacity of machine and attachment must be compatible with attachments that are approved for use with rough terrain forklift trucks comply with ANSI/BIFMA Z55-2000 and EN-1469-100.

 **Bobcat** P.O. Box 6000
West Fargo, ND 58078 USA
www.bobcat.com 