

Unitex® Sledgehammer Plus Floor Stripper



Send to a Friend

Send to a Friend 

- Handles stripping on the toughest surfaces
- Non-ammoniated formula; for use on resilient and non-resilient tile
- pH: 13.5-14.0; pH at 10% solution: 12.8
- Dilute 16-32 ounces per gallon of water
- Covers 700-1,000 sq ft per gallon

TOTAL QTY: 0
TOTAL PRICE: **\$0.00**

[Add to Cart](#)

PRODUCT NAME	PRICE	QTY
Unitex® Sledgehammer Plus Floor Stripper (1 GL) <small>Item # UN-SHP-01 Mfr. Model # UN-SHP-01 Size: Gallon Qty: 1 Add to My Shopping List</small>	\$31.10	QTY: <input type="text" value="0"/>
Unitex® Sledgehammer Plus Floor Stripper (4 GL) <small>Item # UN-SHP-04 Mfr. Model # UN-SHP-04 Size: Gallon Qty: 4 Add to My Shopping List</small>	\$118.49	QTY: <input type="text" value="0"/>
Unitex® Sledgehammer Plus Floor Stripper (5 GL) <small>Item # UN-SHP-05 Mfr. Model # UN-SHP-05 Size: 5 Gallon Pail Qty: 1 Add to My Shopping List</small>	\$124.91	QTY: <input type="text" value="0"/>

Description 

Sledgehammer Plus is a powerful, high-performance stripper that cuts through multiple layers of finish quickly and effectively.

Description



Sledgehammer Plus is a powerful, high-performance stripper that cuts through multiple layers of finish quickly and effectively.

It solves stripping challenges caused by frequent high-speed burnishing, hard urethane fortified finishes, or excessive buildup on floors.

Its low-foaming formula requires no rinsing and won't leave behind an alkaline residue.

Sledgehammer Plus is non-ammoniated and has a light, fresh scent which makes it an ideal choice for areas where a strong ammonia smell can cause problems, such as hospitals, restaurants, and nursing homes.

Use Sledgehammer Plus for stripping resilient and non-resilient floors.

Use on:

- Asphalt
- Brick
- Concrete
- Quarry
- Rubber
- Sheet vinyl
- Terrazzo
- Vinyl
- Vinyl composition (VCT)

Do not use on:

- Cork
- Linoleum
- Tile in poor condition

Key Specifications:

- Color: Clear, slight amber

Usage



Usage ▼

For normal stripping: Dilute 13 oz per gallon of water (1:10).

For heavy stripping: Dilute 25 oz per gallon of water (1:5).


Specs ▼

Ingredients	Ingredients List
Brand	Unitex
Material	Resilient Tile
Type	Liquid
pH	13.0
Category	Strippers
Condition	new

Video ▼



[Safety Data Sheet \(SDS\)](#)




Safety Data Sheet (SDS) ▼

SAFETY DATA SHEET (SDS) 



SATISFACTION GUARANTEED!

- ✓ Same Day Shipping
- ✓ 100% Money Back Guarantee
- ✓ Service & Repair Centers at All Locations

 Email Insider Signup

Sign Up

Receive technical tips, exclusive deals and invitations to special events



Company Information ▼

Help ▼

Resources ▼

Popular Categories ▼

 Click to Chat

 1-800-400-9473

Live Customer Service
Mon. - Fri. 7 a.m. - 7 p.m. CST



Contact Us





SATISFACTION GUARANTEED!

✓ Same Day Shipping ✓ 100% Money Back Guarantee ✓ Service & Repair Centers at All Locations

✉ Email Insider Signup

Enter your email ...

Sign Up

Receive technical tips, exclusive deals and invitations to special events



Company Information



Help



Resources



Popular Categories



Click to Chat

1-800-400-9473

Live Customer Service
Mon - Fri, 7 a.m. - 7 p.m. CST



Contact Us

