

R-SERIES ACTUATOR

This series of robotic actuators allow engineers and end-users to make custom robotic systems that can be deployed directly into wet/dirty industrial and outdoor environments. R-Series Actuators are sealed to IP67 and are designed with a lightweight and rugged form factor that allows them to be used in challenging field applications.

Each actuator integrates a brushless motor, gear reduction, force-sensing, encoders, and control electronics into a compact package that runs on anything from 24V-48V DC and communicates using standard 100Mbps Ethernet. This keeps the overall robotic system lightweight, low-power, simple, and safe.





The R-Series Actuator is a full-featured robotic component as opposed to a simple servo motor. The output rotates continuously, requires no calibration or homing on boot-up, and contains a thru-bore for easy daisy-chaining of wiring. This enables the actuators to be used in everything from wheeled robots to collaborative robotic arms.

HEBI Robotics provides cross-platform software tools that make configuring and controlling the R-Series a breeze, with features such as live plotting, control from mobile devices like phones and tablets, and APIs for MATLAB, ROS, C/C++, and Python.

Contact: info@hebirobotics.com

R-SERIES ACTUATOR — TECHNICAL SPECIFICATIONS

CONFIGURATION	R8-3	R8-9	R8-16
Peak Torque	7 N-m	20 N-m	38 N-m
Cont. Torque	3 N-m	8 N-m	16 N-m
Max Speed	84 RPM	30 RPM	15 RPM
Mass	670g	685 g	715 g
Dimensions	156mm x 78mm x 51mm		
	15mm hollow bore		
Power	24-48V DC		
	Cont. Current: 1.3 A @ 36V		
	Peak Current: 3.0 A @ 36V		
Environment	-10°C to 50°C Ambient / IP67		
Communication	2X 100 Mbps Plastic Optical Fiber (OptoLock®)		
Angular Resolution	0.005°		
Torque Resolution	0.01 Nm		
Backlash	+/- 0.25°		
Sensing	Angular Position (multi-turn absolute, +/- 4 turns)		
	Angular Velocity		
	Output Torque		
	3-axis Accelerometer / Gyro		
	Temperature		
	Voltage		
	Current		
	Internal Pressure		
API Support	MATLAB (Windows / Linux / OS X)		
	ROS (Linux)		
	Python (Windows / Linux / OS X)		
	C/C++ (Windows / Linux / OS X)		
	C# (Windows)		
		s Actuator includes a standard connection kit.	
Additional technical documentation at docs.hebi.us			
	Updated on June 25, 2019	Specifications subject to change without notic	e.