



Brilliance LED FLEX Strip
B-6X13-30-AC12V

AC12V, 1.8 W/m, 150 mA/m
Waterproof, High output



Light Color or CCT:

- | | | | | |
|---|---------------------------------|--------------------------------|---------------------------------|---------------------------------------|
| <input type="checkbox"/> Red | <input type="checkbox"/> Green | <input type="checkbox"/> Blue | <input type="checkbox"/> Amber | |
| <input type="checkbox"/> Orange | <input type="checkbox"/> Yellow | <input type="checkbox"/> Pink | <input type="checkbox"/> Purple | <input type="checkbox"/> Other: _____ |
| <input checked="" type="checkbox"/> 2700K | <input type="checkbox"/> 3000K | <input type="checkbox"/> 3500K | <input type="checkbox"/> 4000K | |
| <input type="checkbox"/> 4500K | <input type="checkbox"/> 5000K | <input type="checkbox"/> 5700K | <input type="checkbox"/> 6500K | <input type="checkbox"/> Other: _____ |

Jacket Color:

- | | | |
|--------------------------------------|---|--------------------------------|
| <input type="checkbox"/> Transparent | <input checked="" type="checkbox"/> White | <input type="checkbox"/> Black |
|--------------------------------------|---|--------------------------------|

Packing Length:

- | | |
|---|---------------------------------------|
| <input checked="" type="checkbox"/> 25m | <input type="checkbox"/> Other: _____ |
|---|---------------------------------------|

SUITABLE FOR WET LOCATIONS.
SUITABLE FOR OPERATION IN
AMBIENT NOT EXCEEDING 45°C.

Use Only with Class 2 power unit.

Uncoil LED reels before applying power.

CONVIENT AUX EMPLACEMENTS MOUILLÉS.
PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE
AMBIANTE N'EXCÉDANT PAS 45°C.

Utilisez seulement avec la puissance de la Classe 2.
Déroulez Bobines LED avant mettre de l'électricité.