

ANY SPOT®

WIRELESS PERSONAL MONITOR

AS-1100

The AS-1100 is easy to use. The Any Spot® WPM replaces floor wedges and the amplifiers that power them. Simply plug the ANY SPOT® into a 'monitor out' jack on the mixing console, create the desired mix, and it's ready to deliver quality sound. The AS-1100 has 120 selectable UHF frequencies to help locate the best and clearest signal to transmit. The transmitter (AS-1100T) is selectable to either mono or stereo.

The AS-1100R (receiver) features a 100mw headphone amplifier with a standard 3.5mm (1/8") headphone output. The AS-1100R is sure to be plenty loud for any environment. The receiver has a built in limiter & LCD display.

The AS-1100T (transmitter) has two XLR/1/4" combo jacks for its inputs, stereo/mono switch, headphone output, volume control, & LCD display. The transmitter includes a single/dual rack mount kit, for mounting one unit in one rack space or mounting two transmitters side by side in one rack space.

The AS-1100 can be purchased with either of our Ear bud upgrades the EB6 (AS-1106) or the EB10 (AS-1110).

The Any Spot® Series of Wireless Personal Monitors is a great alternative for performers who are tired of lugging around heavy and bulky floor monitors and tired of leaving a gig with ringing ears. The AS-1100 allows the user to move freely around the stage and continue to hear the monitor mix.



AS-1100T

- 120 Selectable UHF Frequencies
- Send a Stereo or Mono Mix to Any Number of Receivers on Stage
- Trouble Free Wireless Connectivity
- XLR to 1/4" Connection From Any Source Device
- Easy to Read LCD Screen with metering
- Input Level Control
- 1/4" Headphone Output with Volume Control for Easy Monitoring

AS-1100R

- High Contrast LCD Screen with Four Bar Battery Indicator
- Rubberized Cover for Slip Resistant Use on Belt or Guitar Strap
- Easy to Set Group and Channel Selection
- Built-in Limiter
- Operates on 2 AA Batteries (up to 5 hours Alkaline)
- Lightweight Titanium Driver EB4 Ear Buds Included

Band Pack System

The AS-1100-4 Band Pack System makes it easy for any band to **Get Personal**. The system includes four receivers and one transmitter. It is designed to get the whole band wireless in one package. The AS-1100-4 will allow a band to send one stereo mix to 4 individuals. Add as many additional receivers as needed.



MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR



ANY SPOT[®]

WIRELESS PERSONAL MONITOR

AS-1100

Specifications:

AS-1100 System

Band: UHF

Frequencies: 120

Transmitter Output Level: 10 mW

Operating Range: Under Typical Conditions 300' (92m)

Note: actual range depends on RF signal absorption, reflection, interference, and battery characteristics

Audio Frequency Response: +/-3dB 70Hz~15kHz

Total Harmonic Distortion: <1% @ 1kHz

Signal to Noise: 85dBA

Maximum Deviation Range: +/-40kHz

Dynamic Range: >90dB A-weighted

Operating Temperature Range: 14°F to 122°F (-10° C to +50° C)

Note: battery characteristics may limit this range

Included Accessories: Power Supply, EB4 Ear Buds, Antenna, Single/Dual Rack Ears, Quick Start Guide

AS-1100T Transmitter

Main Frame Size: EIA STANDARD 1/2U

Modulation Mode: FM Standard Modulation

RF Output: 10 mW

Max Audio input level: +6dBV

Gain Adjustment Range: 40dB

Audio Input: Line Level x 2, XLR/ 1/4" Combo Jack

XLR input: Impedance balanced

Pin: 1 Ground (cable shield)

Pin: 2 Audio +

Pin: 3 No Audio -

Dimensions: 1.5" x 8.3" x 3.78" (38 x 212 x 96 mm) (HxWxD)

Weight: 21 oz. (605 g)

Power Supplied By: 12-18 V DC at 300mA supplied by external power supply

AS-1100R Body Pack Receiver

Audio Output Level: 100mW

Sensitivity: -94dBm for 30dB

Stereo Separation: 40dB (at 1kHz)

Output Connector: 1/8" (3.5mm) Stereo Earphone Connector

Dimensions: 3.74" x 2.6" x 1" (95 x 65 x 25 mm) (HxWxD)

Weight: 3.5 oz (100 g) without batteries

Power Supplied By: 2 (AA) size alkaline or rechargeable batteries

Battery Life: About 5 hours (alkaline)



AS-1100T Transmitter



BACK VIEW



EB4 Ear Buds

AS-1100R

FREQUENCY CODES

CODE D 584-607 MHz

CODE N 518-542 MHz



Specifications subject to change without notice.



MAKERS OF THE ORIGINAL
HOT SPOT PERSONAL MONITOR

601 E. Pawnee Wichita, KS 67211 316. 263.2852 FAX 316.263.0642 www.galaxyaudio.com
Distributed in Canada by Audio Distributors International (ADI) 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
450.449.8177 FAX 450.449.8180

V20190419