



2052-C5050

50/50 PREDILUTED GRN ANTIFREEZE/COOLANT

SYSTEM CAPACITY IN QUARTS QUARTS OF COOLANT PLUS ANTIFREEZE REQUIRED
TEMPERATURES SHOWN IN DEGREES FAHRENHEIT

	4	5	6	7	8	9	10
8	-34	-70	USE MINIMUM 50% FOR -34° FREEZE AND 250°F BOIL TO A MAX.				
9	-21	-50	-82	70% FOR -84°F			
10	-12	-34	-62	-88	8 276°F BOIL PROTECTION		
11	-6	-23	-47	-76			
12		-15	-34	-57	-82		
13		-9	-26	-45	-66	-84	
14		-5	-18	-34	-54	-76	
15			-12	-26	-43	-62	-82

NOTE: DO NOT USE OVER 70% ANTIFREEZE CONCENTRATION

50/50 ANTICONGELANTE / REFRIGERANTE PREDILUIDO

- IMPROVED EXTENDED LIFE TECHNOLOGY
- **TECNOLOGÍA DE VIDA EXTENDIDA MEJORADA**
- ALL MAKES, ALL MODELS
- **TODAS LAS MARCAS, TODOS LOS MODELOS**

-34.6°F ANTIFREEZE PROTECTION

+262°F ANTI BOIL PROTECTION

100% ALL SEASON PROTECTION

6 - 1GALLONS BOTTLES | 6 - 3.78 LTR BOTTLES
TOTAL 6.0 GALLONS | TOTAL 22.68 LITERS

1 GAL (3.78 L) www.techno-fill.com



6

PACK