



**COOL 50%**  
MEETS THE ASTM PERFORMANCE REQUIREMENTS

- ASTMA D4985, D5006, D6250
- ASTMA D2954S, D2955-02a
- GM 4900A & 4900A-1
- GM 4900B & 4900B-1
- GM 4900C & 4900C-1
- GM 4900D & 4900D-1
- GM 4900E & 4900E-1
- GM 4900F & 4900F-1
- GM 4900G & 4900G-1
- GM 4900H & 4900H-1
- GM 4900I & 4900I-1
- GM 4900J & 4900J-1
- GM 4900K & 4900K-1
- GM 4900L & 4900L-1
- GM 4900M & 4900M-1
- GM 4900N & 4900N-1
- GM 4900O & 4900O-1
- GM 4900P & 4900P-1
- GM 4900Q & 4900Q-1
- GM 4900R & 4900R-1
- GM 4900S & 4900S-1
- GM 4900T & 4900T-1
- GM 4900U & 4900U-1
- GM 4900V & 4900V-1
- GM 4900W & 4900W-1
- GM 4900X & 4900X-1
- GM 4900Y & 4900Y-1
- GM 4900Z & 4900Z-1

**MOTOR STAR**

**50/50 PREDILUTED GRN  
ANTIFREEZE/COOLANT**  
50/50 ANTICONGELANTE /  
REFRIGERANTE PREDILUIDO

**CAUTION**  
**NO**   
**STEP**

**2052-C5050**