



DURO

IMPORTANT

Lid must be opened when lighting burners.

IGNITE (HI)

Ignition Button

OFF



LIGHTNING INSTRUCTION
Read instruction before lighting.
Open lid during lighting.
If ignition doesn't occur or 5 seconds burn the burner (controls) OFF wait 5 minutes, and repeat the lighting procedure.

TO LIGHT THE MAIN BURNER
1 Make sure the lid is open.
2 Push the push igniter module Push and turn Main Burner knob slowly to IGNITE (HI). Keep knob pressed in until the burner is lit.
3 If burner doesn't light within 5 seconds, turn the knob to OFF wait 5 minutes, and repeat the lighting procedure or light by match.

OFF



SHUT DOWN
Turn all knobs to OFF.
Turn gas supply OFF.

TURN ON
Gas supply before using appliance.
TURN OFF
Gas supply when appliance is not in use.

SERVICE HOTLINE
1-888/909-8818

OFF




Rear Burner
1 Make sure the lid is open.
2 Push the push igniter module Push and turn Rear Burner knob slowly to IGNITE (HI) hold on until the burner is lit.
3 If burner doesn't light within 5 seconds, turn the knob to OFF. wait 5 minutes and repeat the lighting procedure.
4 Check if it continues to press and hold for another 15 seconds or more until the burner flame stays lit.
5 If burner doesn't light after step 4 turn the knob to OFF wait 5 minutes, and repeat the lighting procedure or light by match.



IGNITE (HI)

IGNITE (HI)

LO



CERTIFIED UNDER ANSI Z39.1/CSA 1.46-01 OUTDOOR COOKING GAS APPLIANCES
FOR OUTDOOR USE ONLY IF STORED INDOORS, DETACH AND LEAVE CYLINDER OUTDOORS.
Minimum clearance from sides and back of unit to combustible construction: 24 inches from sides and 24 inches from back.
DO NOT use this appliance under overhead combustible surfaces.
This appliance can be used with LP gas and natural gas. This appliance is adjusted and shipped for use with LP gas and natural gas. If needed, please refer to "LP-to-NG Conversion" manual for the instructions of gas conversion.
Only the installation in a built-in enclosure constructed of non-combustible materials.

OFF



IGNITE (HI)

LO