



Application Instructions:
Shake well before using. Stir in water to dilute for application. Apply to clean, dry fabric surfaces. Spray or brush on liberally. Allow sufficient time for the sealant to penetrate the fabric. Do not use on leather, vinyl, or other non-fabric surfaces. For best results, use on clean, dry fabric surfaces. For more information, visit www.resistall.com.

RESISTALL NG2
Fabric Sealant
Sellador de Tela
NET CONTENTS:
1 GALLON 3.79 L



Application Instructions:
Shake well before using. Stir in water to dilute for application. Apply to clean, dry paint surfaces. Spray or brush on liberally. Allow sufficient time for the sealant to penetrate the paint. Do not use on leather, vinyl, or other non-paint surfaces. For best results, use on clean, dry paint surfaces. For more information, visit www.resistall.com.

RESISTALL NG2
Spray-On Paint Sealant
Sellador de Pintura
NET CONTENTS:
1 GALLON 3.79 L



Application Instructions:
Shake well before using. Stir in water to dilute for application. Apply to clean, dry vinyl or leather surfaces. Spray or brush on liberally. Allow sufficient time for the sealant to penetrate the surface. Do not use on fabric or other non-vinyl/leather surfaces. For best results, use on clean, dry vinyl or leather surfaces. For more information, visit www.resistall.com.

RESISTALL NG2
Vinyl/Leather Sealant
Sellador de Cuero/Vinilo
NET CONTENTS:
1 GALLON 3.79 L