

RTU 20 L UB WHITE 6TED 22CW N H -096TD5
7703158
409884
2 X 2 BAND 36 X 48 2

FR-600-C



Fortress North America, LLC
4220 Duluth Ave, Suite A
Rocklin, CA 95765
www.FortressFS.com

Emergency Telephone Number:
Chemtel LLC
(800) 255-3924 (North America)
+1 (916) 246-0385 (International)
Telephone Number for Information:
(773) 225-9292

Manufacturing location: Rocklin, CA
Expiration Date: July 2024

Mixing Guide:

- Combine 1 gallon of FR-600 concentrate with 2.4 gallons of water to yield 3.4 gallons of FR-600 ready to use (RTU) retardant
- Combine 5 gallons of FR-600 concentrate with 12 gallons of water to yield 17 gallons of FR-600 RTU

Properly mixed FR-600 RTU should have 16-19% Brix on the refractometer

No significant hazards associated with this material. Handle in accordance with good industrial hygiene and safety practices. Not DOT regulated.

Read SDS before use.
Prevention: Avoid breathing mist/fog/aerosol/spray. Do not eat, drink, or smoke when using this product. Use in well ventilated areas. Wear protective gloves/protective clothing/eye protection/face protection.
Response: Immediate first aid is not likely to be required if on skin, in eyes, inhaled or if swallowed.
If on skin: Flush skin with plenty of water. Remove and wash thoroughly contaminated clothing before reuse.
If in eyes: Flush eyes with water for several minutes. Remove contact if wearing.
If inhaled: Remove from exposure and move to fresh air.
If swallowed: Rinse mouth, drink water. Consult doctor if feeling unwell.
Disposal: Dispose of contents and container according to local, state, and federal regulations.



FR-600-C



Fortress North America, LLC
4220 Duluth Ave, Suite A
Rocklin, CA 95765
www.FortressFS.com

Emergency Telephone Number:
Chemtel LLC
(800) 255-3924 (North America)
+1 (916) 246-0385 (International)
Telephone Number for Information:
(773) 225-9292

Manufacturing location: Rocklin, CA
Expiration Date: July 2024

Mixing Guide:

- Combine 1 gallon of FR-600 concentrate with 2.4 gallons of water to yield 3.4 gallons of FR-600 ready to use (RTU) retardant
- Combine 5 gallons of FR-600 concentrate with 12 gallons of water to yield 17 gallons of FR-600 RTU

Properly mixed FR-600 RTU should have 16-19% Brix on the refractometer

No significant hazards associated with this material. Handle in accordance with good industrial hygiene and safety practices. Not DOT regulated.

Read SDS before use.
Prevention: Avoid breathing mist/fog/aerosol/spray. Do not eat, drink, or smoke when using this product. Use in well ventilated areas. Wear protective gloves/protective clothing/eye protection/face protection.
Response: Immediate first aid is not likely to be required if on skin, in eyes, inhaled or if swallowed.
If on skin: Flush skin with plenty of water. Remove and wash thoroughly contaminated clothing before reuse.
If in eyes: Flush eyes with water for several minutes. Remove contact if wearing.
If inhaled: Remove from exposure and move to fresh air.
If swallowed: Rinse mouth, drink water. Consult doctor if feeling unwell.
Disposal: Dispose of contents and container according to local, state, and federal regulations.

