

AQUAMAX®

D.O.T. CLASS: CHEMICALS, N.O.I., NON D.O.T. REGULATED,

MAY CAUSE EYE AND SKIN IRRITATION.

CAUTION!

BEFORE USING THIS PRODUCT READ THE LATEST MATERIAL SAFETY DATA SHEET

+ FOR CHEMICAL EMERGENCIES INCLUDING SPILLS, LEAKS, FIRE, OR EXPOSURE
CALL CHEMTREC DAY OR NIGHT 1-800-424-9300
413-452-2000 (EASTERN TIME) 8:00 AM – 5:00 PM **+**

PRECAUTION: AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WEAR CHEMICAL GOGGLES OR SAFETY GLASSES AND RUBBER GLOVES WHEN HANDLING.

FIRST AID

EYES: FLUSH WITH PLENTY OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

SPILLS: DIKE TO CONTAIN SPILL. ABSORB OR OTHERWISE COLLECT SPILL AND PLACE IN CONTAINER FOR DISPOSAL.

STORE ABOVE 40 F; THAW AND MIX THOROUGHLY IF FROZEN.

H321

QUALITY CONTROL

NET WEIGHT

1

LBS



HEATBATH CORPORATION
PARK METALLURGICAL CORPORATION
(A SUBSIDIARY OF HEATBATH CORPORATION)



**KEEP FROM
freezing**

STYLE R20
LABORPLASTER® (303) 627-0522 www.labormet.com

Customer Comments:



CHICAGO (773) 373-0800 SPRINGFIELD, MA (413) 452-2000
DETROIT (313) 895-7215

STORE IN
DRY PLACE

↑ ↑
**THIS END
UP**

HAZARD RATINGS

0 = minimal
1 = slight
2 = moderate
3 = serious
4 = severe

HEALTH 2

FLAMMABILITY 0

REACTIVITY 0

PERSONAL PROTECTION X