

 **SAFTI***FIRST*<sup>TM</sup>  
 FIRE RATED GLAZING SOLUTIONS Since 1982

**20 min.**



 **SuperLite I**<sup>TM</sup>

DO NOT REMOVE THIS LABEL UNTIL AFTER FINAL INSPECTION



IMPACT SAFETY-RATED  
 CPSC 16 CFR CAT. II 400 ft. lbs.

 **SAFTI***FIRST*<sup>TM</sup>  
 FIRE RATED GLAZING SOLUTIONS Since 1982

**45/60 min.**



 **SuperLite I-XL**<sup>TM</sup>

INSTALL THIS SIDE AWAY FROM FIRE SOURCE



IMPACT SAFETY-RATED  
 CPSC 16 CFR CAT. II 400 ft. lbs.  
 PROVIDES PARTIAL DIRECTIONAL RADIANT HEAT PROTECTION

 **SAFTI***FIRST*<sup>TM</sup>  
 FIRE RATED GLAZING SOLUTIONS Since 1982

**45 min.**



 **SuperLite II-XL**<sup>TM</sup>





# SAFTI**FIRST**<sup>TM</sup>

FIRE RATED GLAZING SOLUTIONS

Since 1982

## 60 min.



### SuperLite II·XL<sup>TM</sup>



FIRE



RADIANT



SAFETY



THERMAL



PRESSURE



HOSE STREAM



# SAFTI**FIRST**<sup>TM</sup>

FIRE RATED GLAZING SOLUTIONS

Since 1982

## 90 min.



### SuperLite II·XL<sup>TM</sup>



FIRE



RADIANT



SAFETY



THERMAL



PRESSURE



HOSE STREAM



# SAFTI**FIRST**<sup>TM</sup>

FIRE RATED GLAZING SOLUTIONS

Since 1982

## 120 min.



### SuperLite II·XL<sup>TM</sup>



FIRE



RADIANT



SAFETY



THERMAL



PRESSURE



HOSE STREAM