



MINWAX

High Performance
Wood Filler

- Permanently repairs damaged wood
- For both interior & exterior uses

WARNING! COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES,
SKIN & RESPIRATORY TRACT. Before using, carefully read CAUTIONS on back panel.

12 Fl Oz
(354 mL) 3/4 PT

MINWAX® High Performance Wood Filler permanently repairs damaged and rotted wood. This super-strength wood filler is ideal for interior and exterior wood repair projects - from small cracks to major repairs. It also works effectively as a wood adhesive for anchoring screws or securing loose joints in furniture. **MINWAX® High Performance Wood Filler** strongly bonds to wood as well as almost any rigid surface including concrete, metal and fiberglass.

DIRECTIONS FOR USE

WARNING: If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

1 PREPARE: Surface must be clean, dry and free from paint, varnish, dirt and grease. If working with rotted or soft wood, remove loose material and apply **MINWAX® High Performance Wood Hardener** to strengthen wood fibers and to form a solid base for filling.

2 MIX only as much as can be used in 15 minutes. Scoop a golf ball sized amount of wood filler into the plastic cap and squeeze in a thin 3/4 inch long line of wood hardener from the tube. Mix thoroughly.

3 APPLY the mixture immediately to the area to be repaired. Spread on a thin layer followed by a sufficient amount to fill gap. (Note: To fill deep holes, spread on 1/8 inch thin layers one at a time until the hole is filled.) Slightly over-fill to allow for sanding down. Work quickly since the mixture remains workable for about 10 minutes at room temperature.

4 FINISH: After approximately 20 minutes, the repair should be hard enough to be carved and shaped using a sharp modelling knife. Wait at least 30 minutes to sand, plane or file. The hardened wood filler can then be painted or stained. To stain wood filler, see Tips for Staining Minwax® High Performance Wood Filler inside cap sticker. Note: This product absorbs stain differently than wood. Therefore, it is unlikely that exact color match to the original wood will be achieved.

CLEAN-UP: Clean application tools and hands with acetone before wood filler hardens.

CAUTION: CONTAINS CRYSTALLINE SILICA and STYRENE. Contents are **COMBUSTIBLE**. Keep away from heat, sparks, and open flame. **HAZARDOUS**. Use only with adequate ventilation. To avoid overexposure, open windows and doors. If you experience eye watering, headaches, dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Close container after use. Store only in original container. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and seek medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call a physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by repeatedly concentrating and inhaling the contents can be harmful or fatal. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. Contains styrene which may cause cancer based on animal data. This product must be mixed with other components before use. Before opening the packages, **READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.** **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.**

Manufactured for MINWAX COMPANY, Upper Saddle River, NJ 07458
Made and Packaged in U.S.A. Container Made in Canada.
©2000 Minwax Company www.minwax.com 800-523-9299

K5021000





High Performance

Wood Filler

REPAIRS • RESTORES • REBUILDS

• HARDENS IN
15 MINUTES • WILL
NOT CRACK, SPLIT
OR FALL OUT

M4522000B

Can Be Shaped, Carved, Planed, Sanded, Drilled, Screwed & Painted

Para obtener las indicaciones y las precauciones en español, llame al numero de teléfono de Minwax Company que aparece mas abajo.