

# DuoFoam™

with **SELF SEAL** PREMIUM GRADE DISTRIBUTOR



## A D V A N T A G E S

- Polyethylene Foam with special moisture resistant film on both sides
- Economical
- Humidity, Mold and Mildew resistant
- Special moisture resistant film and self sealing tape for additional moisture protection and ease of installation
- Made with recycled materials.

## P R O D U C T S P E C I F I C A T I O N S

### Thickness:

.080 (before film lamination)

### Foam Density:

1.7# Density

Film Thickness: 2.5 mil HD/LD out /1 mil HD/LD in  
(includes self sealing tape and adhesive)

### WVTR (Water Vapor Transmission rate):

.43 g/1002/24 hour day

### Standard roll sizes:

40" x 30.03' (100 sf)  
35 rolls per box

### Stock Colors:

White foam and clear film



## I N S T A L L A T I O N I N S T R U C T I O N S

- Always read the flooring manufacturers recommendations and instructions before installing the underlayment.
- Before rolling out the underlayment, be sure to sweep, vacuum, and remove all debris on the substructure.
- Fill in any significant holes, gaps or breaks that may exist on the substructure.
- Roll out the Underlayment over the substructure surface. To connect the rolls together using the self sealing tape, simply join the extended film lip to the other end of the next roll by peeling off the liner of the adhesive tape and adhering it to the extending film lip.
- Always be sure to connect the rolls together evenly so that the foam is not overlapping each other and there are no wide gaps between the foam.

