



Combination Primary Tillage System

EXCLUSIVE 5-STEP PROCESS

1 REPOSITION RESIDUE

Residue Manager wheels (optional) reposition stalks and residue laterally, just ahead of the coulters, for positive cutting. The 15" diameter wheels are independently mounted and contour over uneven terrain.

2 CUT RESIDUE

Coulter module features ultra-large 25" diameter coulters on 9" spacing for improved residue cutting versus discs. An innovative live hydraulic down pressure system allows the operator to set down pressure to match field conditions.

3 IMPROVE SOIL TILTH

A Split-the-Middle shank pattern, achieved with two ranks of shanks on 18" spacing provides maximum soil fracture and non-stop operation in heavy residue.

4 LEVEL SOIL

The DOMINATOR Disc Conditioner System is hydraulically adjustable to meet varying surface residue requirements. Two rows of discs cut clods and provide additional leveling.

5 FIRM SOIL

The exclusive 24/7® Soil Conditioning Reel accomplishes final clod sizing and soil firming with the ability to select a range of constant down pressure or float position to extend the weather/tillage window.



5 AGRONOMIC STEPS VERSUS 3

The DOMINATOR's 5-function design manages residue, soil tilth and fall seedbed conditions in a series of agronomic processes arranged in a logical sequence. The results far surpass the output of three-function designs which require additional residue sizing or seedbed preparation trips.