

LIFELONG BONDS
START HERE



38



WILDCAT

Bonding Elastomer Waterbase Exterior Primer

TRANS BLUE ONE GALLON / 3.785 LITERS

- Fills
- Blocks Rust
- Blocks Tannin

- Bonds
- Bridges
- Smooths

INGREDIENT	CAS #
Water	7732-18-5
Titanium Dioxide	13463-67-7
Talc	14807-96-6
MICA	12001-26-2
Acrylic Resin	Proprietary

VOC Coating: Not To Exceed
1.19 lbs/gal(100 g/l)

WILDCAT BONDING ELASTOMER WATERBASE EXTERIOR PRIMER

Richard's Wildcat Bonding Elastomer Waterbase Exterior Primer extends the life of exterior paint by bonding to aged paint and bridging the cracks and gaps where paint is aligatored, cracked or peeled. This primer is designed to stick not only to aged paint, but also to bare substrates like wood, Masonite, concrete, stucco, and galvanized and rusted metal. Wildcat Primer will stabilize old paint with a lasting flexible film that can be topcoated with all exterior architectural topcoats. FOR EXTERIOR USE

SUGGESTED PRODUCT USES: Suitable for, but not limited to the following properly prepared substrates;

• **Interior/Exterior** – Gypsum Drywall, Wallboard, Plaster, Wood Trim & Doors, Masonry, Stucco, Concrete, Cinder Block, Brick, Wood Siding, Wood Fencing, Aluminum & Galvanized Metal

SURFACE PREPARATION: General – The entire surface area to be painted should be fully cured, clean, dry, sound and free from dirt, grease, oils, waxes, mildew and any other surface contaminants that may adversely affect the performance of this material. Thorough surface preparation will improve the performance of any coating system.

PREVIOUSLY PAINTED SURFACES: Remove loose, scaling, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing or by power tool cleaning methods, such as electric sanders or grinders, etc. Sand rough paint edges smooth to adjacent surface area. Sand glossy surfaces to dull existing finish. Prime bare surface areas and allow to thoroughly dry before applying finish coatings.

GALVANIZED & NON-FERROUS METAL: It is recommended to allow surface to weather for a minimum of six (6) months then solvent clean per SSPC-SP 1. If weathering is not possible, solvent clean per SSPC-SP 1, and primer accordingly. **DRYWALL:** Insure that the surface is dust & chalk free. **MASONRY / CONCRETE:** All new masonry surfaces should be allowed 30 – 45 days to properly dry/cure in accordance with industry standards. The surface should be tested for pH and alkali levels. Surface should not read higher than 8.5 – 9 level. **WOOD:** New wood surfaces should be painted before installation or immediately after. Do not allow the wood to weather. Weathered wood surfaces should be sanded to a fresh wood surface before coating. Remove any grade stamps or pencil marks from new wood by lightly sanding. Wood moisture content should be below 15% and wood surfaces that have a mill glaze should be sanded to allow for proper adhesion. **MILDEW:** Surface areas affected by mildew should be treated with a commercial mildew removal and/or cleaner product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly. **SURFACE REPAIRS:** Repair/replace any damaged and/or delaminated surface areas with the proper recommended patching and/or building materials. Allow all patching materials to dry thoroughly before application of paint coatings

RECOMMENDED FINISH COATINGS: Wildcat can be topcoated with virtually any type finish, including both water-base and solvent-base coatings. The following Richard's products are recommended finishes for this primer, but are not limited to the products listed below;

Flat – 100 Line, Signature Series 100% Acrylic Int./Ext. Flat House Paint; **Lo- Lustre / Eggshell** – 220 Eternity High Performance Exterior Coating, 130 Line, Signature Series 100% Acrylic Int./Ext. Lo-Lustre House Paint; **Satin** – 400 Line, Signature Series 100%

KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how you can protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-Lead, or log onto www.epa.gov/lead.

DISCLAIMER

LIMITED WARRANTY: Richard's Paint Mfg. Co., Inc. Warrants our products to meet the application, appearance and performance properties stated on the label. This Limited Warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the coating, as described in the directions on the label of this container. If this product is found not to perform as specified, Richard's Paint will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **ALL OTHER WARRANTIES ARE EXCLUDED BY RICHARD'S PAINT MFG. CO., INC., EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

LIMITATIONS: Seller's liability for any reason is expressly limited to reimbursement of the purchase price of the materials sold after proof of purchase is provided to the seller. **THIS WARRANTY EXCLUDES (1) LABOR AND COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OR RESULTING FOR ANY REASON UNDER THE SALE, HANDLING, OR USE OF GOODS SOLD.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state. This Limited Warranty may not be transferred or assigned.



RICHARD'S PAINT MFG. CO., INC.

www.richardspaint.com • 200 PAINT STREET • ROCKLEDGE, FLORIDA 32955