

PRODUCT INFORMATION

Finish	Actual Size	Thickness
Polished	135-7/8" x 78-3/4" (345 cm x 200 cm)	1-1/4" (3 cm) & 3/4" (2 cm)

Not all colors available in alternative finishes. Please contact your local slab center for availability.

Thinner slabs available upon request. Please contact your local slab center to confirm sizes and availability.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

ONE Quartz Surfaces do not meet minimum coefficient of friction thresholds recommended by safety standard-setting organizations. Water, oil, grease, etc., create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

APPLICATION NOTES:

Historic Series not suitable for exterior applications due to small resin content. The sun will etch the material.



Twenty Five Year Commercial Limited Warranty, visit daltile.com for complete warranty details.



Lifetime Residential Limited Warranty, visit daltile.com for complete warranty details.



Made in the USA*

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16"	Medium (V2)

NOTES

ONE Quartz Surfaces products are nonporous, reducing the potential for bacteria growth, resist common food stains and are stronger than natural granite.

ONE Quartz Surfaces products are virtually maintenance free.

ONE Quartz Surfaces products contain natural quartz stone providing consistent color and visual movement. A wide range of color options allow for more design freedom.

ONE Quartz Surfaces products have a durable, scratch-resistant surface.

ONE Quartz Surfaces products are heat and scorch-resistant under normal cooking conditions (use of a trivet is recommended for longer or extreme heat exposure).

Visit daltile.com/ONEQuartz for additional polished, semi-polished, honed and leather finish details.

Twenty-Five year limited warranty. Visit daltile.com/ONEQuartz for details.

White thin-set or mortar is recommended for the lighter colors of ONE Quartz Surfaces tiles.

For information refer to "Factors to Consider" at daltile.com/Factors.

SLAB PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Breaking Strength	C648	1,207 lbs
Compressive Strength (min)	C170	22,082 psi
Abrasion Resistance	C241	60+
Abrasion Wear Index	C501	120
Thermal Expansion	C531	1.2 x 10 ⁻⁵
Water Absorption	C97	.03-0.1%
Flexural Strength	C880	4,744 psi
Ultraviolet Light Resistance	G23	Passes
Stain & Chemical Resistance (24-hour immersion)		No effect

*Made in the USA with imported material.