



Power-FL8



Power-FL10

Description	8" Subwoofer	10" Subwoofer	12"
Driver	8" Polypropylene	10" Polypropylene	12"
Crossover Frequency	40 - 110 Hz Variable; 24 dB/Octave + LFE	40 - 110 Hz Variable; 24 dB/Octave + LFE	40 -
Crossover Type	Low Pass	Low Pass	24 d
Max Power	250 W Cont. / 600 W Max	250 W Cont. / 600 W Max	Low
Freq Response	32 - 150 Hz	22 - 150 Hz	250 W
Dimensions	15.5"H 11.5"W 13"D	16.6"H 12.5"W 15"D	22 - 1
Weight	23 lbs.	30 lbs.	18.5"H 42 lbs

PhaseTech's Solaris series of outdoor speakers meets the challenge of outdoor space. Fully weatherproof and backed by a ten-year warranty, the Solaris series offers performance that is second to none.

Bass response is a component often overlooked in outdoor audio systems. However, how difficult it is to provide good bass reinforcement in large open areas is a well-known problem. PhaseTech tunes up the low-end response in the Solaris series to provide a sound characteristic.

SOLARIS



SPF-15



SPF-25

ation
nce

3" Surface-Mount
8Ω

5.25" Surface-Mount
8Ω

3" D