



Intertek
5014371


Made in EU
Thermally protected
Protection Thermique

ruck
AIR MOVEMENT

Conforms to ANSI/UL Std. 507 and Certified to CAN/CSA Std. C22.2 No. 113

10" Prime

120V ~	I _{max.}	t _A /t _M	P _{1N}	Π _N	
60Hz	1,9A	60/60°C	217W	2950 1/min	ISO F



SN 210125-B00147-10037 ID 147 491 25.01.2021

USE ONLY IN DUCTS WITH HEATED AIR LESS THAN 60 °C (140 °F)

UTILISER UNIQUEMENT DANS DES CONDUITS CHAUFFÉS À AU PLUS 60 °C (140 °F)



WARNING:
Cancer and Reproductive Harm –
www.p65warnings.ca.gov

CAUTION: THIS DUCT FAN SHALL BE INSTALLED A MINIMUM OF ONE METRE FROM ANY ACCESSIBLE OPENING OF THE DUCT

CAUTION: Automatically Operated Device – To Reduce The Risk Of Injury Disconnect From Power Supply Before Servicing.
This fan shall not be installed behind a suspended floor/ceiling or a structural wall, ceiling or floor.

ATTENTION: Ce ventilateur doit être installé à une distance minimale d'un mètre de toute ouverture accessible du conduit.
ATTENTION: Dispositif à fonctionnement automatique. Pour réduire le risque de blessure, débranchez l'appareil de l'alimentation électrique avant d'être servi.