

1-877-754-3435 info@subtechmfg.com



Home Service Products Resources Financing Contact

# PLUMBING PRODUCTS

These cameras include the Intruder series and have a mini or standard size.

Contact Us

## Proprietary Products for Drain Inspection and Leak Detection

We use cookies to ensure that we give you the best experience on our website. If you continue to use this site, you agree to our terms and conditions and privacy policy.



Intruder™ – Standard

Leak Detector  
ST-2000

Intruder™ – Mini



See Details

See Details

See Details

# Intruder™ – Standard

## FEATURES

### Model Specifications

- Line Capacity: 3" to 12" (7cm to 30cm)
- Cable Length 200' up to 300'
- Operating Depth 350 ft. (150psi)
- Resolution 420 TVL Pixels
- 512(H) x 492(V) [PAL 512(H) x 585(V)]
- Sensitivity 0.3 Lux
- Lighting 28 White LED's
- Camera Dimensions: 1.6" x 1.4" (41mm x 36mm)
- Push-Rod Diameter: .48" (12mm)
- Video Format: NTSC
- Power: 110v/60hz AC, 12v DC
- Operating Temperature: 14F to 122F/-10C to 50C



Call for prices

## STANDARD CAMERA

### Intruder™ – Standard Series

#### Standard Equipment

- Rugged & Durable and Professionally Packaged
- Standard Camera
- 200' Push Cable OR 300' Push Cable
- 7" LCD Command Module
- Text Writer, Footage Counter, Picture Inverter
- Light Adjustment, Time/Date
- AC/DC Operation
- 512 Hz Built in Transmitter

#### Available Options

- Built In USB Recorder
- Phone Playback Adapter
- Self Leveling Camera Head
- 18 volt battery receptacle (Battery and Charger not included)
- WIFI to phone or Tablet
- Camera Locator Receiver



OPTION

### Wifi

To mirror the screen so you can see through the camera from your smartphone, tablet or laptop.



Call for prices



OPTION

### USB for Recording

Built-in USB recording: can be added to any camera system.

Call for prices



1 2 Next

## Intruder™ – Mini



FOR SMALLER PIPES

### Intruder™ – Mini Series



**Standard Equipment**

- Professionally Packaged
- Rugged & Durable
- Mini Color Camera
- 7" LCD Command Module
- Light Adjustment, Time/Date
- Microphone
- 512 Hz Built in Transmitter
- Text Writer, Footage Counter, Picture Inverter
- 18 Volt Battery Receptacle (Battery and Charger not included)
- 140' Pushrod OR 200' Pushrod

**Available Options**

- Phone Playback Adapter
- WIFI to phone or Tablet
- Camera Locator Receiver
- Built In USB Recorder
- Self Leveling Camera Head

O P T I O N A L

**ST-SLM-2040 Self Leveling Camera**



1 2 Next





## Water Leak Detector



### LEAK DETECTOR

## ST-2000 Water Leak Detector

### Municipalities & Utilities

Locate leaks on water mains, fire main systems and monitor for future potential water loss.

### Plumbers

Locate water leaks under concrete slabs, in walls, swimming pools or hot tubs.

### Contractors

Locate leaks on new pipeline, pressure failures, residential and commercial water lines.

### FEATURES

## ST-2000 Specifications

- Amplifier Input Impedance: 200K
- Output Impedance: 10 OHM
- Power: 6 AA Alkaline Batteries (1.5 V DC x 6)
- Power Consumption: 60mA Standby (20 hours)
- Amplification: 69 dB/-3.5 dB Distortion: 6.0" x 2.4" x 5.0"
- Weight: 41.0 Ounces
- General Ground Microphone Sensitivity: 0.75 V/G @ 1 KHz
- Probe Microphone Sensitivity: 0.75 V/G @ 1 KHz
- Headphone Impedance: 32 OHM
- Headphone Sensitivity: 102 dB/mW @ 1KHz
- Carry Case: High Density Polyethylene 20." X 13.5" x 9.0"
- Filter Characteristics:
  - 16 Programmable Settings
  - 8th order/ -60 dB Fstop Max
  - 0.025 dB Max ripple
  - 70 Hz 500 Hz Bandpass

Call for prices

(Click image to enlarge)



**OPTION**

### Vloc 3 Locator

- No ghost signals
- Graphical locate display
- Sonde locate and pushrod trace modes
- Optional Bluetooth option for GPS mapping
- High visibility color 4.3"/10cm Display

**OPTION**

### Locator VM-540

- Push button depth
- Operates in 50/60Hz, 512Hz, 640Hz, 33kHz frequencies
- Digital display – Depth, Signal Level, Battery Condition
- Audible tone indicating signal strength
- Simple keypad
- High impact thermoplastic (ABS) injection molded housing
- Carbon fiber reinforced antenna tube
- High rejection of power source interference
- Superior sensitivity over wide temperature range
- Weather resistant – IP54 and NEMA 4 rated
- Enhanced ergonomic design
- 20-Hour Battery Life



Call for prices




## Contact Information

**Subtech Design & Manufacturing Inc.**

2905 Railroad Ave Suite A  
Ceres, CA 95307  
Phone:  
1-209-531-9716  
1-877-754-3435

[Privacy Policy](#)

[Terms and Conditions](#)



## Send us a message

First Name \*

Last Name \*

Phone:

Email Address \*

Message \*

reCaptcha \*

I'm not a robot



Send Message

Please help donate to:



© 2021 Subtech Design & Manufacturing Inc., All rights reserved.

Website by Web Design Just For You