

Plumbing Heating HVAC PEX Fittings Valves Thermostats Electrical Resources Our Team

Are you a Pro? Join Our TRADEMASTER Program! Exclusive Benefits, Absolutely FREE. Apply Now >

Home > Plumbing Supplies > Valves > Solenoid Valves > Hydramotors

Combustion Normally Closed Gas Shutoff Valve Hydramotor Actuator, 2-1/2" Pipe, 86 Cv (120V)

ASCO RedHat

SKU: H118AK122F1 Brand: Asco RedHat Rating: ★★★★★

\$2,715.69 each In Stock Get 1 Thu, Apr 29

[Add to List](#) [ADD TO CART](#)

Plumbing Heating HVAC PEX Fittings Valves Thermostats Electrical Resources Our Team

Are you a Pro? Join Our TRADEMASTER Program! Exclusive Benefits, Absolutely FREE. Apply Now >

Home > Plumbing Supplies > Valves > Solenoid Valves > Hydramotors

Combustion Normally Closed Gas Shutoff Valve Hydramotor Actuator, 2-1/2" Pipe, 86 Cv (120V)

ASCO RedHat

SKU: H118AK122F1 Brand: Asco RedHat Rating: ★★★★★

\$2,715.69 each In Stock Get 1 Thu, Apr 29

[Add to List](#) [ADD TO CART](#)

Free Shipping This item ships free

Easy Returns No restocking fee for 90 days

Product Info Reviews Q&A

Description

The normally closed H118 is a combination hydramotor actuator and safety shutoff/control gas valve. It is used for commercial and industrial burners in applications such as furnaces, dryers, dehydrators, conversion burners and heaters.

The cast iron globe-type valve body features a soft synthetic seat and integral heavy-duty return spring for light and certain closure in one second or less upon current interruption.

The self contained, hermetically sealed, pull-type electro-hydraulic actuator consists of a motor/pump unit immersed in oil, reducing wear and provides highly reliable operation.

Fluid: Fuel Gas - Use with natural, mixed, manufactured, or LP gas. Also suitable for the following service: Scrubbed and dried coke, sewer and digester gases.

Specifications:

- Opening Time: 28 second max.
- Closing Time: 1 second max.
- Enclosure: Type 1 General Purpose standard
- Type 4/2 Watertight/Explosion proof optional
- Ambient Temperature: -40F to 150F (-40C to 66C)
- Body Class: Cast Iron, 1" to 3" - 200# screw, 4" - 120# flange

Questions? Speak with a real person who will go out of their way to help!

888-757-4774

Call Text Chat Email

Open Now: 8am-7:45pm EDT

https://www.supplyhouse.com/Asco-RedHat-H118AK122F1-Combustion-Normally-Closed-Gas-Shutoff-Valve-Hydramotor-Actuator-2-1-2-Pipe-86-Cv-120V 26-APR-2021 25575157.1