

INSTALLATION INSTRUCTIONS



AFWALL® MILLENNIUM™ FLUSHOMETER WALL-MOUNTED TOILETS

Models 3351.101, 3352.101, 3353.101, 3354.101, 2257.101, 2257.101.NAF, 2633.101, 2634.101

Meets the American Disabilities Act Guidelines and ANSI A117.1 Requirements for the Physically Challenged

Thank you for selecting American Standard – the benchmark of fine quality for over 100 years. To ensure this product is installed properly, please read these instructions carefully before you begin. (Certain installations may require professional help.) Also be sure your installation conforms to local codes.

▲ CAUTION: PRODUCT IS FRAGILE. TWO PEOPLE ARE RECOMMENDED FOR HANDLING TO AVOID BREAKAGE AND POSSIBLE INJURY!

NOTE: For proper operation product requires a minimum of 30 psi working line pressure

RECOMMENDED TOOLS AND MATERIALS

Closet Carrier Support
Putty Knife

Regular Screwdriver
Adjustable Wrench

Sealant
Tape Measure

Carpenter's Level
Flush Valve

SAVE FOR FUTURE USE

1 Pictures may not exactly define contour of china

2 FIXTURE MOUNTING
Fixture studs should project 58mm (2-1/4") from face of finished wall.

NOTE: If carrier bolt does not extend or is flush with china, use retrofit caps 7381285-200.0070A (sold separately).

STANDARD BOLT CAP

RETROFIT BOLT CAP



Product names listed herein are trademarks of AS America, Inc.
© AS America, Inc. 2014

7301962-100 Rev. E