


Hoistway Cable

600V Unjacketed Hoistway Cable Power / Signal, Shielded Pairs & Coax



Application:

For use in Elevator Hoistways in accordance with Article 620 of the NFPA 70 "National Electrical Code"

Features:

Flexible Copper Conductors
 Flame Retardant PVC; VW-1 & FT1 Rated
 Optional 20AWG Shielded Pairs and Coaxial Cables
 Stratified Synthetic Binders

Cable Construction:

Flexible Bunch Stranded Bare Copper Conductors
 Flame Retardant Polyvinyl Chloride Insulation
 Optional 20AWG Shielded Pairs and Coaxial Cables
 Contra-Helically Cabled Layers
 Color Coded and Numbered Wire Identification
 Cable is Unjacketed

Technical Details:

Voltage Rating:	600V/300V
Temperature:	60°C
Conductors:	Bare Copper Bunch Stranded ASTM B 174-71
Insulation:	60°C Flame Retardant Polyvinyl Chloride
Color Code:	Color Coded and numbered

Approvals:

(UL) Hoistway Cable
 CSA Hoistway Cable
 NEC Compliant

JM Part Number	Size and Number of Components				Coax	Fiber	Cable Diameter		Weight	
	14AWG (2.08mm ²)	18AWG (.82mm ²)	20AWG Shielded Pair	18AWG Shielded Pair			inches	mm	Lbs/MFt	kg/km
Power/Signal, Shielded Pair & Coax Composite Unjacketed Hoistway Cable 600V										
HC0314	3	-----	-----	-----	-----	-----	0.29"	7.4	59	88
HC0418	-----	4	-----	-----	-----	-----	0.25"	6.4	39	58
HC0718	-----	7	-----	-----	-----	-----	0.32"	8.1	68	101
HC0814SPL	8	-----	-----	-----	-----	-----	0.45"	11.4	158	228
HC1018	-----	10	-----	-----	-----	-----	0.42"	10.7	97	144
HC1218	-----	12	-----	-----	-----	-----	0.46"	11.7	119	177
HC1414	14	-----	-----	-----	-----	-----	0.60"	15.2	222	330
HC1418	-----	14	-----	-----	-----	-----	0.46"	11.7	135	201
HC1618	-----	16	-----	-----	-----	-----	0.53"	13.5	165	245
HC1918	-----	19	-----	-----	-----	-----	0.53"	13.5	184	274
HC2108SPL	-----	21	-----	-----	-----	-----	0.65"	16.5	215	320
HC2418	-----	24	-----	-----	-----	-----	0.63"	16.0	232	345
HC3018	-----	30	-----	-----	-----	-----	0.67"	17.1	291	433
HC3718	-----	37	-----	-----	-----	-----	0.74"	18.7	358	533
HC4218	-----	42	-----	-----	-----	-----	0.84"	21.3	407	606
HC6118	-----	61	-----	-----	-----	-----	0.95"	24.0	591	879
HCC39	4	35	-----	-----	-----	-----	0.82"	20.7	418	622
HCC42	14	24	2	-----	-----	-----	0.96"	24.4	599	891
HCC48LO	6	25	8	-----	1	-----	0.87"	22.0	588	875
HCC49	4	45	-----	-----	-----	-----	0.92"	23.4	515	766
HCC57	4	40	6	-----	1	-----	1.05"	26.7	606	902
HCC62	4	58	-----	-----	-----	-----	1.02"	25.9	641	954
HCC71	6	61	2	-----	-----	-----	1.14"	28.9	786	1170