

FACT™ Cable Termination Unit (CTU) for one cable with max. diameter of 8.5 mm or one flex tube 6-10 mm

- Cable termination kits enable quick and easy termination of most cable sizes and types
- Designed for termination of cables directly onto the FACT panel, allowing the installer to preterminate cables outside the frame

Product Classification

Brand	FACT™
Product Series	FACT
Product Type	Fiber cable termination unit
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America

Environmental Specifications

Environmental Space Indoor


General Specifications

Application	For use with FACT panels
Package Quantity	1
Packaging Type	Bag Carton

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system





TENIO™ Cable Termination Unit kit

Product Classification

Product Type	Cable termination kit
Product Series	TENIO
Regional Availability	EMEA

General Specifications

Package, quantity	1
Packaging Type	Bag Carton

Environmental Specifications

Environmental Space	Outdoor
----------------------------	---------


Regulatory Compliance/Certifications

Agency
RoHS 2011/65/EU

Classification
Compliant



Fiber Closure Cable Termination Unit, Large for up to 16 mm diameter cables



Product Classification

Product Type	Cable termination bracket
Product Series	FIST-MSD TENIO
Regional Availability	Australia/New Zealand EMEA Latin America

General Specifications


Single Cable Diameter, maximum 16.00 mm | 0.63 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



760244935 | CTU-G-GRND



Fiber Closure Cable Termination Unit, Giant for up to 27 mm diameter cables with extra grounding wire

Product Classification

Product Type	Cable termination bracket
Product Series	FIST-MSC TENIO
Regional Availability	Australia/New Zealand EMEA Latin America

General Specifications

Single Cable Diameter, maximum 27.00 mm | 1.06 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

